

FEATURES & SPECIFICATIONS

INTENDED USE

Stylish ceiling/wall mounted luminaire in either white or walnut finish with a variety of lamp combinations and sizes enhanced by linear sided acrylic diffuser. Designed for baths, kitchens, rec rooms, corridors, aisles, stairwells, over or beside mirrors, over bulletin boards, in vanities, in displays.

SIZE W x L x H in inches (mm)

4.50H x 5.62W (115 x 145)

Available in 24, 36, and 48in (610, 915, 1220) lengths

LAMP

1 or 2 Lamp Positions

MOUNTING

Back plate provided with adequate knockouts and mounting holes for either wall or ceiling installation.

MATERIALS & FEATURES

All metal parts are die formed from heavy gauge cold roll steel with overlapping end caps to insure uniformity and dimensional stability. One light and two light units same external dimensions.

DIFFUSER

2 Lamp Positions

WIRING

Standard ballast are 120 volts, 60 hertz.



LISTING

Fixture & Ballast: UL Listed

Ballast: Thermally protected, class P, HPF,

Non PCB

TYPICAL OPTIONS AND ACCESSORIES

Custom finishes, internal divider, front baffle, pull chains, convenience outlets, and Emergency ballasts. CONTACT FACTORY for custom, compact fluorescent night light options. See options page at the end of the T02WallF section, or contact factory for more details.

ORDERING INFORMATION

Example: 555A232DIVMVWH

555	A	2	32	DF	MV		WH
Series	Lens Material	Lamp #	Lamp Type	Divider & Front Shield	Ballast Count	Ballast Count	Finish
555 Lensed wall mount Up/down light	A Clear Prismatic acrylic MW Smooth white acrylic	2 (Lamps not included)	17 24 in. T8 25 36 in. T8 32 48 in. T8	Blank No Divider or Front Shield DIV Divider only F Front Shield only T Top Shield only DF Divider and Front Shield TF Top and Front Shield	MV Electronic, Multivolt (120-277) S Electronic, residential	Blank Single Ballast (1) Dual One Lamp Ballasts	WH White (Standard) OAK Simulated Oak painted finish WAL Simulated Walnut painted finish CH Chrome finish CHEND Chrome finish on end caps only
							Options
							SW Pull chain, 2 way switching (Use with single ballasts)
							GCO Grounded convenience outlet (North American 3 Prong)
							EM Emergency ballast, 500 lumens



Texas Fluorescents
Reinvented

555 Series

Ceiling/Wall Mount Luminaire

DIMENSIONS

All dimensions are inches. Specifications subject to change without notice.

