



## FEATURES & SPECIFICATIONS

### INTENDED USE

The BKR a specification grade wall mount for the bath, stairwells, office, and “over the bed” applications, and is distinguished by excellent lighting distribution and craftsmanship.

### SIZE

W x L x H in inches (mm)

4.48H x 2.56W (85 x 140)

Available in 24, 36, and 48in (610, 915, 1220) lengths

### MOUNTING

Direct wall mount.

### MATERIALS & FEATURES

Housing is die-formed and embossed code 22 gage steel. Standard finish is high reflectance baked white enamel; chrome ends or full chrome body are available as an option. Wiring knockouts are provided on back of housing. Lens is fully captured by end plate.

End cap held in place with acorn nut.

- Standard high reflectance white finish with smooth white lens
- Chrome body, or chrome ends only finishes available.
- Options include prismatic lens, special ballasts, pull chain switches, and convenience outlets.

### TYPICAL OPTIONS AND ACCESSORIES

Custom finishes, pull chains, convenience outlets. See options page at the end of the T02WallIF section, or contact factory for more details.



## ORDERING INFORMATION

Example: BKR MW 48L S24W2200L DMV 40K CHEND

### STANDARD

<b>BKR</b>	<b>MW</b>	<b>48L</b>	<b>S24W2200L</b>	<b>DMV</b>	<b>40K</b>	<b>CHEND</b>
<b>Series</b>	<b>Size</b>	<b>Wattage and Lumen</b>		<b>Driver</b>	<b>Kelvin Temperature</b>	<b>Finish</b>
<b>BKR</b>	24L 24" 48L 48"	<b>S12W1100L**</b>	12 System Watts, 1200 Delivered Lumens	<b>DMV</b> 0-10V	<b>30K</b> 3000K <b>35K</b> 3500K <b>40K</b> 4000K <b>50K</b> 5000K	<b>BLANK</b> White(standard) <b>CH</b> Chrome finish <b>CHEND</b> Chrome finish *on end caps only
Direct wall mount Classic Round Silhouette Fixture		<b>S24W2200L*</b>	24 System Watts, 2200 Delivered Lumens	<b>MV</b> ? gfl - Half 120V-277V		
		*28W not available in 24" length **12W is not available in 48" length				
	<b>LENS</b>					<b>Options</b>
	<b>MW</b> Smooth white acrylic					<b>SW2</b> Pull chain, 2 way switching (Use with single ballast) <b>GCO</b> Grounded convenience outlet (North American 3 Prong) *SW2 and GCO options available for 120V models only.

### HIGH OUTPUT

Example: BKR MW 48L S40W3600L DMV 40K CHEND

<b>BKR</b>	<b>MW</b>	<b>48L</b>	<b>S40W3600L</b>	<b>DMV</b>	<b>40K</b>	<b>CHEND</b>
<b>Series</b>	<b>Size</b>	<b>Wattage and Lumen</b>		<b>Driver</b>	<b>Kelvin Temperature</b>	<b>Finish</b>
<b>BKR</b>	24L 24" 48L 48"	<b>H20W1800L**</b>	20 System Watts, 1800 Delivered Lumens	<b>DMV</b> 0-10V	<b>30K</b> 3000K <b>35K</b> 3500K <b>40K</b> 4000K <b>50K</b> 5000K	<b>BLANK</b> White(standard) <b>CH</b> Chrome finish <b>CHEND</b> Chrome finish *on end caps only
Direct wall mount Classic Round Silhouette Fixture		<b>H40W3600L*</b>	40 System Watts, 3600 Delivered Lumens	<b>MV</b> ? gfl - Half 120V-277V		
		*40W is not available in 24" length **20W is not available in 48" length				
	<b>LENS</b>					<b>Options</b>
	<b>MW</b> Smooth white acrylic					<b>SW2</b> Pull chain, 2 way switching (Use with single ballast) <b>GCO</b> Grounded convenience outlet (North American 3 Prong) *SW2 and GCO options available for 120V models only.

\*Consult for more options

Catalog Number:

Notes:

## DIMENSIONS

