

### FEATURES & SPECIFICATIONS

#### INTENDED USE

Economical, versatile PL wall fixtures in choice of acrylic globes or polycarbonate jar diffusers in white or clear. Wall brackets available in black or white. Consult factory for Energy Star versions.

#### SIZE H x W in inches (mm)

Wall Bracket - 5.25L x 4.50W x 4.50H

Globes - (CAG & WAG) - 6"

Jar - (WPJ & CPJ) - (7W) 5.25", (9W) 7.25", (13W) 8.25"

#### LAMP

1 lamp position

#### MOUNTING

Wall Mounted

#### MATERIALS & FEATURES

- Pocket lanterns are molded of durable plastics.
- Available in black or white finishes.

#### LISTING

Fixture & Ballast: UL Listed

Ballast: Thermally protected, class P, HPF,

Non PCB, UL listed for wet locations

#### TYPICAL OPTIONS AND ACCESSORIES

Photocell may be added to fixtures upon request. See options page at the end of the T02WallF section or contact factory for more details.



Now Available in LED

#### ORDERING INFORMATION

Example: BPW113CPJM120-LP

Item Number	Dimensions (LxWxH)	Lamping
BPW118WAGE120	6" x 6.5" x 8.0"	1-18W Quad 4-Pin
BPW123GUWAG	6" x 6.5" x 8.0"	1-23W GU24
BPW123GUCAG	6" x 6.5" x 8.0"	1-23W GU24
<b>BPWL4W912L40KWAG</b>	<b>6" x 6.5" x 8.0"</b>	<b>4 CREE LED 11W, 912 Lumens, 4000K</b>
BPWL11W912L40KWPJ	6" x 6.5" x 8.25"	11W 912 Lumens, 4000K
BPW13W1000LD12040KCPJ	6" x 6.5" x 8.25"	13W, 1000 Lumens Dimmable 120V
BPWINCLPLEDWHWPJ	6" x 6.5" x 8.25"	Incand. Socket w/LED A19 9.5W 2700K Incl.

Add ES for Energy Star Version and lamps will be included.

#### LED A19/E26 Lamp Include:

- 120V
- 9.5W
- Med Base E26 Base
- 800 Lumens
- Replaces 60W Incandescent or 13W CFL
- CRI 80
- 15,000 Hour Life
- 270 Beam Angle
- 2700K Standard
- (Consult for 4100K)

Consult for other Lamping and LED Options. Choice of globe, CAG, WAG, WPJ, CPJ

#### L900C LED REPLACEMENT PARTS

**L09C-DC-700-04-R** = 4 CREE LED ARRAY  
**IC900-DMV-1** = LED DRIVER

\* DATA PER LM79/LM80/TM21 AVAILABLE UPON REQUEST  
\*\* ESTIMATED FROM LED SOURCE