



Texas Fluorescents
Reinvented

CATALOG#:

PROJECT:

TYPE:

Series EWW

Elliptical Wall Wash Coffered Grid Mount

Specification grade, recessed perimeter elliptical wall wash to highlight wall and shelf mounted goods in commercial and retail environments. Provides uniform VERTICAL surface lighting.

CONSTRUCTION

Housing is die-formed and embossed code 22 gauge steel. Finish is high reflectance baked white enamel. Access plates with wiring knockouts are provided on one side of housing. Ballast is accessed from side through adjacent ceiling tile. Premier full specular reflectors at sides and ends create a professional finish and control the wall wash lighting distribution.

MOUNTING

Recessed inverted T-Bar ceilings. Grid mount

TYPICAL OPTIONS & ACCESSORIES

Whips, fuses, and frame kits. Contact factory for more details



DIMENSIONS

10.62"W x 24.0"L x 4.5"D


10.62"W x 48.0"L x 4.5"D

FEATURES & BENEFITS

- Perimeter highlight for wall and shelf mounted goods
- "Silver" full bright reflectors maximize efficiency, light output, and control wall wash distribution.
- Access plate to simplify installation
- 1 or 2 lamp positions



DRAWINGS & IMAGES



ORDER INFORMATION

SERIES	LAMP POSITION	LAMP TYPE	REFLECTOR	BALLAST & VOLTAGE	OPTIONS
EWW	1 1 Lamp 2 2 Lamps (Lamps not included)	40BX Biaxial (TT5) 2G11 4 Pin 40W	M20 Mirrored Reflector	E120 Electronic 120V E277 Electronic, 277V MV Electronic, Multivolt (120-277)	WP 6 ft. 3 wire 18 gauge whip WP10 6 ft. 4 wire 18 gauge whip EM65 Emergency ballast 650 Lumens