

FSF Series

LED Medium Body Strip with Lens



FEATURES & SPECIFICATIONS

Great Performance Strip Fixture - now available with Lens. This LED offering is perfect for so many applications. Designed economically yet with balance and sleek aesthetics. This fixture is perfect for: Retail, Industrial, Back House applications as well as the perfect solution for Mezzanine low ceiling installations where a wide distribution light pattern is needed. 5 year factory warranty.

MOUNTING

Surface mount, chain hung, double stem.

TYPICAL OPTIONS AND ACCESSORIES

Whips, wireguards, Emergency battery backup (IOTA ILB-CP10HE), or contact factory for more details.

SIZE*

W x L x H in inches

2ft: 4.25W x 24.00L x 3.25H

4ft: 4.25W x 48.00L x 3.25H

8ft: 4.25W x 96.00L x 3.25H

*All dimensions are inches. Specifications subject to change without notice.



2 ft - STANDARD

Example: FSF24LFRZ33W3300LDMV40K

FSF	FR	24L	Z33W3300L	DMV	40K
Series	Lens	Length	Wattage and Lumen	Driver	Kelvin Temperature
FSF	FR Frosted Lens	24L 24"	J14W1400L 14 System Watts, 1400 Delivered Lumens	DMV 0-10V Dimming	30K 3000K 35K 3500K 40K 4000K 50K 5000K
Medium Body Strip			J18W1800L 18 System Watts, 1800 Delivered Lumens		
SMFSF			Z28W2800L 28 System Watts, 2800 Delivered Lumens		
Medium Body Strip with Microwave Sensor			Z33W3300L 33 System Watts, 3300 Delivered Lumens		
					Options
					WP 6 ft. 3 wire 18 gauge whip
					WP10 6 ft. 4 wire 18 gauge whip
					EM10HE 10w Emergency battery backup
					MDT4 Occupancy Sensor

*Consult factory for more options

Catalog Number:
Notes:

FSF Series

LED Medium Body Strip with Lens



4 ft - STANDARD

Example: FSFFR48LJ31W3100LDMV40K

FSF	FR	48L	J31W3100L	DMV	40K
Series	Lens	Length	Wattage and Lumen	Driver	Kelvin Temperature
FSF	FR Frosted Lens	48L 48"	J28W2800L 28 System Watts, 2800 Delivered Lumens	DMV 0-10V Dimming	30K 3000K
Medium Body Strip			J31W3100L 31 System Watts, 3100 Delivered Lumens		35K 3500K
SMFSF			Z48W4800L 48 System Watts, 4800 Delivered Lumens		40K 4000K
Medium Body Strip with			Z57W5700L 57 System Watts, 5700 Delivered Lumens		50K 5000K
Microwave Sensor			Z61W6100L 61 System Watts, 6100 Delivered Lumens		
Options					
WP 6 ft. 3 wire 18 gauge whip					
WP10 6 ft. 4 wire 18 gauge whip					
EM10 10w Emergency battery backup					
EM12 12w Emergency battery backup					
MDT4 Occupancy Sensor					

8 ft - STANDARD

FSF	FR	96L	J48W4800L	DMV	40K
Series	Lens	Length	Wattage and Lumen	Driver	Kelvin Temperature
FSF	FR Frosted Lens	96L 96"	J48W4800L 48 System Watts, 4800 Delivered Lumens	DMV 0-10V Dimming	30K 3000K
Medium Body Strip			J57W5700L 57 System Watts, 5700 Delivered Lumens		35K 3500K
SMFSF			J61W6100L 61 System Watts, 6100 Delivered Lumens		40K 4000K
Medium Body Strip with			Z97W9700L 97 System Watts, 9700 Delivered Lumens		50K 5000K
Microwave Sensor			Z114W11400L 114 System Watts, 11400 Delivered Lumens		
Options					
WP 6 ft. 3 wire 18 gauge whip					
WP10 6 ft. 4 wire 18 gauge whip					
EM10 10w Emergency battery backup					
EM12 12w Emergency battery backup					
MDT4 Occupancy Sensor					

*Consult factory for more options

Catalog Number:
Notes: