

**FEATURES & SPECIFICATIONS**

Stylish ceiling luminaire in either satin nickel or bronze is available in multiple sizes to meet a variety of applications. Matching wall, bath and linear versions make this series ideal for multi-family or hospitality applications.

**MOUNTING**

Back plate provided with adequate knockouts and mounting holes for either wall or ceiling installation.

**CONSTRUCTION**

All metal parts are die-formed from heavy gauge cold roll steel.

**DIFFUSER**

Opal acrylic shade.

**WIRING**

Choice of GU Lamps, Quad Lamps or LED.

**COMPACT FLUORESCENT**

Item Number	Dimensions (L x W x H)	Lamping
HOTCD118GUSN	10" x 10" x 4.25"	1-18W GU MAX
HOTCD118SSN	10" x 10" x 4.25"	1-18W Quad 4 Pin
HOTCD126GUSN	12" x 12" x 4.25"	1-26W GU MAX
HOTCD218GUSN	14" x 14" x 4.25"	2-18W GU MAX
HOTCD218SSN	14" x 14" x 4.25"	2-18W Quad 4 Pin
HOTCD226GUSN	17.75" x 17.75" x 4.25"	2-26W GU MAX
HOTCD226SSN	17.75" x 17.75" x 4.25"	2-26W Quad 4 Pin
HOTCDO232SSN	32.3" x 18.1" x 4.25"	2-FC12T9 (32W CIRC)

Lamps Now Sold Separately. Consult Factory for emergency option and other lamping options.

**LED**

Item Numbers	Input Voltage A1	Watts	Lumens	Finish	Color	Dimensions
HOTCD10L18W1300LD120SN30K	120V Triac dimming	17	1200	SATIN NICKEL	4000	12"Dia x 4.2"H
HOTCD10L18W1300LD120SN40K	120V Triac dimming	18	1400	SATIN NICKEL	4000	12"Dia x 4.2"H
HOTCD12L17W1200LD120SN40K**	120V Triac dimming	17	1200	SATIN NICKEL	4000	12"Dia x 4.2"H
HOTCD12L18W1400LMVSN40K**	120V-277V	18	1400	SATIN NICKEL	4000	12"Dia x 4.2"H
HOTCD14L24W2250LMVSN40K**	120V-277V	24	2250	SATIN NICKEL	4000	14.5"Dia x 4.6"H
HOTCD16L28W2050LMVSN40K**	120V-277V	28	2050	SATIN NICKEL	4000	16"Dia x 4.9"H
HOTCD16L30W2600LMVSN30K	120V-277V	30	2600	SATIN NICKEL	3000	16"Dia x 4.9"H
HOTCD18L33W3300LMVSN40K**	120V-277V	33	3300	SATIN NICKEL	4000	17.8"Dia x 4.9"H



Item Numbers	Input Voltage A1	Watts	Lumens	Finish	Color	Dimensions
HOTCDO32LF28W2050LMVSN40K	120V-277V	28	2050	SATIN NICKEL	4000	32.3"Lx18.1"Wx4.25"H
HOTCDO32LR48W4000LMVSN40K	120V-277V	48	4000	SATIN NICKEL	4000	32.3"Lx18.1"Wx4.25"H

Change 40K to 30K for 3000K color temperature.

\* LED Driver: 120V dimming type or 120V ~ 277V, constant current type

\* Certification: ETL / cETL

\* LED: Nichia or LG, 50,000 hours rating

\* LED Color Temperature: 3000K or 4000K

\* LED CRI: 80 min on 4100K and 3000K

\* Warranty - 5 years

# Spill Ring Series

## Close-to-Ceiling

## HOTCD Series


**LISTING**

Fixtures conform to Underwriters' Laboratories standards for production and are carefully tested prior to packing. UL damp Listed. Consult for Energy Star. LED versions are ETL listed.

**WARRANTY**

LED components have 5 year limited warranty.