



Texas Fluorescents
Reinvented

FEATURES & SPECIFICATIONS

Stylish ceiling luminaire in either satin nickel or bronze is available in multiple sizes to meet a variety of applications. Matching wall, bath and linear versions make this series ideal for multi-family or hospitality applications.

MOUNTING

Back plate provided with adequate knockouts and mounting holes for either wall or ceiling installation.

CONSTRUCTION

All metal parts are die-formed from heavy gauge cold roll steel.

DIFFUSER

Opal acrylic shade.

WIRING

Choice of GU Lamps, Quad Lamps or LED.

COMPACT FLUORESCENT

Item Number	Dimensions (L x W x H)	Lamping
HOTCD118GUSN	10" x 10" x 4.25"	1-18W GU MAX
HOTCD118SSN	10" x 10" x 4.25"	1-18W Quad 4 Pin
HOTCD126GUSN	12" x 12" x 4.25"	1-26W GU MAX
HOTCD218GUSN	14" x 14" x 4.25"	2-18W GU MAX
HOTCD218SSN	14" x 14" x 4.25"	2-18W Quad 4 Pin
HOTCD226GUSN	17.75" x 17.75" x 4.25"	2-26W GU MAX
HOTCD226SSN	17.75" x 17.75" x 4.25"	2-26W Quad 4 Pin
HOTCDO232SSN	32.3" x 18.1" x 4.25"	2-FC12T9 (32W CIRC)

Lamps Now Sold Separately. Consult Factory for emergency option and other lamping options.

LED

Item Numbers	Input Voltage A1	Watts	Lumens	Finish	Color	Dimensions
HOTCD10L18W1300LD120SN30K	120V Triac dimming	17	1200	SATIN NICKEL	4000	12"Dia x 4.2"H
HOTCD10L18W1300LD120SN40K	120V Triac dimming	18	1400	SATIN NICKEL	4000	12"Dia x 4.2"H
HOTCD12L17W1200LD120SN40K**	120V Triac dimming	17	1200	SATIN NICKEL	4000	12"Dia x 4.2"H
HOTCD12L18W1400LMVSN40K**	120V-277V	18	1400	SATIN NICKEL	4000	12"Dia x 4.2"H
HOTCD14L23W1600LMVSN40K**	120V-277V	23	1600	SATIN NICKEL	4000	14.5"Dia x 4.6"H
HOTCD16L28W2050LMVSN40K**	120V-277V	28	2050	SATIN NICKEL	4000	16"Dia x 4.9"H
HOTCD18L33W2400LMVSN40K**	120V-277V	33	2400	SATIN NICKEL	4000	17.8"Dia x 4.9"H



Item Numbers	Input Voltage A1	Watts	Lumens	Finish	Color	Dimensions
HOTCDO32LF28W2050LMVSN40K	120V-277V	28	2050	SATIN NICKEL	4000	32.3"Lx18.1"Wx4.25"H
HOTCDO32LR48W4000LMVSN40K	120V-277V	48	4000	SATIN NICKEL	4000	32.3"Lx18.1"Wx4.25"H

Change 40K to 30K for 3000K color temperature.

* LED Driver: 120V dimming type or 120V ~ 277V, constant current type
 * Certification: ETL / cETL
 * LED: Nichia or LG, 50,000 hours rating

* LED Color Temperature: 3000K or 4000K
 * LED CRI: 80 min on 4100K and 3000K
 * Warranty - 5 years

Spill Ring Series

Close-to-Ceiling

HOTCD Series



LISTING

Fixtures conform to Underwriters' Laboratories standards for production and are carefully tested prior to packing. UL damp Listed. Consult for Energy Star. LED versions are ETL listed.

WARRANTY

LED components have 5 year limited warranty.

Saylite
 2055 Luna Rd. Suite 142 Carrollton, TX 75006
 Phone: 972-247-3171 Fax: 972-247-0200
 www.saylite.com email: sales@saylite.com

Catalog Number:
Notes: