

FEATURES & SPECIFICATIONS

INTENDED USE

A direct lighting fixture that makes a bold statement, complementing design elements such as stone, metal, brick and glass. Industrial look provides a modern aesthetic. Available standard in galvanized steel finish or powder coated black. Mounts with cable kit. Louver is matte silver anodized parabolic.

HOUSING

Die-formed cold rolled steel body with heavy duty construction. Mates with Parabolic louver.

SIZE W x L x H in inches (mm)

8.0W x 49.0L or 98.0L x 6.5H

MOUNTING

Fixtures can be surface mounted to the ceiling or pendant hung by stem or cable. Welded heavy gauge steel flanges can be ordered to accept 3/8" threaded stems. Alignment brackets are available for continuous row mounting.



TYPICAL OPTIONS AND ACCESSORIES Cord sets, whips, occupancy sensors Hanging kits, Wire guards. Contact factory for additional options.

LOUVER

Matte silver anodized, parabolic. with optional slots on the side of louver. End cap complete the finished louvered look

ORDERING INFORMATION

STANDARD

Example: LVS48LF48W5650LDMV40KWHHC301WH

LVS	48L	F48W5650L	DMV	40K	WH	HC301WH
Series	Width		Driver		Finish	
LVS Modern Louvered Industrial Strip	48L 48"		DMV 0-10V Dimming *Field installed-Dimming Wire DMVFID 0-10V Dimming *Factory installed-Dimming Wire		BK Black WH White SI Silver	
Wattage and Lumen				Color Tempertre		
F24W2800L	24 System Watts, 2800 Delivered Lumens			30K 3000K 35K 3500K 40K 4000K 50K 5000K		
F48W5650L	48 System Watts, 5650 Delivered Lumens					
F57W6400L	57 System Watts, 6400 Delivered Lumens					
Options						
			HC301WH	Cable kit with 4' Cable & 3 Wires Power Feed/Cable Incl. and White Canopy		
			HC302WH	Cable kit with 12' Cable & 3 Wires Power feed/Cable Incl. and White Canopy		
			HC3015WWH	Cable kit with 4' Cable & 5 Wires Power Feed/Cable Incl. and White Canopy		
			HC3025WWH	Cable kit with 12' Cable & 5 Wires Power feed/Cable Incl. and White Canopy		
			2SCS24WH	Two Stem kits with 24" Stem, Canopy and Mounting hardware for a 4' fixture		

HIGH OUTPUT

LVS	48L	H72W8200L	DMV	40K	WH	HC301WH
Series	Width		Driver		Finish	
LVS Modern Louvered Industrial Strip	48L 48"		DMV 0-10V Dimming *Field installed-Dimming Wire DMVFID 0-10V Dimming *Factory installed-Dimming Wire		BK Black WH White SI Silver	
Wattage and Lumen				Color Tempertre		
H72W8200L	72 System Watts, 8200 Delivered Lumens			30K 3000K 35K 3500K 40K 4000K 50K 5000K		
Options						
			HC301WH	Cable kit with 4' Cable & 3 Wires Power Feed/Cable Incl. and White Canopy		
			HC302WH	Cable kit with 12' Cable & 3 Wires Power feed/Cable Incl. and White Canopy		
			HC3015WWH	Cable kit with 4' Cable & 5 Wires Power Feed/Cable Incl. and White Canopy		
			HC3025WWH	Cable kit with 12' Cable & 5 Wires Power feed/Cable Incl. and White Canopy		
			2SCS24WH	Two Stem kits with 24" Stem, Canopy and Mounting hardware for a 4' fixture		

*Consult for more options

LVS Series

Modern Louvered Industrial Strip



ORDERING INFORMATION

STANDARD

Example: LVS96LF97W11300LDMV40KWHHC301WH

LVS	96L	F97W11300W	DMV	40K	WH	HC301WH
Series	Width		Driver		Finish	
LVS Modern Louvered Industrial Strip	96L 96"		DMV 0-10V Dimming *Field installed-Dimming Wire DMVFID 0-10V Dimming *Factory installed-Dimming Wire		BK Black WH White SI Silver	
	Wattage and Lumen			Color Tempertre		
	F48W5650L 48 System Watts, 5650 Delivered Lumens			30K 3000K 35K 3500K 40K 4000K 50K 5000K		
	F97W11300L 97 System Watts, 11300 Delivered Lumens					
	F114W12800L 114 System Watts, 12800 Delivered Lumens					
					Options	
					HC301WH Cable kit with 4' Cable & 3 Wires Power Feed/Cable Incl. and White Canopy	
					HC302WH Cable kit with 12' Cable & 3 Wires Power feed/Cable Incl. and White Canopy	
					HC3015WWH Cable kit with 4' Cable & 5 Wires Power Feed/Cable Incl. and White Canopy	
					HC3025WWH Cable kit with 12' Cable & 5 Wires Power feed/Cable Incl. and White Canopy	
					2SCS24WH Two Stem kits with 24" Stem, Canopy and Mounting hardware for a 4' fixture	

HIGH OUTPUT

LVS	96L	H144W16450L	DMV	40K	WH	HC301WH
Series	Width		Driver		Finish	
LVS Modern Louvered Industrial Strip	96L 96"		DMV 0-10V Dimming *Field installed-Dimming Wire DMVFID 0-10V Dimming *Factory installed-Dimming Wire		BK Black WH White SI Silver	
	Wattage and Lumen			Color Tempertre		
	H144W16450L 144 System Watts, 16450 Delivered Lumens			30K 3000K 35K 3500K 40K 4000K 50K 5000K		
					Options	
					HC301WH Cable kit with 4' Cable & 3 Wires Power Feed/Cable Incl. and White Canopy	
					HC302WH Cable kit with 12' Cable & 3 Wires Power feed/Cable Incl. and White Canopy	
					HC3015WWH Cable kit with 4' Cable & 5 Wires Power Feed/Cable Incl. and White Canopy	
					HC3025WWH Cable kit with 12' Cable & 5 Wires Power feed/Cable Incl. and White Canopy	
					2SCS24WH Two Stem kits with 24" Stem, Canopy and Mounting hardware for a 4' fixture	

*Consult for more options

Catalog Number:
Notes: