



Texas Fluorescents
Reinvented

SH PES SERIES

High Efficiency Surface Parabolic



This new High Efficiency Surface Parabolic combines the comfortable distribution of light associated with a standard parabolic with the high efficiency options of LED. Available in a choice of 2" white or semi-specular louvers in a shallow body less than 4" deep, this fixture provides superior efficiency. The white louver gives the luminaire a broad light distribution that evenly illuminates all surfaces in the space, which creates a comfortable balanced brightness for the occupants. The semi-specular louver provides the more classic appearance and higher efficiency than the standard parabolic. Use 2 lamps instead of 3 lamps in the 6 cell 2x2 configuration and 12 cell 2x4 configuration to save energy over the typical 3 light standard parabolics.

X1 LED version allows the benefits of LED, long life, energy savings and superior lighting without any ballast/driver to fail. With X1 LED, LED T8 lamps are easy to change and upgrade whenever required.

CONSTRUCTION

Housing is die-formed and embossed code 22 gauge steel. Finish is high reflectance baked white enamel. Wiring knockouts are provided on back and end of housing. Ballast cover or reflector snaps into place; no tools required for ballast access. Louvers formed from aluminum are available in a semi-specular silver or baked white enamel finish. Choice of a variety of cell configurations and are held closed by two positive cam latches. Premium, full specular reflectors are available as an option to increase efficiency or modify lighting distribution. Overlay lens can also be added for additional lamp shielding.

SIZE W x L x H in inches
22.65"W x 22.65"L x 3.7"H
22.65"W x 46.75"L x 3.7"H



X1 LED

The most economical, practical and user friendly series of LED fixtures with the energy savings, quality of light, long life and hassle-free maintenance. X1 LED fixtures are UL Listed with the latest LED T8 Bypass lamps. Fixtures provide over 44% energy savings over comparable fluorescent fixtures utilizing less expensive fixtures than the fluorescent version (no ballast required) and have flexibility to change wattage and color temperature any time. Fixture performance will evolve over time with the evolution of the T8 LED lamp technology. Concerned about maintenance with an LED array and driver fixture, X1 LED solves that by utilizing a self contained LED lamp that fits into fixture just like a fluorescent lamp.

Lamp Specifications:

Our T8 LED lamps are available in 2 or 4 ft sizes in different wattage, lumens and color temperature options. Savegreen Lighting is a premier supplier of LED T8 lamps and makes a variety of Bypass T8 lamps to meet the needs of your special application. Options include more energy efficient 12W, 15W and 17W lamps with Premium 10 Year warranty as well as high output options up to 3500 lumens. Double ended LED T8 lamps are also available. See lamp options and specs at www.savegreenlighting.com.

Optional Dimming Options:

The 4 FT lamps are available with two dimming options; Specially designed dimming lamps require an external driver that runs 1 or 2 lamps. So more than 2 lamps require multiple external drivers or Consult for Bypass Type B lamps that can be dimmed without any external driver and dim with standard 2 wire dimming. See dimming options and specs at www.saylite.com.

Emergency Options:

The standard X1 LED Lamps require an inverter or an All-in-one emergency kit that includes LED array, battery and driver. Dimmable T8 LED with external driver works with standard LED EM. For a 5 watt inverter that is similar to adding a 500 Lumen emergency in a conventional fluorescent fixture, add "INV5W" to the end of the item number. This will allow 5 watts of one lamp to work in emergency mode. Or add "EMKT12" to the end of the item number to get a 12W stand alone emergency kit in the fixture that comes with a driver, battery and small LED array that works in Emergency mode. See emergency options and specs at www.saylite.com.



Saylite, Texas Fluorescents Revisited

2055 Luna Rd. Suite 142 Carrollton, TX 75006
Phone: 972-247-3171 Fax: 972-247-0200
www.saylite.com email: sales@saylite.com

Catalog Number:
Notes:



Texas Fluorescents
Reinvented



Ordering Options

(Fixtures below include LED T8 Lamp LT8ABP48L18W2250LXXK. For Other Lamp Options See below and Replace LNXXX with short code below. Specify without Lamps by removing LNXXX)

ITEM NO.	DESCRIPTION
SHPES9C217X1LN15W40	2x2 3750 Lumen Surface Parabolic 9C w/2x15W LED T8 4000K Lamps Included
SHPES9C317X1LN15W40	2x2 5625 Lumen Surface Parabolic 9C w/3x15W LED T8 4000K Lamps Included
SHPES9C417X1LN15W40	2x2 7500 Lumen Surface Parabolic 9C w/4x15W LED T8 4000K Lamps Included
SHPES12C232X1LN18W40	2x4 4500 Lumen Surface Parabolic 18C w/2x18W LED T8 4000K Lamps Included
SHPES18C232X1LN18W40	2x4 4500 Lumen Surface Parabolic 18C w/2x18W LED T8 4000K Lamps Included
SHPES18C332X1LN18W40	2x4 6750 Lumen Surface Parabolic 18C w/3x18W LED T8 4000K Lamps Included
SHPES18C432X1LN18W40	2x4 9000 Lumen Surface Parabolic 18C w/4x18W LED T8 4000K Lamps Included

Change 40 to 35 or 50 for different Kelvin. Change Lamp Wattage to 13W on 2FT or 15W on 4FT
Change SHPES to SHPEW for White Louver

For 5W Emergency, Add INV5 at the End of Item Number for KTEMRGLED5500AC. See other options at www.saylite.com
For fixtures wired for double ended lamps, change X1 to X2 and see the Savegreen Lamps below for the proper Double Ended Lamp.
For fixtures without lamps included, remove the "LNXXX" at the end of the item number and have X1 or X2 for Single or Double Ended wiring.

LN18W40 - Lamp Specification

50,000 Hour Life with 5 Year Warranty
Beam Angle 140 Degree
Aluminum Base and Aluminum Housing with Glass Cover
Operating Temperature: - 20C to 50C
Color Temperature: 3500K, 4000K, 5000K
G13 Pins (Same as Fluorescent Linear T8 Bipin)
AC100 – 277V without Ballast
Single Ended or Double Ended Power (If not specified use X1 Single Ended Power)

Savegreen T8 or T5 LED Lamp Options

To include one of these lamps in fixture, remove "LNXXX" and add Savegreen Inside code below.
(See www.savegreenlighting.com for specification sheets or more information on these lamp options.)

VERSION	SAVEGREEN INSIDE	SAVEGREEN ITEM NO.
Popular	SGB15W35	LT8BG48L15W1740LXXK
Standard	SGS29W35	LT8BGC24L9W1050LXXK
Standard	SGS312W35	LT8BGC36L12W1200LXXK
Standard	SGS15W35	LT8BGC48L15W1740LXXK
Premium	SGP12W35	L10T8BGC48L12W1750LXXK
Premium	SGP15W35	L10T8BGC48L15W2000LXXK
Premium	SGP18W35	L10T8BGC48L18W2500LXXK
High Output	SGH26W40	LT8BGC48L26W3500LXXK
Double Ended	SGD18W35	LT8BDGC48L18W2100LXXK
T5HO	SGT525W40*	LT5BG46L25W3300LXXK
Magic	SGM18W35K	LT8ABP48L18W2250LXXK
Magic	SGM18W35K	LT8ABP48L15W1875LXXK
Magic	SGM215W35K	LT8ABP24L15W1875LXXK

Change 35 to 40 or 50 for different Kelvin. *For T5, CCT 40K and 50K available.

10-YEAR
WARRANTY



Saylite, Texas Fluorescents Revisited

2055 Luna Rd. Suite 142 Carrollton, TX 75006
Phone: 972-247-3171 Fax: 972-247-0200
www.saylite.com email: sales@saylite.com

Catalog Number:
Notes: