

### APPLICATIONS

A direct/indirect lighting fixture that makes a bold statement by complementing design elements such as stone, metal, brick and glass. Industrial look provides a modern aesthetic. Available standard in white finish with matte silver anodized parabolic louver. Mounts with cable kit.

### FEATURES & BENEFITS

- ◆ Available standard in white finish or powder coated black
- ◆ Mounts with cable kit
- ◆ Size: 6.0W x 48.0L x 5.25H
- ◆ 5 year warranty

### SPECIFICATIONS

Die-formed cold rolled steel body with heavy duty construction. Fixtures can be surface mounted to the ceiling or pendant hung by stem or cable. Welded heavy gauge steel flanges can be ordered to accept 3/8" threaded stems. Alignment brackets are available for continuous row mounting.



### ORDERING DATA

EXAMPLE: DLV6132MVWHEM-H4W

DLV6							
Series	Ballast	Finish	Options	Cord/Canopy Finish			
<b>DLV6</b> Louvered Industrial Strip	<b>MV</b> 120-277VAC <b>120</b> 120V <b>277</b> 277V	<b>WH</b> White <b>BK</b> Black <b>SI</b> Silver	<b>EM</b> Emergency Battery Pack 10W ~ 1300 Lumens <b>EM5</b> Emergency Battery Pack 5W ~ 650 Lumens <b>EM7</b> Emergency Battery Pack 7W ~ 900 Lumens <b>LED</b> Wired 1 end hot for T8 LED tubes* <b>LED2E</b> Wired 2 ends hot for T8 LED tubes* <small>*Assembled with no ballast, made for UL listed, self ballasted retrofit LED lamps</small>	<b>WH</b> White <b>BK</b> Black <b>BKWH</b> Black cord/white canopy	<b>Optional/Cable Kit</b>		
<b># of Lamps</b> 1 1 lamp 2 2 lamps	<b>Lamp Type</b> <b>28</b> 46" T5 <b>32</b> 48" T8 <b>39</b> 36" T5HO <b>54</b> 46" T5HO <b>28TAN</b> 46" Tandem T5 <b>32TAN</b> 48" Tandem T8 <b>54TAN</b> 46" Tandem T5HO				<b>H4W</b> Cable kit with 4' cable & power feed/0-10V dimming		
				<b>H4W5</b> Cable kit with a 4' cable & power feed/0-10V dimming (5 wire)			
				<b>H12W</b> Cable kit with 12' Cable and Power Feed/0-10V dimming			
				<b>H12W5</b> Cable kit with a 12' Cable and power feed/0-10V dimming (5 wire)			
				<b>2SCS24WH</b> Two stem kits with 24" stem, canopy, and mounting hardware for a 4' fixture			
<small>**See chart below for whip &amp; cord ordering options</small>							

**Cord & Whip Ordering Chart (Add to End of Fixture Part Number)						
Part No.	# of Wires	Length	End Fitting	Finish	Voltage	Amps (TL Only)
<b>WP</b> - Whip	<b>(Blank)</b> 3 Wire	<b>(Blank)</b> 6 feet	<b>(Blank)</b> No Plug	<b>BK</b> - Black	<b>(Blank)</b> 120-277V	<b>15</b> - 15 Amps
<b>CS</b> - Cordset	<b>4</b> - 4 Wire	<b>8</b> - 8 feet	<b>P*</b> - Standard Plug	<b>WH</b> - White	<b>120</b> - 120V	<b>20</b> - 20 Amps
	<b>5</b> - 5 Wire	<b>10</b> - 10 feet	<b>TL*</b> - Twist Lock		<b>277</b> - 277V	
	<b>6</b> - 6 Wire	<b>12</b> - 12 feet			<b>347</b> - 347V	
		<b>15</b> - 15 feet			<b>480</b> - 480V	



Dimensions and specifications subject to change without notice.