

APPLICATIONS

Decorative surface mounted luminaire provides unique floating cloud appearance. Ideal for kitchens, hallways, lobbies and areas requiring diffused soft light.

FEATURES & BENEFITS

- ◆ **P³ Technology - Post Powder Paint**
- ◆ > 90% reflectivity
- ◆ Corrosion and scratch resistant
- ◆ Smooth edges for easy handling
- ◆ Flat surfaces and square corners provide a contemporary styling
- ◆ White opal acrylic wraparound diffuser
- ◆ Diffuser self-aligns and hinges from either side for easy maintenance and re-lamping
- ◆ Black finish optional
- ◆ Clean appearance with no exposed fasteners
- ◆ Available with two and four lamps
- ◆ High impact resistant "Indestruct-A-Puff" (standard on MC9 and MC15)
- ◆ **C** prefix designates the fixture and lens are in one carton
- ◆ **UL** listed for damp location



SPECIFICATIONS

Housing is die-formed and spot welded, 22 gauge cold rolled steel. Finish is high reflectance white with **P3 - Post Powder Paint**. Ballast cover snaps into place eliminating the need for tools when accessing the ballast. Diffuser hinges from either side in a lift and shift manner and is self-centering. Mounts over electrical junction box. Mounting holes are provided within offset to prevent distortion of housing when tightening mounting fasteners. The soft matte opal white acrylic diffusers provide even illumination. Listed by and bears **UL** label.



NOTE: Order Fixture & Lens

ORDERING DATA

EXAMPLE: MC9232MVB1 & L1037

MC	24	2	32	MV	B1
Series MC	Lamp Position 9 (9" wide) 15 (15" wide)	# of Lamps 2 2 Lamp 4 4 Lamp	Lamp Type 17 24" T8 28 46" T5 32 48" T8 54 46" T5HO U32X 6" U-bent T8 (2x2 only) U32Y 1 5/8" U-bent T8 (2x2 only)	Ballast Type MV Electronic 120V to 277V 120V Electronic 120V 277V Electronic 277V R120 Residential Electronic 120V PMV Program Start Multivolt	

Brands

Code No.	Description
A	Advance
G	GE Ballast
L	Lutron
S	Sylvania Ballast
U	Universal

Performance Levels

Ballast			
Manufacturer	Standard - Leave blank if no preference	High Efficiency Instant Start	High Efficiency Program Start
Advance (A)	Centium ICN (A)	Optanium (AL, AN, AH)	Optanium PS (APL, APN ???)
GE (G)	Proline GE (G)	UltraMax (GL, GN, GH)	UltraStart (GPL, GPH, GPH)
Osram/Sylvania (S)	Quicktronic Pro (S)	Quicktronic QHE (SL, SN, SH)	ProStart (SPL, SPN, SPH)
Universal (U)	ULT STD Electronic (U)	HP Electronic (UL, UN, UH)	AccuStart (UPI, UPN, UPH)

Options

- B1** T8/T5 1L 500 Lumens Battery Backup (B11)
- B2** T8/T5 1L/2L 700 Lumens Battery Backup (B48)
- B3** T8/T5 1L/2L 1400 Lumens Battery Backup (B223)
- B51** T5HO 1L 500 Lumen Battery Backup (B625)
- B52** T5HO 1L 800 Lumens Battery Backup (B585)
- B53** T5HO 1L 1300 Lumens Battery Backup (B626)
- 11** Dual Ballasts 1 Lamp + 1 Lamp
- 21** Dual Ballasts 2 Lamp + 1 Lamp
- 22** Dual Ballasts 2 Lamp + 2 Lamp
- 31** Dual Ballasts 3 Lamp + 1 Lamp
- RIF** Radio Interference Filter

*Battery Backup (#) if ordering separately
 *Lamps purchased separately.
 *Call for additional options

To order fixture and lens together, drop M. Example: Order C9-232R120

Dimensions and specifications subject to change without notice.

CAT#	
JOB NAME	TYPE

DIMENSIONS

INDESTRUCT-A-PUFF



HOUSING	LENS	NOMINAL SIZE
MC9-232	L1037	9" x 4'
MC15-417	L1039	15" x 2'
MC15-432	L1038	15" x 4'
*C9-232	Incl.	9" x 4'
*C15-417	Incl.	15" x 2'
*C15-432	Incl.	15" x 4'

*C prefix designates the fixture and lens are in one carton

Dimensions and specifications subject to change without notice.