



JOB NAME:

CAT#:

TYPE:

APPLICATIONS

This surface mounted corridor fixture features low brightness linear sides. For use in indoor applications, such as hallways, bathrooms, aisles and stairwells.

Screw fastened end caps secure the white opal acrylic wraparound diffuser in place. The 15-LED is capable of single or continuous row mounting. Housing and ends are die-formed cold rolled steel. Finish is high reflectance baked white enamel. The wraparound, extruded, ribbed, white, opal diffuser is designed for durability and visual comfort. The 15-LED mounts over the electrical junction box. Mounting holes are provided. Knock-outs are provided for stem mounting.



FEATURES & BENEFITS

- Available in 4.62"W x 24.0"L x 4.5Dp or 4.62"W x 48.0"L x 4.5Dp
- White opal acrylic wraparound diffuser
- Single or continuous row mounting capability
- Steel housing with white enamel finish
- Every fixture individually tested
- _cETL_{US} listed for damp location

ORDERING

EXAMPLE: 15 24 LED 24 DMV 30

15		LED		DMV	
1. SERIES	2. SIZE	3. GEAR	4. WATTAGE/LUMENS	5. DRIVER	6. COLOR TEMP
15	24 24"	LED	24 in.	DMV 120-277V Multivolt 0-10V Dimmable	30 3000K
LED Corridor Light	48 48"		24 24 Watts 2400 Lumens		35 3500K
			31 31 Watts 3100 Lumens		40 4000K
			48 in.		50 5000K
			48 48 Watts 4800 Lumens		
		62 62 Watts 6200 Lumens			

Dimensions and specifications subject to change without notice.

