

### APPLICATIONS

Surface mounted corridor fixture with low brightness linear sides. Vandal resistant. For use in indoor applications, such as hallways, bathrooms, aisles and stairwells.

### FEATURES & BENEFITS

- ◆ Available in 4.62"W x 24.0"L x 4.5Dp or 4.62"W x 48.0"L x 4.5Dp
- ◆ White opal acrylic wraparound diffuser
- ◆ Single or continuous row mounting capability
- ◆ Steel housing with white enamel finish
- ◆ Every fixture individually tested
- ◆ UL labeled for damp location

### SPECIFICATIONS


White opal acrylic wraparound diffuser. Screw fastened end caps secures diffuser in place. Single or continuous row mounting capability. Steel housing with white enamel finish. Housing and ends are die-formed cold rolled steel. Finish is high reflectance baked white enamel. Wraparound extruded ribbed white opal diffuser designed for durability and visual comfort. Diffuser is held in place on both ends by the screw fastened end caps. End caps may be removed for continuous row mounting with the use of optional joiner assembly. Mounts over electrical junction box. Mounting holes are provided. Knock-outs are provided for stem mounting. Listed by and bears UL label.



### ORDERING DATA

**EXAMPLE: 44-48LED48DMV40**

Series	Lamp #	Lamp Type	Ballast Type	Options
15 Corridor Light	1 1 lamp	15 18" T8 17 24" T8 25 36" T8 32 48" T8 32TAN 2-48" T8 Tandem	R120 Residential Electric T8 MV Multivolt	B1 Battery Backup 1 Lamp RIF Radio Interference Filter



Dimensions and specifications subject to change without notice.

