



Texas Fluorescents
Reinvented

CATALOG#: _____
PROJECT: _____
TYPE: _____

Series S

LED Open Strip (2.75" WIDE)

The S Series is a narrow body LED strip for interior warehouse, retail, and utility areas requiring general illumination. The fixture is designed in a commercial-quality, narrow strip configuration.

CONSTRUCTION

Housing is die-formed and embossed code 22 gauge steel. Finish is high reflectance baked white enamel. Wiring knockouts are provided on back, side, and end of housing.

MOUNTING

Surface mount, chain hung, double stem.

TYPICAL OPTIONS & ACCESSORIES

Emergency battery backup available. Finishes available in standard white, black or silver, plus custom finishes available upon request. Cord sets, whips, wire guards, occupancy sensors. Contact factory for more details.



DIMENSIONS

2ft. - 24"L x 2.75"W x 2"H

4ft. - 48"L x 2.75"W x 2"H

8ft. - 96"L x 2.75"W x 2"H

Consult factory for custom length options

FEATURES & BENEFITS

- Fully assembled housing is formed and welded, 22 gauge steel
- Available in white, black or silver standard finishes; consult factory for custom finish options
- Option of smooth frosted lens to maximize light output
- Available in many lumen packages / wattages, through use of programmable drivers
- Multiple Kelvin temperatures; consult factory for RGBW option
- Recommended for retail and commercial applications, warehouses and utility areas requiring general illumination
- Suitable for dry or damp locations
- >50,000 hrs of L70 LED life
- CRI >80
- Power Factor >0.90
- 0-10 Volt dimmable 120-277V (120 ELV/TRIAC avail)
- Emergency battery backup available
- 5 year warranty



ORDER INFORMATION

Factory at your fingertips. Fill in the blanks to create your part number or create a custom configuration.

| SENSOR | SERIES | LENGTH | W | | L | | DRIVER | | COLOR & CRI** | |
|--|-------------------------|---------|--|-------------------------|--------------------------|------------------------------|-----------------|-----------------|---------------|-----------------|
| | | | WATTAGE* | LUMENS* | WATTAGE* | LUMENS* | DRIVER | DRIVER | COLOR | CRI** |
| SS Sensor - On/Off SV Bi-level (xx) SD Daylight Harvesting  | S Open Strip | 24L 24" | J22W2800L | 22 Watts 2800 Lumens | DMV | 0-10V Dimming | 30K | 3000K 80 CRI | 35K | 3500K 80 CRI |
| | | | FRJ22W2600L (w/Frosted Lens) | 22 Watts 2600 Lumens | | | | | | |
| | | 48L 48" | J37W5000L | 37 Watts 5000 Lumens | D1MV | 0-10V Dimming (dim to 1%) | 50K | 5000K 80 CRI | 930K | 3000K 90 CRI |
| FRJ37W4600L (w/Frosted Lens) | 37 Watts 4600 Lumens | DMV(xx) | 0-10V Dimming (xx) for percentage of light output when not occupied. (required for SV sensor) | 935K | | | | | | |
| 96L 96" | J74W10050L | | | | 74 Watts 10050 Lumens | 940K | 4000K 90 CRI | | | |
| FRJ74W9300L (w/Frosted Lens) | 74 Watts 9300 Lumens | 950K | 5000K 90 CRI | | | | | | | |

Additional Options

| FINISH | OPTIONS |
|-----------|---|
| WH White | EM 10W Emergency battery backup (remote only) |
| BK Black | EM12 12W Emergency backup (remote only) |
| SL Silver | EM20 20W Emergency backup (remote only) |
| | WP 6 ft. 3 wire 18 gauge whip |
| | WP10 6 ft. 4 wire 18 gauge whip |

Note:


*Programmable LED drivers allow custom configured wattages and corresponding lumens.

**Consult factory for 90CRI 5000K availability.


We reserve the right to change design, materials, LEDs and finish in any way that will not alter installed appearance or reduce function and performance.

DRAWINGS & IMAGES

End View



4 FT



8 FT

