

APPLICATIONS

Economically designed narrow wraparound provides reliable and efficient lighting. Ideal for use in indoor applications such as homes, modular homes, mobile homes, stores and public building where low glare and ease of installation is required.

FEATURES & BENEFITS

- ◆ > 90% reflectivity
- ◆ Corrosion and scratch resistant
- ◆ Smooth edges for easy handling
- ◆ Nominal 9" width with a shallow design
- ◆ Clear acrylic diffuser with prismatic bottom and ribbed linear sides
- ◆ Diffuser self-aligns and hinges from either side for easy maintenance
- ◆ Available in lengths from 24 to 48 inches - (2' & 4' lengths)
- ◆ Standard two lamp configuration
- ◆ Easy re-lamping and re-ballasting
- ◆ Single or continuous row mounting capability
- ◆ Surface, stem or chain mountable
- ◆ Every fixture individually tested
- ◆ **UL** listed for damp location



SPECIFICATIONS

Housing and ends are die-formed and embossed from cold rolled steel. Finish is high reflectance **P3 - Post Powder Paint**. Inspection knockouts provided for mounting to junction box. Ballast cover snaps into place eliminating the need for tools when accessing the ballast. Diffuser hinges from either side in a lift and shift manner and is self-centering. End caps may be butted together for continuous row mounting. Narrow design provides spacing for cooler operation. Knockouts are provided for stem mounting. Listed by and bears **UL** label.

ORDERING DATA


EXAMPLE: 770-228MV277

Series	Lamp Position	Lamp Size	Ballast Type	Voltage	Options
770	2	17 24" T8 28 48" T5 32 32" T8 54 54 48" T5HO	MV Multivolt 120-277V LED** Wired 1 end hot for T8 LED tubes LED2E** Wired 2 ends hot for T8 LED tubes	Blank Not specified 277 277 Volt	B1 Battery backup 1 lamp B2 Battery backup 2 lamp L41 Lamp included (T5/T8-4100K) L35 Lamp included (T5/T8-3500K) RIF Radio interference filter 11 Dual Ballast 2 lamp

**Assembled with no ballast, made for UL Listed, self-ballasted retrofit T8 LED lamps

*Call for additional options
**See chart below for whip & cord ordering options

DIMENSIONS



**Cord & Whip Ordering Chart (Add to End of Fixture Part Number)

Part No.	# of Wires	Length	End Fitting	Finish	Voltage	Amps (TL Only)
WP - Whip	(Blank) 3 Wire	(Blank) 6 feet	(Blank) No Plug	BK - Black	(Blank) 120-277V	15 - 15 Amps
CS - Cordset	4 - 4 Wire	8 - 8 feet	P* - Standard Plug	WH - White	120 - 120V	20 - 20 Amps
	5 - 5 Wire	10 - 10 feet	TL* - Twist Lock		277 - 277V	
	6 - 6 Wire	12 - 12 feet			347 - 347V	
		15 - 15 feet			480 - 480V	

Dimensions and specifications subject to change without notice.

