




Texas Fluorescents  
Reinvented

# EWP Series

LED ENGINEERED WRAPAROUND WITH  
SOLID ENDS



## FEATURES & SPECIFICATIONS

**INTENDED USE** Heavy duty construction ideal for individual or continuous runs with solid ends. Engineered wraparound high efficiency luminaire available in either four or eight foot lengths. Low initial cost, maintenance free, this series also delivers excellent brightness control.

**SIZE** W x L x H in inches (mm)  
9.56"W x 48"L x 3.19"Dp (4ft.)  
9.56"W x 96"L x 3.19"Dp (8ft.)

### CONSTRUCTION

Completely die formed from heavy gauge cold rolled steel. Design embossed ends are locked and secures to the housing. Wireway cover snaps on or off without tools.

### MOUNTING

Suitable for individual or continuous run installations. May be surface or pendant mounted.

### Typical Options and Accessories

EM - Emergency battery backup, WP - whips.

### DIFFUSERS

A crystal clear diffuser extruded from 100% virgin acrylic that will maintain its color under normal conditions, indefinitely. Linear prisms on the interior side walls direct the light ceilingwards, which can then refract back down. The bottom is composed of an evenly spaced pattern of conical prisms yielding low brightness, glarefree diffused light. Diffuser is lift and shift for ease of relamping and cleaning and is capable of hanging down from either side of the housing.

## ORDERING INFORMATION

Example: EWPLR48LS32W3450LDMV40K

### STANDARD

EWP		LR		48L		S34W3450L		DMV		40K	
Series		Lens		Size		Wattage and Lumen		Driver		Kelvin Temperature	
EWP		LR Linear Ribbed Lens		48L	48"	<b>S32W3450L</b>	32 System Watts, 3450 Delivered Lumens	<b>DMV</b>	0-10V Dimming	<b>30K</b>	3000K
						<b>S48W4800L</b>	48 System Watts, 4800 Delivered Lumens			<b>35K</b>	3500K
						<b>H72W7000L</b>	72 System Watts, 7000 Delivered Lumens			<b>40K</b>	4000K
										<b>50K</b>	5000K
				<b>96L</b>	96"	<b>S48W4800L</b>	48 System Watts, 4800 Delivered Lumens				
						<b>S65W7000L</b>	65 System Watts, 7000 Delivered Lumens				
						<b>S97W9600L</b>	97 System Watts, 9600 Delivered Lumens				

## Plug in system Options - it's for continuous run application by simply plugging in sections together

Part Number	Descriptions
PI1	3 Wires Harness, Including White, Black and Green
PI2	4 Wires Harness, Including White, Black, Green and Blue for Emergency Battery Backup
PI3D	5 Wires Harness, Including White, Black, Green, Violet and Gray

\* Consult Factory for more options

Saylite  
2055 Luna Rd. Suite 142 Carrollton, TX 75006  
Phone: 972-247-3171 Fax: 972-247-0200  
www.saylite.com email: sales@saylite.com

Catalog Number:
Notes: