

INDRHLED16

LED NEMA4X/NSF REMOTE HEAD

STANDARD

OPTIONAL



ILLUMINATION

- Two fully adjustable, ultra bright 3.3 watt high performance MR-16 base LED lamp heads for optimized center-to-center spacing.

ELECTRICAL

- Powered from low voltage 6V/12V DC power source with low voltage wiring (not provided).

MOUNTING

- Universal knockout pattern on back provided with gasket for watertight seal for back mount.
- Distance of maximum run is determined by system voltage, wire gauge, and total maximum wattage on the run.
- Suitable for wall or ceiling mount.

HOUSING

- Housing is reinforced polycarbonate construction in white, gray or black finish.
- Corrosion-resistant enclosure with one piece, high-impact resistant, UV stabilized polycarbonate lens and molded gasket with stainless steel screws.
- Knockouts provided for conduit feed applications.



OPTIONS

- TP: Tamper-proof hardware helps discourage unauthorized access to the unit.

WARRANTY / LISTING

- Five year warranty.
- UL listed with approved Best Lighting Products.
- IP66 rated for Ingress protection.
- NEMA4X and NSF rated.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL certified for use in food service operations.

DIMENSIONS



FIXTURE COMPATIBILITY CHART

Reference individual unit equipment specification sheets for remote load capacity availability.

EZXTEU-RC*	LEDXTEU-RC*	CXTEU-RC*
CEU-RC	CKXTEURC	LEDR5HO*
E-1-RC	R-16HO*	RMR-16-65/125
TFX-2	DXR	CADXR
NYDXR	LEDCADXR	LEDSDXR627
RMLEDXTE-RC*	RMCLPU-RC*	INDEMR16
CLPU-RC*	R-5HO*	LEDTFX-2
CAR	CWLEZXTE-RC	INDCWLEZXTE

*SDT versions of the fixtures are not compatible with the INDRHLED16 remote heads.

ORDERING INFORMATION

Sample Part Number: INDRHLED161B

MODEL	HEADS	HOUSING COLOR	OPTIONS
INDRHLED16	1	W	TP Tamper-Proof
	2	B	
	G		