



JOB NAME:

CAT#:

TYPE:

APPLICATIONS

Premium grade recessed troffer dish with a center basket that provides direct/indirect light with modern styling and high visual comfort. For use in commercial and industrial buildings where low glare, high quality, design and ease of installation are required.

Housing is a die-formed from cold rolled steel. P3 - Post Powder Paint finish in a matte white. Indirect reflectors are precision formed and contoured to provide soft indirect illumination while maintaining high efficiency and wide uniform lighting distribution. Die-formed steel basket is perforated for direct illumination with a translucent opal white acrylic overlay diffuser for visual comfort. Perforated basket flexes over mounting studs on housing for easy installation. Wiring access plate or knockouts are provided on back of housing for flexible conduit attachment. Hole provided for chain mounting support to building structure. Surface mount options are available.



FEATURES & BENEFITS

- Contemporary shallow design
- Single basket shaped perforated metal shield
- Translucent opal white acrylic diffuser overlay
- Clean appearance with no exposed fasteners
- Solid metal basket available for indirect lighting
- Min CRI 82
- IC Rated
- cETL_{US} listed for damp location up to 67 watts

Dimensions and specifications subject to change without notice.





JOB NAME:

CAT#:

TYPE:

ORDERING

EXAMPLE: RDICB 22 LED 24 DMV 30 EM WP

RDICB		LED								
1. SERIES	2. SIZE	3. GEAR	4. WATTAGE/LUMENS		5. DRIVER		6. LENS		7. COLOR TEMP	
RDICB	22 2x2 24 2x4	LED	2x2		DMV	120-277V Multivolt 0-10V Dimmable		PF Perforated Lens		30 3000K 35 3500K 40 4000K 50 5000K
			24	24 Watts 2160 Lumens	SDMV	Step dimming Multivolt				
			28	28 Watts 2160 Lumens	D347V	347VAC 0-10V Dimming				
			35	35 Watts 2720 Lumens	D120	Triac Dimming 120VAC				
			2x4		D277	Triac Dimming 277VAC				
			32	32 Watts 2760 Lumens						
			48	48 Watts 3840 Lumens						
			57	57 Watts 4320 Lumens						
			72	72 Watts 5600 Lumens						

8. EMERGENCY(O)¹

EM Emergency
Battery Pack 10W
~ 1700 lumens

EM5 Emergency
Battery Pack 5W
~ 850 Lumens

9. CORD(O)¹

WP 6' 3 Wire Flexible
Conduit

Notes:
¹(O) is optional

Dimensions and specifications subject to change without notice.

