CATALOG#:

PROJECT

TYPE:

Series 44

Architectural LED Linear Pendant Squares (4ft and 8ft)

Make a bold statement in your space with dramatic, geometrically-shaped linear lines of light in square configurations. Series 44 fixtures are available in two standard sizes, 4 feet and 8 feet, with a 4-inch linear profile. (Inquire for rectangular or alternative configurations.) Lit corners, shadowless LED lighting and energy efficiency contribute to excellent performance for general lighting applications, while the architectural, pre-configured nature of these fixtures make them ideal for circulation spaces, lobbies, retail settings (cosmetics areas of department stores, etc.) and conference rooms. Available in two lumen packages, white or RGBW options, and in a variety of finishes. Standard snap-in frosted white lens specifically crafted to diffuse LED lighting. Bladed, specular parabolic or white cubed louver, plus matte white lens also available. Fixture installs quickly and easily with four cable kits, one per corner.

CONSTRUCTION

Die-formed and welded 22-gauge cold rolled steel. Knockouts on ends allow continuous wire-way mounting. A 1/2" regressed flange at the bottom insures uniformity and rigidity. Frosted white lens standard; alternative lens and louver options available.

DIMENSIONS

4x4 - 48"L \times 48"W \times 4"H 8x8 - 96"L \times 96"W \times 4"H Contact for custom configurations

FEATURES & BENEFITS

- Pendant mount architectural luminaires hung with supplied cable for each corner
- Direct lighting (and Direct/ Indirect, see ordering info on pg 2)
- Two standard sizes, each with two wattage/lumen package options
- Four Kelvin Temperatures (3000K, 3500K, 4000K, 5000K) or RGBW color shifting (Consult factory for RGBW option)
- Multiple lens and louver options available
- White or numerous color finishes available
- Emergency Battery Backup option available
- CRI >80 (90 CRI avail)
- >50.000 hrs of L70 LED life
- 0-10 Volt dimmable 120-277V (120 ELV/TRIAC avail)
- Power factor >0.90
- Suitable for dry and damp locations
- 5 year warranty







CATALOG#:	Se
PROJECT:	Arcl
TYPE:	Pen

Series 44

Architectural LED Linear Pendant Squares (4ft and 8ft)

ORDER INFORMATION

Factory at your fingertips. Fill in the blanks to create your part number or create a custom configuration.

					W	L				
SERIES		LENS MATERIAL	LE	NGTH	WATTAGE*	& LUMENS*		DRIVER	C	OLOR
44 Square	MW SP1	Matte white lens (Only avail- able for downlight) Specular Parabolic Louver	4×4	48"W × 48"L	Up or Down Lig R96W	96 Watts 9600 Lumens	DMV G120	0-10V Dimming ELV/TRIAC dimming at 120V only	35K 40K	4000K
	BL	Bladed louver semispecular		x 4"H	R128W	128 Watts 12800 Lumens			50K	5000K
	PLA	White Cubed Acrylic Louver	8x8	96"W	R192W	192 Watts	D1MV	0-10V Dimming (dim to 1%)		
	for LEDs; only available for	(85% transmission) Special for LEDs; only available for		× 96"L × 4"H	R256W 256	19200 Lumens 256 Watts 25600 Lumens				
		uplight and downlight								
			4×4	48"W × 48"L × 4"H	UR48WD48W UR64WD64W	96 Watts 9600 Lumens 128 Watts 12800 Lumens				
			8×8	96"W × 96"L × 4"H	UR96WD96W UR128WD128W	192 Watts 19200 Lumens 256 Watts 25600 Lumens				
					1/3 Up & 2/3 D					
			4×4	48"W × 48"L × 4"H	UR32WD64W UR43WD85W	96 Watts 9600 Lumens 128 Watts 12800 Lumens				
			8×8	96"W × 96"L × 4"H	UR64WD128W UR85WD171W	192 Watts 19200 Lumens 256 Watts 25600 Lumens				
					2/3 Up & 1/3 D	own Light				
			4×4	48"W × 48"L × 4"H	UR64WD32W UR85WD43W	96 Watts 9600 Lumens 128 Watts 12800 Lumens				
			8x8	96"W × 96"L × 4"H	UR128WD64W UR171WD85W	192 Watts 19200 Lumens 256 Watts 25600 Lumens				

Additional Options

С	CRI** FINISH		OPTIONS OPTIONS			
Blank 90	80 CRI 90 CRI	WH BK SI	White Black Silver	SQHC401WH SQHC4015WWH SQHC4035WWH EM EM12 EM20	Cable kit with 4' cable & 3 wires power feed/cable incl. and white canopy Cable kit with 4' cable & 5 wires power feed/cable incl. and white canopy Cable kit with 12' cable & 5 wires power feed/cable incl. and white canopy 10W Emergency battery backup (internal, excludes less than 4ft) 12W Emergency battery backup (internal, excludes less than 4ft) 20W Emergency battery backup (remote only)	

Note:

We reserve the right to change design, materials, LEDs and finish in any way that will not alter installed appearance or reduce function and performance.

^{*}Programmable LED drivers allow custom configured wattages and corresponding lumens.

^{**} Consult factory for 90CRI 5000K availability




CATALOG#:	
PROJECT:	

Series 44

Architectural LED Linear Pendant Squares (4ft and 8ft)

DRAWINGS & IMAGES



TYPE:

REPLACEMENT LENS ORDERING INFORMATION

SERIES	DESCRIPTION
044PSF4X4	Replacement Snap-in Frosted lens for 4x4 (order 1 per each fixture side)
044PSF8X8	Replacement Snap-in Frosted lens for 8x8 (order 1 per each fixture side)

8X8

