

CATALOG#:

PROJECT:

TYPE:



# LENSED LED High Bay Full Body

High efficiency LED engineered for premium performance in medium and high ceiling applications ideally suited for warehouses, manufacturing plants, sports facilities and retail spaces. A precision-formed reflector system available in highly reflective enhanced white reflector achieve maximum light output for ceilings from 15 feet to 40 feet. The unique arrangement is ideal for wide area lighting to put the light exactly where you need it with less fixtures. Based on ceiling height, these fixtures can replace an HID high bay using half of the wattage. Surface, pendant, chain or stem mounting. Highest quality materials and workmanship.

#### CONSTRUCTION

Housing is 22 gauge prepainted steel. Air vents surround the drivers in the back of the fixture to maximize LED and driver performance, reliability and life. High reflective enhanced white reflectors are computer designed to maximize photometric performance and put the light where you need it. Access plate in the back makes wiring fast and hassle-free. Back of fixture is designed with built-in mounting holes for tong hanger, cable kit and surface mount.

#### MOUNTING

Designed for surface, pendant, stem or chain hanging. Mounting holes are provided for simple, fast installation. See Buyers Guide for list of all mounting options available and sold separately

#### **TYPICAL OPTIONS & ACCESSORIES**

Emergency battery backup, Cord sets, whips, occupancy sensors, Hanging kits, Wire guards. Contact factory for additional options.

### **DIMENSIONS**

48L: 48.10"L x 16.385"W x 3.62"H

#### **FEATURES & BENEFITS**

- A sturdy/durable fixture body with superior appearance and appeal
- Ideal for commercial, retail and industrial applications
- Mounts easily with chain or cable kit
- Protected by an optional wire guard
- Suitable for dry or damp locations
- >50,000 hrs of L70 LED life
- · CRI >80
- 0-10 Volt dimmable 120-277V
- · Power factor 0.99
- 5 year warranty








| CATALOG#: | Series HBC             |  |  |
|-----------|------------------------|--|--|
| PROJECT:  | LED High Bay Full Body |  |  |

# **DRAWINGS & IMAGES**

TYPE:




# Back - 48"




TONG HANGERS HOLE DISTANCES

# **SIDE**



# **END**





Texas Fluorescents Reinvented

| CATALOG#: |  |  |
|-----------|--|--|
| PROJECT:  |  |  |

TYPE:

Series HBC LED High Bay Full Body

# **ORDER INFORMATION**

| SERIES                 | S   | IZES    | WATTAGE & LUMENS |                           | REFLECTOR |  | DRIVER |                   | COLOR                                |                |
|------------------------|-----|---------|------------------|---------------------------|-----------|--|--------|-------------------|--------------------------------------|----------------|
|                        |     |         |                  |                           |           |  |        |                   |                                      |                |
| HBCL<br>Frosted Smooth | 48L | 11.39"  | F97W11900L       | 97 Watts<br>11900 Lumens  | W30       | White Steel<br>reflector,<br>no uplight,<br>standard<br>distribution | DMV    | DMV 0-10V Dimming | <b>30K</b> 3000K<br><b>35K</b> 3500K | 3500K          |
| Acrylic                |     |         | H118W13500L      | 118 Watts<br>13500 Lumens |           |  |        |                   | 40K<br>50K                           | 4000K<br>5000K |
|                        | 48L | 16.385" | N127W18000L      | 127 Watts<br>18000 Lumens |           | Aluminum reflector,  |        |                   |                                      |                |
|                        |     |         | N144W20000L      | 144 Watts<br>20000 Lumens |           | no uplight,<br>standard<br>distribution                              |        |                   |                                      |                |
|                        |     |         | N162W24000L      | 162 Watts<br>24000 Lumens |           | distribution   |        |                   |                                      |                |
|                        |     |         | N216W30000L      | 216 Watts<br>30000 Lumens |           |  |        |                   |                                      |                |
|                        |     |         | N272W36000L      | 272 Watts<br>36000 Lumens |           |  |        |                   |                                      |                |
|                        |     |         | N280W40000L      | 280 Watts<br>40000 Lumens |           |  |        |                   |                                      |                |
|                        |     |         | N315W45000L      | 315 Watts<br>45000 Lumens |           |  |        |                   |                                      |                |
|                        |     |         | N355W50000L      | 355 Watts<br>50000 Lumens |           |  |        |                   |                                      |                |
|                        |     |         | N400W55000L      | 400 Watts<br>55000 Lumens |           |  |        |                   |                                      |                |
|                        |     |         | N433W60000L      | 433 Watts<br>60000 Lumens |           |  |        |                   |                                      |                |
|                        |     |         | *                | *                         |           |  |        |                   |                                      |                |
|                        |     |         |                  |                           |           |  |        |                   |                                      |                |
|                        |     |         |                  |                           |           |  |        |                   |                                      |                |

|             | OPTIONS   |
|-------------|---|
|             |   |
| MDT4        | Occupancy Sensor Wide Angle                       |
| MDF4        | Occupancy Sensor and Daylight                     |
| C8515       | 5-15P 120V 8ft Cord & Straight Blade Plug         |
| C8L715      | L7-15P 277V 8ft Cord & Locking Plug               |
| C8          | 8ft Cord No Plug                                  |
| WP          | 6ft 3 Wire, Whip                                  |
| WP64W       | 6ft 4 Wire, Whip                                  |
| EM          | 10W, 90 mins, 120-277VAC                          |
| WG          | Wire Guard  |
| LSXR610(xx) | Occupancy Sensor (Full On and Steps to XX% Level) |

MOUNTING

GT310 Cable kit -(2)10' aircraft cable with (1)10' 3 wire white cord GT315 Cable kit-(2)15' aircraft cable with (1) 15' 3 wire white cord

HC101 20' chain & (4) S hooks

HC204 (2)10' length chain & (2) end mount tong hangers

#### VIOTO.

\*Programmable LED drivers allow custom configured wattages and corresponding lumens.

We reserve the right to change design, materials, LED's and finish in any way that will not alter installed appearance or reduce function and performance.



| CATALOG#: |  |  |
|-----------|--|--|
| PROJECT:  |  |  |

Series HBC LED High Bay Full Body

TYPE:

# ORDER INFORMATION DLC Listed Items

#### ITEM NUMBER

HBC48LF97W11900LW30DMV40K

HBC48LH118W13500LW30DMV50K

HBC48LN127W18000LA10DMVxxx30Koooo

HBC48LN127W18000LA10DMVxxx35Koooo

HBC48LN127W18000LA10DMVxxx40Koooo

HBC48LN127W18000LA10DMVxxx50Koooo

HBC48LN144W20000LA10DMVxxx30Koooo

HBC48LN144W20000LA10DMVxxx35Koooo

HBC48LN144W20000LA10DMVxxx40Koooo

HBC48LN144W20000LA10DMVxxx50Koooo

HBC48LN162W24000LA10DMVxxx30Koooo

HBC48LN162W24000LA10DMVxxx35Koooo

HBC48LN162W24000LA10DMVxxx40Koooo

HBC48LN162W24000LA10DMVxxx50Koooo

HBC48LN216W30000LA10DMVxxx30Koooo

HBC48LN216W30000LA10DMVxxx35Koooo

HBC48LN216W30000LA10DMVxxx40Koooo

HBC48LN216W30000LA10DMVxxx50Koooo

HBC48LN272W36000LA10DMVxxx30Koooo

HBC48LN272W36000LA10DMVxxx35Koooo

HBC48LN272W36000LA10DMVxxx40Koooo

HBC48LN272W36000LA10DMVxxx50Koooo

