



JOB NAME:

CAT#:

TYPE:

APPLICATIONS

Full body micro silhouette makes a bold statement with a minimal design in post painted powder coated flat white polyester finish (consult factory for other finishes). Scaled to the LED module the matte white diffuser surrounds the LEDs for a soft lighting. Fixture can be surface mounted on the wall or ceiling or pendant mounted with specially engineered cable mounting kit.

FEATURES & BENEFITS

- Fully assembled housing is formed and welded 22 gauge steel chemically treated to resist corrosion and enhance paint adhesion
- Can be mounted individually or in continuous row
- Available with smooth frosted lens
- Knockouts on back accept standard electrical fittings (by others)
- Optional occupancy sensors, whips, fuses and cord set
- Optional sensor is self-contained, interchangeable and push-button programmable
- Surface or pendant mounted horizontally or vertically



Optional:
Add SS to the end of the part number for Occupancy Sensor

DIMENSIONS



Dimensions and specifications subject to change without notice.





JOB NAME:

CAT#:

TYPE:

ORDERING

EXAMPLE: LD23 24 LED 14 DMV WH FR 30

LD23		LED								
1. SERIES	2. SIZE	3. GEAR	4. WATTAGE/LUMENS		5. DRIVER		6. FINISH		7. LENS	
LD23	24 23.6"	LED	<u>2 FT</u>		DMV	120-277VAC		WH	White	FR Frosted
	48 47.15"		14	14 Watts 1400 Lumens		0-10V Dimmable		BK	Black	
	96 94.43"		20	20 Watts 2000 Lumens	SDMV	120-277VAC		BN	Brushed Nickel	
			<u>4 FT</u>			Step dimming-347VAC		OR	Orange	
			28	28 Watts 2800 Lumens	D347V	0-10V Dimming		IN	Iron	
			31	31 Watts 3200 Lumens		120-277VAC		BZ	Bronze	
			40	40 Watts 4000 Lumens	TDMV	Triac Dim @120V				
			45	45 Watts 4500 Lumens		Triac Dimming 120VAC				
			<u>8 FT</u>		D120	Triac Dimming 120VAC				
			56	56 Watts 5600 Lumens	D277	Triac Dimming 277VAC				
			62	62 Watts 6200 Lumens						
			80	80 Watts 8000 Lumens						

8. COLOR TEMP		9. SENSOR(O) ¹		10. HANGING KIT(O) ¹		11. PLUG IN OPTIONS(O) ¹	
30	3000K	SS	Integral Occ Sensor	H4W	HC301 Cable kit with 4' cable & power feed Cable incl. w/ white canopy and cord	P11	3 wire harness, including white, black and green
35	3500K	SSD	Integral Dimming Occ Sensor with Daylight	H4W5	HC301 Cable kit with 4' cable & power feed 0-10V Dimming Cable incl. w/white canopy and cord (5 wire)	P12	4 wire harness, including white, black, green and blue for emergency backup
40	4000K			H12W	HC302 Cable kit with 12' cable & power feed Cable incl. w/ white canopy and cord	P13D	5 wire harness, including white, black, green, violet and gray
50	5000K			H12W5	HC302 Cable kit with 12' cable & power feed 0-10V Dimming Cable incl. w/white canopy and cord (5 wire)		

NOTES:

¹(O) is optional

Dimensions and specifications subject to change without notice.

