



**JOB NAME:**

**CAT#:**

**TYPE:**

**FEATURES & BENEFITS**

- Input Voltage: 120VAC, 56/60Hz
- Input Current: 150mA ± 10%
- L<sub>70</sub> >36000 hrs
- Ambient Temperature: -20°C to +50°C
- Min CRI 80
- CCT: 4000K (Consult for other color temperatures)
- Suitable for damp locations
- Fixture is linkable and can be hard wired or use power cord.
- Fixture comes with power cord, knock-connector and joiner cable.
- Fixture comes with rocker switch installed



**DIMENSIONS**

- 9”L x 5”W x 1”H
- 12”L x 5”W x 1”H
- 18”L x 5”W x 1”H
- 24”L x 5”W x 1”H
- 33”L x 5”W x 1”H
- 42”L x 5”W x 1”H

**ORDERING**

EXAMPLE: MLUC 9 L 5W E120 40

**MLUC**

1. SERIES	2. SIZE	3. ROW CONNECTION	4. WATTAGE/LUMENS	5. DRIVER	6. COLOR TEMP
MLUC LED Under Cabinet Fixture	9 9”	L Linkable	<b>5W</b> 5 Watts 250 Lumens <u>9 in.</u>	E120 Electronic 120V only	40 4000K
	12 12”		<b>6W</b> 6 Watts 300 Lumens <u>12 in.</u>		
	18 18”		<b>9W</b> 9 Watts 450 Lumens <u>18 in.</u>		
	24 24”		<b>11W</b> 11 Watts 550 Lumens <u>24 in.</u>		
	33 33”		<b>13W</b> 13 Watts 650 Lumens <u>33 in.</u>		
	42 42”		<b>16W</b> 16 Watts 900 Lumens <u>42 in.</u>		

Dimensions and specifications subject to change without notice.



---

**JOB NAME:**

**CAT#:**

**TYPE:**

---

**ACCESSORIES**



**Knock-out Connector**



**39" Power Cord**



**6" Joiner Cable**

Dimensions and specifications subject to change without notice.