



JOB NAME:

CAT#:

TYPE:

APPLICATIONS

Give your facility a clean and sleek look with this LED premium strip. This fixture is sure to enhance any environment, provide energy savings, and give better quality lighting. This fixture is cost effective and makes this perfect for: schools, retail, warehouse, storage or any other facility area currently using strip fixtures.



FEATURES & BENEFITS

- Extruded frosted acrylic Lens
- Available in 24", 48", and 96" (2', 4', & 8') lengths
- Easy assembly and maintenance
- $L_{70} > 60,000$ hrs.

DIMENSIONS

W x L x H in inches

24 in: 4.25"W x 24.00"L x 3.25"H

48 in: 4.25"W x 48.00"L x 3.25"H

96 in: 4.25"W x 96.00"L x 3.25"H

Lumens are subject to a tolerance of $\pm 10\%$ and not relevant to RGB
Input wattage can vary depending on options
Dimensions and specifications subject to change without notice.





JOB NAME:

CAT#:

TYPE:

ORDERING

EXAMPLE: 44FSF 24 LED 18 DMV FR 30

44FSF		LED					
1. SERIES	2. LENGTH	3. GEAR	4. WATTAGE/LUMENS	5. DRIVER	6. LENS	7. COLOR TEMP	
44FSF LED Premium Lensed Strip	24 24" long	LED	24 in.		DMV 120-277V Multivolt 0-10V Dimmable	FR Frosted	30 3000K
	48 48" long		18 18 Watts 1980 Lumens	35 3500K			
	96 96" long		24 24 Watts 2640 Lumens	40 4000K			
			28 28 Watts 3080 Lumens	50 5000K			
			30 30 Watts 3300 Lumens				
			48 in.				
			24 24 Watts 2640 Lumens				
			30 30 Watts 3300 Lumens				
			35 35 Watts 3850 Lumens				
			48 48 Watts 5280 Lumens				
			57 57 Watts 6270 Lumens				
			96 in.				
			48 48 Watts 5280 Lumens				
	57 57 Watts 6270 Lumens						
	70 70 Watts 7700 Lumens						
	97 97 Watts 10670 Lumens						
	118 118 Watts 12980 Lumens						

8. EMERGENCY (O)' EM Emergency Battery Pack 10W ~1300 Lumens	9. SENSOR (O)' OS Occupancy Sensor OSD Occupancy Sensor w/ daylight harvesting and dimming SSM Integral microwave sensor	10. CORD & WHIP (O)' CS 6' cord 18/3 WP 6' whip 3 wire MC <small>*See cord & whip ordering chart below</small>
---	---	--

*Cord & Whip Ordering Chart (Add to End of Fixture Part Number)						
Part No.	# of Wires	Length	End Fitting	Finish	Voltage	Amps (TL Only)
WP - Whip CS - Cordset	(Blank) 3 Wire 4 - 4 Wire 5 - 5 Wire 6 - 6 Wire	(Blank) 6 feet 8 - 8 feet 10 - 10 feet 12 - 12 feet 15 - 15 feet	(Blank) No Plug P* - Standard Plug TL* - Twist Lock	BK - Black WH - White	(Blank) 120-277V 120 - 120V 277 - 277V 347 - 347V 480 - 480V	15 - 15 Amps 20 - 20 Amps

ACCESSORIES

A144-2 (2)V-hooks and (2) 2 ft chains

Notes:
'(O) is optional

Lumens are subject to a tolerance of ±10% and not relevant to RGB
 Input wattage can vary depending on options
 Dimensions and specifications subject to change without notice.

