



JOB NAME:

CAT#:

TYPE:

APPLICATIONS

A direct/indirect fixture that makes a bold statement by complementing design elements such as stone, metal, brick, and glass. The industrial look provides a modern aesthetic. It is available standard in white finish, and mounts with a cable kit. The louver is matte silver anodized parabolic.

FEATURES & BENEFITS

- Available standard in white finish or powder coated black
- Mounts with cable kit
- cETL_{US} listed
- 5 year warranty

DIMENSIONS

48.0"L x 6.0"W x 5.25"H



Dimensions and specifications subject to change without notice.





JOB NAME:

CAT#:

TYPE:

ORDERING

EXAMPLE: DLV6 48 LED 48 DMV WH 40 H4W5

DLV6		LED							
1. SERIES	2. LENGTH	3. GEAR	4. WATTAGE/LUMENS		5. DRIVER	6. FINISH		7. COLOR TEMP	
DLV6	48 48" long	LED	<u>48 inch</u>		DMV 120-277V Multivolt 0-10V Dimmable	WH White SI Silver BK Black BZ Bronze GV Galvanized Steel	30 3000K 35 3500K 40 4000K 50 5000K		
	96 96" long		24 24W 2800 Lumens						
			48 48W 5650 Lumens						
			57 57W 6400 Lumens						
			72 72W 8200 Lumens	SDMV Step dimming Multivolt					
			<u>96 inch</u>						
			48 48W 5650 Lumens	LUT Lutron Driver ¹					
			97 97W 11300 Lumens						
			114 114W 12800 Lumens						
			144 144W 16450 Lumens						

8. EM(O) ²		9. HANGING KIT(O) ²	
EM	Emergency Battery Pack 10W ~ 1700 lumens	H4W	Cable kit with 4 cable + power feed cable incl. w/ white canopy
EM5	Emergency Battery Pack 5W ~ 850 Lumens	H4W5	Cable kit with 4' cable + power feed 0-10V dimming cable included w/ white canopy (5 wire)
		H12W	Cable kit w/ 12' cable + power feed cable incl.w/ white canopy
		H12W5	Cable kit w/ 12' cable + power feed 0-10V dimming. Cable included with white canopy (5 wire)
		2SCS24WH	Two stem kits with 24" stem, canopy, and mounting hardware for a 4' fixture

Cord & Whip Ordering Chart (Add to End of Fixture Part Number)						
Part No.	# of Wires	Length	End Fitting	Finish	Voltage	Amps (TL Only)
WP - Whip CS - Cord-set	(Blank) 3 Wire 4 - 4 Wire 5 - 5 Wire 6 - 6 Wire	(Blank) 6 feet 8 - 8 feet 10 - 10 feet 12 - 12 feet 15 - 15 feet	(Blank) No Plug P* - Standard Plug TL* - Twist Lock	BK - Black WH - White	(Blank) 120-277V 120 - 120V 277 - 277V 347 - 347V 480 - 480V	15 - 15 Amps 20 - 20 Amps

Notes:

¹See Lutron Chart for Driver & Controls Options

²O is Optional

Dimensions and specifications subject to change without notice.

