



JOB NAME:

CAT#:

TYPE:

### APPLICATIONS

Mobern's SAL SR area light is a highly efficient, long life, low profile wet location rated luminaire that provides uniform illumination that is perfect for auto dealerships, parking lots, walkways, roadways, campuses, facade lighting, grocery stores and other public areas.




### FEATURES & BENEFITS

- One piece die-cast aluminum housing with outstanding corrosion protection
- UV resistant polycarbonate optical lens
- Round pole and square pole mounting, direct wall mounting, slip fitter
- Long lasting L70 ≥ 50,000 hrs
- IP66 rated
- Operated temperature range: -40°C to 45°C (-40°F to 113°F)
- Type III distribution standard
- cUL<sub>us</sub> Wet Location listed




### DIMENSIONS



40W/70W/100W (Slipfitter Mount)



40W/70W/100W (Pole Mount)



40W/70W/100W (Wall Mount)



Dimensions and specifications subject to change without notice.






JOB NAME:

CAT#:

TYPE:



**ORDERING**

EXAMPLE: SAL SR 12 LED 150 DMV 40 OS PC

SAL SR		LED									
1. SERIES	2. SIZE	3. DISTRIBUTION	4. GEAR	5. WATTAGE/LUMENS*		6. DRIVER		7. FINISH		8. COLOR TEMP	
SAL SR Area Light	12 12"	Blank Type 3	LED	40	40 Watts 5500 Lumens	DMV	120-277V Multivolt 0-10V Dimmable	Blank	Bronze	40	4000K*
	16 16"			70	70 Watts 9600 Lumens					50	5000K
	25 25"			100	100 Watts 13800 Lumens					SG	Silver/Gray
				150*	150 Watts 20700 Lumens					WH	White
				200*	200 Watts 27600 Lumens						
	250**	250 Watts 34500 Lumens									
	300**	300 Watts 41400 Lumens									
	350**	350 Watts 48300 Lumens									

\*16" Only  
\*\* 25" only

**9. SURGE PROTECTOR**

SP Surge Protection

**10. PHOTOCCELL**

PO 120V-277V Photocell  
P3 347V Photocell  
P4 480V Photocell

NOTES:

\*Check with your local sales person for lead time and distribution availability.

DLC Listed Fixtures				
Model Number	Housing Color (hh)	Color Temp	Options	DLC Listing
SALSR12-LED40DMVhhxx	hh= Blank, BK, SG, WH	xx= 40, 50	SP	Premium
SALSR12-LED70DMVhhxx	hh= Blank, BK, SG, WH	xx= 40, 50	SP	Premium
SALSR12-LED100DMVhhxx	hh= Blank, BK, SG, WH	xx= 40, 50	SP	Premium



Dimensions and specifications subject to change without notice.



**JOB NAME:**

**CAT#:**

**TYPE:**

**ACCESSORIES**

(Field Installed)

SAL-SQ-ARM	Square pole mounting arm for SAL (Bronze)
SAL-RD-ARM	Round pole mounting arm for SAL (Bronze)
SAL-SF	Slip fitter mounting for SAL (Bronze)
SAL-WALL-ARM	Wall mounting for SAL (Bronze)
SAL-SQ-ARM-PCMV	Square arm with 120-277V photocell
SAL-RD-ARM-PCMV	Round arm with 120-277V photocell
A-SC-AL01-100W-BA	Backlight control


**ARM**

**SAL-SQ-ARM**  
**SAL-RD-ARM**



Arm Mount (4" and 5" Square & Round Poles)  
Standard versatile mounting arm is simple to install and can be used with existing poles for retrofit installation.

**SAL-SF**




Slipfitter Mount  
An optional cast aluminum mast arm adapter secures fixture head to nominal 2" (2-3/8" O.D. pipe size) horizontal tenon arm.

**SAL-WALL-ARM**




Wall Mount  
Wall mount is easy to install for direct wall mounting with 1/2" conduit wiring or standard J-box mounting.

**SAL-SQ-ARM**  
**DIMENSIONS**



**SAL-RD-ARM**  
**DIMENSIONS**



Dimensions and specifications subject to change without notice.










JOB NAME:

CAT#:

TYPE:

**EPA OF AREA LIGHT**

Item							
	1	2 @90°	2 @120°	2@180°	3 @90°	3 @120°	4 @90°
150W/200W	0.4418	0.7145	0.8813	0.8836	1.0548	1.0135	1.0548
250W/300W/350W	0.5614	0.8471	1.105	1.1228	1.294	1.2503	1.294

Dimensions and specifications subject to change without notice.