



CATALOG#: _____
PROJECT: _____
TYPE: _____

Series SLW

Slotted Low Profile LED Linear Pendant

Saylite introduces LED low profile Direct/Indirect rectilinear Lighting that can be pendant, surface and wall mounted individually. Ideal for general lighting applications in both commercial and residential applications for circulation spaces, high impact areas and kitchen islands and home offices. The versatility and clean styling makes this an ideal choice in many applications.

CONSTRUCTION

Powder coated white aluminum extrusion with white interior and cast aluminum end plates. The diffuser / lens is a smooth frosted acrylic. Available in 4 and 8 foot nominal lengths.

MOUNTING

Pendant, surface or wall mount.



DIMENSIONS

48L - 48" L x 7.7" W x 2" H

96L - 96" L x 7.7" W x 2" H

FEATURES & BENEFITS

- Available in Pendant, Surface and Wall mount
- Low profile 2" H
- Exceptionally well into low ceiling environments
- CRI >80 standard, 90 optional
- L70: >50,000 Hours
- Dimming: 0-10V 120-277V standard, 120V ELV/TRIAC optional
- Power factor >0.90
- 5 year warranty





CATALOG#: _____
 PROJECT: _____
 TYPE: _____

Series SLW

Slotted Low Profile LED
Linear Pendant

ORDER INFORMATION

Factory at your fingertips. Fill in the blanks to create your part number or create a custom configuration.

SERIES	LENS		LENGTH		WATTAGE* & LUMEN*			DRIVER		COLOR/CRI**	
SLW Slotted Low Profile LED Linear Pendant	FR	Frosted Lens	48L	48 in.	Down Light Only	S48W4800L	48 Watts 4800 Lumens	DMV	0-10V Dimming	30K	3000K 80 CRI
					Direct/ Indirect	US12WD24W	Uplight 12 Watts Downlight 24 Watts 3600 Lumens	G120	ELV/TRIAC Dimming at 120V only	35K	3500K 80 CRI
					Direct/ Indirect	US18WD36W	Uplight 18 Watts Downlight 36 Watts 5400 Lumens	D1MV	0-10V Dimming (dim to 1%)	40K	4000K 80 CRI
	MW	Matte White	96L	96 in.	Down Light Only	S96W9600L	96 Watts 9600 Lumens	DMV(xx)	0-10V Dimming	50K	5000K 80 CRI
					Direct/ Indirect	US24WD48W	Uplight 24 Watts Downlight 48 Watts 7200 Lumens			930K	3000K 90 CRI
					Direct/ Indirect	US36WD72W	Uplight 36 Watts Downlight 72 Watts 10800 Lumens			935K	3000K 90 CRI
									940K	4000K 90 CRI	
									950K	5000K 90 CRI	

FINISH		OPTIONS	
WH	White	HC4015WWH	Cable kit with 4' cable & 5 wire power feed/cable incl., white cord and white canopy (included power feed and non-power feed)
SL	Silver	HC401WHNPF	Cable kit with 4' cable and white canopy, non-power feed (non-power feed only)
RD	Red	HC405WWH	Cable kit with 12' cable & 5 wire power feed/cable incl., white cord and white canopy (included power feed and non-power feed)
IN	Iron	HC402WHNPF	Cable kit with 12' cable and white canopy, non-power feed (non-power feed only)
BK	Black		

Note:
 *Programmable LED drivers allow custom configured wattages and corresponding lumens.
 ** Consult factory for 90 CRI 5000K availability.
 We reserve the right to change design, materials, LEDs and finish in any way that will not alter installed appearance or reduce function and performance.