

CAT#: TYPE: **JOB NAME:**

ILLUMINATION

- Ultra bright, energy efficient, long life red or green LED exit sign illumination
- Two fully adjustable high performance premium grade ultra bright white LED lamps
- 3.0 watt (1 LED x 3 watts) per head

ELECTRICAL

- Dual 120/277 voltage
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 8.4V long life, maintenance-free, rechargeable NiCd battery
- · Internal solid-state transfer switch automatically connects the internal battery to the lamp heads for minimum 90-minute emergency illumination.
- · Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING

- Aluminum mounting canopy included for top or end mount
- Universal knockout pattern on back plate for wall mount


HOUSING

- · Unique design provides spec grade exit sign with LED lamp heads in one low
- Premium-grade, extruded aluminum housing (also available in black or white powder-coated finishes)
- Field selectable knockout chevron directional indicators
- Quick-snap face plate closure
- Unique design allows double face conversion in the field

WARRANTY/LISTING

- Five year warranty on all electronics and housing. Battery prorated for 5 years
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes
- UL listed for damp locations (0°C-50°C)
- Certified to CEC under Title 20 regulations

DIMENSIONS



Dimensions and specifications subject to change without notice.









All LED Exit & Emergency Aluminum Combo

JOB NAME: CAT#: TYPE:

ORDERING

EXAMPLE: CKXTEU 1 R W W EM

CKXTEU

1. MODEL	2. # OF FACES		3. LETTER COLOR		4. HOUSING COLOR		5. FACE PANEL		6. BATTERY	
CKXTEU	1 2	Single Face Double Face	R G	Red Green	W B	White Black	W B	White Black	EM	Battery Backup
	3	Universal/ Single/Double			Α	Aluminum	Α	Aluminum		

7. REMOTE CAPACITY (O)1

Face

RC Remote Capacity

Notes:

¹(O) is optional

Dimensions and specifications subject to change without notice.





