

JOB NAME: CAT#: TYPE:

ILLUMINATION

 Two fully adjustable, ultra bright 3.3 watt high performance MR-16 base LED lamp heads for optimized center-to-center spacing

ELECTRICAL

 Powered from low voltage 6V/12V DC power source with low voltage wiring (not provided)

MOUNTING

- Universal mounting knockout pattern on back provided with gasket for watertight seal for back mount
- Distance of maximum run is determined by system voltage, wire gauge and total maximum wattage on the run
- Suitable for wall or ceiling mount


HOUSING


- · Housing is reinforced polycarbonate construction in white, gray, or black finish
- Corrosion-resistant enclosure with one piece, high-impact resistant, UV stabilized polycarbonate lens and molded gasket with stainless steel screws
- · Knockouts provided for conduit feed applications


WARRANTY/LISTING

- · Five year warranty
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes
- UL listed with approved Mobern Lighting products
- NEMA4X and NSF rated
- IP66 rated
- UL certified for use in food service operations

DIMENSIONS







Dimensions and specifications subject to change without notice.













INDRHLED16 LED NEMA4X/NSF Remote Head

JOB NAME:	CAT#:	TYPE:

ORDERING

EXAMPLE: INRHLED16 2 W

INDRHLED16

1. MODEL	2. # 0	OF HEADS	3. H	OUSING COLOR	4. TA	AMPERING (O)1
INDRHLED16	1	Single Head	W	White	TP	Tamper-Proof
INDICILLOIO	2	Double Head	В	Black		
			G	Gray		



¹(O) is optional

Dimensions and specifications subject to change without notice.

