

JOB NAME:
CAT#:
TYPE:

ILLUMINATION

- Ultra bright, energy efficient, long life red or green LEDs

ELECTRICAL

- Dual 120/277 voltage
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 1.2V long life, maintenance-free, rechargeable NiCd battery (EM models only)
- Internal solid-state transfer switch automatically connects the internal battery to the lamp heads for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING

- EZ-snap mounting canopy included for top or end mount
- Universal knockout pattern on back plate for wall mount

HOUSING


- Injection molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish
- Aesthetically pleasing curved face with rounded corner design
- EZ snap-out chevron directional indicators



WARRANTY/LISTING

- Five year warranty on all electronics and housing. Battery prorated for 5 years
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes
- UL listed for damp locations (0°C-50°C)
- Certified to CEC under Title 20 regulations

DIMENSIONS



Dimensions and specifications subject to change without notice.





JOB NAME:

CAT#:

TYPE:

ORDERING

EXAMPLE: EZRXTU 2 R W EM

EZRXTU

1. MODEL	2. # OF FACES	3. LETTER COLOR	4. HOUSING COLOR	5. BATTERY
EZRXTU	2 Universal Single/ Double Face	R Red G Green	W White B Black	(blank) AC-Only EM Battery Backup

Dimensions and specifications subject to change without notice.

