



**JOB NAME:**

**CAT#:**

**TYPE:**



Surface mount, specification grade, direct/indirect dual diffuser luminaire provides smooth and uniform ambient lighting for all commercial and industrial buildings. Reflected light from matte surfaces provide a softened "sky light" appearance to the modern office environment. Choice of perforated basket or linear ribbed lens.

- Direct/indirect mimics "sky light" appearance
- Matte white reflective surfaces for soft, uniform light distribution
- Recessed perforated dual diffuser with acrylic overlay.
- UL listed for damp locations

**CONSTRUCTION**

Housing is die-formed and embossed code gauge steel. Luminaire body finish is high reflectance baked white enamel, with matte white reflectors. Wiring knockouts are provided on the back of housing. Dual diffuser snaps into place; no tools are required for removal. Diffuser is perforated to maintain even brightness, and provided with an internal, acrylic overlay to obscure lamps. Ribbed acrylic lens provides increased light output.

**SIZE W x L x H in inches (mm)**

**2x2** - 23.68"W x 23.68"L x 3.25"H

**2x4** - 23.68"W x 47.7"L x 3.25"D

The most economical, practical, and user friendly series of LED fixtures with energy savings, quality of light, long life and hassle-free maintenance/ EZLED fixtures are UL listed with the latest LED T8 bypass lamps. These fixtures provide over 44% energy savings over comparable fluorescent fixtures utilizing less expensive fixtures than the fluorescent version (no ballast required). They also provide the flexibility to change the wattage and color temperature at any time. Are you concerned about maintenance with an LED array and driver fixture? EZLED resolves that issue by utilizing a self-contained LED lamp that fits into your fixture just like the classic fluorescent tube. The fixture performance will evolve over time with the evolution of the T8 LED lamp technology, and our five-year warranty guarantees a reliable, high quality product.

**Lamp Specifications**

Our EZLED fixtures come standard with SaveGreen T8 LED lamps. They are available in 2 or 4 foot sizes in different wattage, lumens, and color temperature options (see lamp options and specifications at [www.savegreenlighting.com](http://www.savegreenlighting.com)).

- L70 > 50000 hrs.
- Operating temperature: -20°C to 50°C
- Color Temperature: 3500K, 4000K, 5000K
- G13 pins (same as fluorescent linear T8 bipin)
- AC100-277V
- Integral driver (non-isolated) eliminates the need for external driver or ballast
- Environmentally friendly, no mercury used
- UL Classified
- Min CRI 80
- 5 year warranty

**Optional Dimming**

The 4 foot lamps are available with a dimming option. Specially designed dimming lamps require an external driver that runs 1 or 2 lamps (more than 2 lamps require multiple external drivers).

**Emergency Options**

The standard EZLED lamps require an inverter or an all-in-one emergency kit that includes LED array, battery, and driver. Dimmable T8 LED with external driver works with standard LED EM in it.

Dimensions and specifications subject to change without notice.





**JOB NAME:**

**CAT#:**

**TYPE:**

**ORDERING**

EXAMPLE: SRDISD 22 4 32 LEDL7W 35 JAM RL

**SRDISD**

1. SERIES	2. SIZE	3. # OF LAMPS	4. LAMP TYPE	5. LAMP WATTAGE	6. COLOR TEMP	7. LAMP BRAND
SRDISD	22 2x2	2 2 Lamps	17 24" T8	<b>T8 Options</b> <b>2ft.</b>	30 3000K	<b>Blank</b> House Brand (Savegreen)
	24 2x4	4 4 Lamps	32 48" T8			
			54 46" T5HO	<b>4ft.</b>	35 3500K	<b>KEY</b> Keystone
				<b>LEDL7W</b> 7 Watts 950 Lumens	40 4000K	<b>JAM</b> James Brand (Special Order)
				<b>LEDL9W</b> 9 Watts 1050 Lumens	50 5000K	
				<b>LEDL12W</b> 12.5 Watts 1750 Lumens		
				<b>LEDL15W</b> 15 Watts 1740 Lumens		
				<b>LEDL18W</b> 18 Watts 2500 Lumens		
				<b>T5 Options</b>		
				<b>LEDL25W</b> 25 Watts 3300 Lumens		

**8. DIFFUSER**

**PF** Perforated Basket  
**RL** Ribbed acrylic

**9. WHIP**

**WP** 6' whip, 3 wire

**10. INVERTER**

**INV5** 5W Integrated Inverter

Dimensions and specifications subject to change without notice.

