



CATALOG#: \_\_\_\_\_  
PROJECT: \_\_\_\_\_  
TYPE: \_\_\_\_\_

# Series RH

## Single and Double Emergency LED Remote Heads

### ILLUMINATION

- Long lasting, efficient ultra-bright white LED lamp heads
- High performance chrome-plated metallized reflector and plastic lens (indoor applications) or glass lens (outdoor applications) for optimal light distribution
- Adjustable LED lamp heads increases center-to-center spacing with 9 LEDs in each lamp head

### ELECTRICAL

- Powered from low voltage power source with low voltage wiring (not provided)

### MOUNTING

- Universal mounting base mounts to single-gang switch box
- Distance of maximum run is determined by system voltage, wire gauge and total maximum wattage on the run
- Suitable for wall or ceiling mount

### HOUSING

- Indoor application remote heads are injection-molded, engineering-grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish
- Outdoor application remote heads are die-cast aluminum, sealed and gasketed in gray or black finish

### CERTIFICATIONS & WARRANTY

- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes
- UL Listed with approved Saylite products
- Five year warranty on electronics and housing





CATALOG#: \_\_\_\_\_  
 PROJECT: \_\_\_\_\_  
 TYPE: \_\_\_\_\_

# Series RH

Single and Double Emergency LED Remote Heads

## ORDER INFORMATION

Factory at your fingertips. Fill in the blanks to create your part number or create a custom configuration.

Model #	# of Heads	Voltage	Wattage	Application	Approved for
RHLED1-R1	1	3.6 Volt	1	Indoor	LEDR5-HO
RHLED1SDT-R1	1	3.6 Volt	1	Indoor	LEDR5-HO
RHLED2-R1	2	3.6 Volt	2	Indoor	LEDR5-HO
RHLED2-SDT-R1	2	3.6 Volt	2	Indoor	LEDR5-HO
RHLED1-WP-R1	1	3.6 Volt	1	Outdoor	LEDR5-HO
RHLED1-SDT-WP-R1	1	3.6 Volt	1	Outdoor	LEDR5-HO
RHLED2-WP-R1	2	3.6 Volt	2	Outdoor	LEDR5-HO
RHLED2-SDT-WP-R1	2	3.6 Volt	2	Outdoor	LEDR5-HO

Model #	# of Heads	Voltage	Wattage	Application	Approved for
RHLED1-CLPCXTE	1	9.6 Volt	1	Indoor	CLPU, LEDCXTE
RHLED1SDT-CLPCXTE	1	9.6 Volt	1	Indoor	CLPU, LEDCXTE
RHLED2-CLPCXTE	2	9.6 Volt	2	Indoor	CLPU, LEDCXTE
RHLED2-SDT-CLPCXTE	2	9.6 Volt	2	Indoor	CLPU, LEDCXTE
RHLED1-WP-CLPCXTE	1	9.6 Volt	1	Outdoor	CLPU, LEDCXTE, LEDTFX-2
RHLED1-SDT-WP-CLPCXTE	1	9.6 Volt	1	Outdoor	CLPU, LEDCXTE, LEDTFX-2
RHLED2-WP-CLPDXT	2	9.6 Volt	2	Outdoor	CLPU, LEDCXTE, LEDTFX-2
RHLED2-SDT-WP-CLPCXTE	2	9.6 Volt	2	Outdoor	CLPU, LEDCXTE, LEDTFX-2

Note:  
 We reserve the right to change design, materials, LEDs and finish in any way that will not alter installed appearance or reduce function and performance.