

FEATURES & SPECIFICATIONS

INTENDED USE

A wrap around fluorescent fixture designed for parking garages, school corridors or any application where high abuse or vandalism could occur.

Construction

Back plate is die formed of 16 gauge steel. Lens attached to back plate with tamper resistant stainless steel screws.

Diffuser

Diffuser is made of injection molded UV stabilized 100% clear, polycarbonate with an internal prismatic pattern.

Mounting

Units may be surface or wall mounted.

Listing

Fixtures conform to Underwriters' Laboratories standards for production and are carefully tested prior to packing. Fixtures are UL Listed wet location for ceiling and damp location for wall mounting.



Electrical

Unless otherwise specified, ballasts are rapid start, class "P" thermally protected, H.P.F., CBM-ETL. Standard voltage on all fixtures is 120V-277V 60Hz AC, or as specified. Sufficient knockouts are provided on the back for all connections and through wiring with wire harness..

ORDERING INFORMATION

Example: CV800 2328MV

Series	Lamp Count	Lamp Type & Tandem Code	Ballast & Voltage [1]	Options [1]
CV800	2	32 (Blank) 4' 48" 32WT8	MV Electronic, Multivolt (120-277)	WP 6ft. 3 wire 18 gauge whip WP10 6ft. 4 wire 18 gauge whip EM Emergency ballast 500 lumens EM14 Emergency ballast 1400 lumens PI1 Included Wire harness, 3 wire
		8 48" 32WT8 8 ft. Tandem (double lamp count)		

