



# FSF Series

## LED Medium Body Strip with Lens



## FEATURES & SPECIFICATIONS

Great Performance Strip Fixture - now available with Lens. This LED offering is perfect for so many applications. Designed economically yet with balance and sleek aesthetics. This fixture is perfect for: Retail, Industrial, Back House applications as well as the perfect solution for Mezzanine low ceiling installations where a wide distribution light pattern is needed. 5 year factory warranty.

## MOUNTING

Surface mount, chain hung, double stem.

## TYPICAL OPTIONS AND ACCESSORIES

Whips, wireguards, Emergency battery backup (IOTA ILB-CP10HE), or contact factory for more details.

**SIZE\*****W x L x H in inches**

2ft: 4.25W x 24.00L x 3.25H

4ft: 4.25W x 48.00L x 3.25H

8ft: 4.25W x 96.00L x 3.25H

\*All dimensions are inches. Specifications subject to change without notice.



## 2 ft - STANDARD

Example: **FSF24LFRZ33W3300LDMV40K**

FSF		FR		24L		Z33W3300L		DMV		40K		
Series		Lens		Length		Wattage and Lumen		Driver		Kelvin Temperature		
FSF		FR	Frosted Lens	24L	24"	J14W1400L	14 System Watts, 1400 Delivered Lumens	DMV	0-10V Dimming	30K	3000K	
Medium Body Strip						J18W1800L	18 System Watts, 1800 Delivered Lumens			35K	3500K	
SMFSF						J28W2800L	28 System Watts, 2800 Delivered Lumens			40K	4000K	
Medium Body Strip with Microware Sensor						Z33W3300L	33 System Watts, 3300 Delivered Lumens			50K	5000K	
											Options	
											WP	6 ft. 3 wire 18 gauge whip
											WP10	6 ft. 4 wire 18 gauge whip
											EM10HE	10w Emergency battery backup
											MDT4	Occupancy Sensor

**\*Consult factory for more options**

Saylite  
2055 Luna Rd. Suite 142 Carrollton, TX 75006  
Phone: 972-247-3171 Fax: 972-247-0200  
www.saylite.com email: sales@saylite.com

Catalog Number:

Notes:



SS-Embedded Sensor

## FSF Series

### LED Medium Body Strip with Lens



#### 4 ft - STANDARD

Example: FSFFR48LJ31W3100LDMV40K

FSF	FR	48L	J31W3100L	DMV	40K		
Series	Lens	Length	Wattage and Lumen		Driver	Kelvin Temperature	
<b>FSF</b>	<b>FR</b> Frosted Lens	<b>48L</b> 48"	<b>J28W2800L</b>	28 System Watts, 2800 Delivered Lumens	<b>DMV</b> 0-10V Dimming	<b>30K</b>	3000K
Medium Body Strip			<b>J31W3400L</b>	31 System Watts, 3400 Delivered Lumens		<b>35K</b>	3500K
<b>SMFSF</b>			<b>Z48W4800L</b>	48 System Watts, 4800 Delivered Lumens		<b>40K</b>	4000K
Medium Body Strip			<b>Z57W6300L</b>	57 System Watts, 6300 Delivered Lumens		<b>50K</b>	5000K
with							
Microwave Sensor			<b>Z62W6200L</b>	62 System Watts, 6200 Delivered Lumens			
<b>SSFSF</b>							
Medium Body Strip							
with							
Embedded On/Off							
Sensor							
						<b>Options</b>	
						<b>WP</b>	6 ft. 3 wire 18 gauge whip
						<b>WP10</b>	6 ft. 4 wire 18 gauge whip
						<b>EM10</b>	10w Emergency battery backup
						<b>EM12</b>	12w Emergency battery backup
						<b>MDT4</b>	Occupancy Sensor

#### 8 ft - STANDARD

FSF	FR	96L	J48W4800L	DMV	40K		
Series	Lens	Length	Wattage and Lumen		Driver	Kelvin Temperature	
<b>FSF</b>	<b>FR</b> Frosted Lens	<b>96L</b> 96"	<b>J48W4800L</b>	48 System Watts, 4800 Delivered Lumens	<b>DMV</b> 0-10V Dimming	<b>30K</b>	3000K
Medium Body Strip			<b>J57W5700L</b>	57 System Watts, 5700 Delivered Lumens		<b>35K</b>	3500K
<b>SMFSF</b>			<b>J62W6600L</b>	62 System Watts, 6600 Delivered Lumens		<b>40K</b>	4000K
Medium Body Strip			<b>Z97W9700L</b>	97 System Watts, 9700 Delivered Lumens		<b>50K</b>	5000K
with							
Microwave Sensor			<b>Z114W11400L</b>	114 System Watts, 12600 Delivered Lumens			
<b>SSFSF</b>			<b>Z124W12400L</b>	124 System Watts, 12400 Delivered Lumens			
Medium Body Strip							
with							
Embedded On/Off							
Sensor							
						<b>Options</b>	
						<b>WP</b>	6 ft. 3 wire 18 gauge whip
						<b>WP10</b>	6 ft. 4 wire 18 gauge whip
						<b>EM10</b>	10w Emergency battery backup
						<b>EM12</b>	12w Emergency battery backup
						<b>MDT4</b>	Occupancy Sensor

\*Consult factory for more options