



## FEATURES & SPECIFICATIONS

### INTENDED USE

Full body contoured strip makes a bold statement with a minimal design in post-painted in powder coated flat white finish (consult factory for other finishes). Scaled to fluorescent modules, the frosted diffuser surrounds the bulbs for soft lighting.

### Construction

Fully assembled housing is formed and welded, 22 gauge steel, chemically treated to resist corrosion and enhance paint adhesion. Can be mounted individually or in continuous row.

### Diffuser

Available with smooth frosted lens.

### Mounting

Surface mount or Pendant mount. Horizontal or Vertical.

### Listing

Fixtures conform to Underwriters' Laboratories standards for production and are carefully tested prior to packing. Fixtures are UL Listed wet location for ceiling and damp location for wall mounting.

### Electrical

Unless otherwise specified, ballasts are rapid start, class "P" thermally protected, H.P.F., CBM-ETL. Standard voltage on all fixtures is 120V-277V 60Hz AC, or as specified. Sufficient knockouts are provided on the back for all connections and through wiring with wire harness..

## ORDERING INFORMATION

Example: SERRF1328DMVWH

SER		1		17		MV		
Series	Lens	Lamp Position		Lamp Type		Tandem Code		Driver
SER	<b>Blank</b> No Lens	<b>1</b> Single Row	<b>14</b> 22in. T5	<b>Blank</b> XXin. T8	<b>MV</b> 120-277VAC Multivolt			
	<b>FR</b> Frosted Ribbed	<b>2</b> Two Rows	<b>24</b> 22in. T5HO	<b>8</b> (2) 48in. T8 8 ft Tandem	<b>DMV</b> 120-277VAC Triac & 0-10V Dimming			
			<b>17</b> 24in. T8					
			<b>28</b> 46in. T5					
			<b>54</b> 46in. T5HO					
			<b>32</b> 48in. T8					
Finish		Options						
<b>WH</b> White	<b>WP</b> 6ft. 3 wire 18 gauge whip							
<b>BK</b> Black	<b>WP10</b> 6ft. 4 wire 18 gauge whip							
<b>SL</b> Silver	<b>EM</b> Emergency ballast 500 lumens							
<b>RD</b> Red	<b>EM14</b> Emergency ballast 1400 lumens							
	<b>PI1</b> Included Wire harness, 3 wire							