

JOB NAME:

CAT#:

TYPE:

## APPLICATIONS

Introducing the Mobern PRF1-LED Premium grade enclosed and gasketed vaportight fixture. This Energy-Saving High Performance LED enclosure is ideal for both indoor and outdoor applications where dust and water resistance is required. Ideal for parking garages, cold storage, marinas, barns, canopies, car washes, poultry farms, agricultural applications and other areas susceptible to corrosive and wet conditions.

## FEATURES & BENEFITS

- Single piece co-extruded lens and housing
- Lens and housing are all one piece
- Available in 2', 4', & 8' lengths



## ORDERING

EXAMPLE: PRF1 2 LED 24 DMV GY A 30

PRF1		LED		DMV		6. FINISH	
1. SERIES	2. SIZE	3. GEAR	4. WATTAGE/LUMENS	5. DRIVER			
PRF1	2 2 ft 4 4 ft 8 8 ft	LED	24 24 Watts 2250 Lumens 48 48 Watts 4500 Lumens 96 96 Watts 9000 Lumens	DMV 0-10V Dimming 120-277VAC Multivolt SDMV Step Dimming 120-277VAC 100%-40% D120 120V Dimmable D347V 347VAC 0-10V Dimmable D277 Triac Dimming 277VAC	GY Grey		
7. HOUSING MATERIAL	8. COLOR TEMP	9. SENSOR(O) <sup>1</sup>	10. EMERGENCY(O) <sup>1</sup>	11. CORD(O) <sup>1</sup>			
A Acrylic	30 3000K 35 3500K 40 4000K 50 5000K	OS Occ Sensor -On/Off OSD Occ Sensor w/Dimming & Daylight Harvesting OSW Occ Sensor Wet Location OSC Occ Sensor Cold Location SS Occ Sensor Internal Microwave	EM Emergency Battery Backup	CS Cord 18/3 6"			

**Notes:**  
<sup>1</sup>O is Optional

Dimensions and specifications subject to change without notice.





JOB NAME:

CAT#:


TYPE:

**ACCESSORIES**

- A-PRF-MB      Mounting Bracket
- A-PRF-S1-SB      Safety bail (order 2 per mounting bracket)
- A-PRF-AS-BLK-N      ACME screw
- A-SLP-GRMT-0500      Optional wire grommet

**DIMENSIONS**

- 8'L x 3.86"W x 3.75"H
- 4'L x 3.86"W x 3.75"H
- 2'L x 3.86"W x 3.75"H



Dimensions and specifications subject to change without notice.

