

JOB NAME: CAT#: TYPE:

APPLICATIONS

Premium grade surface mounted wraparound luminaire with low brightness linear sides. For use in indoor applications where high efficiency, high performance and ease of installation is required. Ideal for retail stores, stairwells, utility areas, schools, offices and public buildings.

- · Clear acrylic diffuser with prismatic bottom and ribbed linear sides
- · Diffuser self-aligns and hinges from either side for easy maintenance
- · Surface, stem or chain mountable
- · Single or continuous row mounting capability
- · UL listed for damp location

CONSTRUCTION

Housing and ends are die-formed from cold rolled steel. Finish is high reflectance baked white enamel with a reflectance factor exceeding 86%. Diffuser hinges from either side in a lift and shift manner and is self centering. UL listed for damp locations.

The most economical, practical, and user friendly series of LED fixtures with energy savings, quality of light, long life and hassle-free maintenance/ EZLED fixtures are UL listed with the latest LED T8 bypass lamps. These fixtures provide over 44% energy savings over comparable fluorescent fixtures utilizing less expensive fixtures than the fluorescent version (no ballast required). The also provide the flexibility to change the wattage and color temperature at any time. Are you concerned about maintenance with an LED array and driver fixture? EZLED resolves that issue by utilizing a self-contained LED lamp that fits into your fixture just like the classic fluorescent tube. The fixture performance will evolve over time with the evolution of the T8 LED lamp technology, and our five-year warranty guarantees a reliable, high quality product.

FEATURES & BENEFITS

Our EZLED fixtures come standard with SaveGreen T8 LED lamps. They are available in 2 or 4 foot sizes in different wattage, lumens, and color temperature options (see lamp options and specifications at www.savegreenlighting.com).

- L70 > 50000 hrs.
- Operating temperature: -20°C to 50°C
- Color Temperature: 3500K, 4000K, 5000K
- G13 pins (same as fluorescent linear T8 bipin)
- AC100-277V
- Integral driver (non-isolated) eliminates the need for external driver or ballast
- · Environmentally friendly, no mercury used
- UL Classified
- Min CRI 80
- 5 year warranty



Optional Dimming

The 4 foot lamps are available with a dimming option. Specially designed dimming lamps require an external driver that runs 1 or 2 lamps (more than 2 lamps require multiple external drivers).

Emergency Options

The standard EZLED lamps require an inverter or an all-in-one emergency kit that includes LED array, battery, and driver. Dimmable T8 LED with external driver works with standard LED EM in it.

DIMENSIONS

2 lamp - 11.25 x 24 x 3.4 (2ft)

2 lamp - 11.25 x 48 x 3.4 (4ft)

4 lamp - 15.8 x 48 x 3.4 (4ft)

4 lamp - 15.8 x 96 x 3.4 (8ft)

8 lamp - 15.8 x 96 x 3.4 (8ft)











Dimensions and specifications subject to change without notice.



JOB NAME: CAT#: TYPE:

ORDERING

EXAMPLE: 772 2 17 LED7W 30 WP INV5

772					
1. SERIES	2. # OF LAMPS	3. LAMP TYPE	4. WATTAGE/LUMENS	5. COLOR TEMP	6. LAMP BRAND
772	2 2 Lamps 3 3 Lamps 4 4 Lamps	17 24 inch T8 32 48 inch T8 32TAN 96 inch T8 54* 46 inch T5HO *Only available in 840 & 850	T8 Options 2 ft. LEDL7W 7 Watts 950 Lumens Keystone LEDL15W 9 Watts 1050 Lumens 4 ft. LEDL12W 12.5 Watts 1750 Lumens Keystone LEDL15W 15 Watts 1740 Lumens LEDL18W* 18 Watts 2500 Lumens 8 ft. LEDL12W 12.5 Watts 1750 Lumens Keystone LEDL15W 15 Watts 1740 Lumens LEDL15W 15 Watts 1740 Lumens LEDL15W 15 Watts 2500 Lumens LEDL18W* 18 Watts 2500 Lumens LEDL18W* 25 Watts 3300 Lumens LEDL25W 25 Watts 3300 Lumens	30 3000K 35 3500K 40 4000K 50 5000K	Blank House Brand Lamp (Savegreen) KEY Keystone Brand JAM James Brand** **Special Order
8. CORD	10.	INVERTER			

6' Whip, 3 Wire

A144 (2) V-Hook & (2) ft.chain

Wireguard per 4 ft.

WP

A69

ACCESSORIES

Lumens are subject to a tolerance of $\pm 10\%$ and not relevant to RGB Input wattage can vary depending on options Dimensions and specifications subject to change without notice.

INV5 5W Integrated

Inverter

*Consult for other options











Dimensions and specifications subject to change without notice.



JOB NAME: CAT#: TYPE:

END CAP COLOR SELECTION GUIDE

