

Texas Fluorescents Reinvented

555 SERIES

Ceiling/Wall Mount



Stylish ceiling/wall mounted luminaire in either white or walnut finish with a variety of lamp combinations and sizes enhanced by linear sided acrylic diffuser. Designed for baths, kitchens, rec rooms, corridors, aisles, stairwells, over or beside mirrors, over bulletin boards, in vanities, in displays. The X1LED 555 series utilize efficient LED T8 lamps that provide high lumen output with efficient energy savings. Since they don't require any ballast or driver the only component that will ever need changing is the LED T8 lamp. The lamps are warranted for five years. Unlike 555 series that utilize LED arrays and drivers these fixtures have the flexibility to change wattage, lumens, and color temperature simply by changing the lamps without the need to call a licensed electrician.

LAMP

2 lamp positions

CONSTRUCTION

All metal parts are die formed from heavy gauge cold roll steel with overlapping end caps to insure uniformity and dimensional stability. One light and two light units same external dimensions.

MOUNTING

Back plate provided with adequate knockouts and mounting holes for either wall or ceiling installation.

WIRING

Standard ballast are 120volts, 60 hertz.

SIZE W x L x H in inches

4.50H x 4.375W Available in 24, 36, and 48in lengths



X1 LED

The most economical, practical and user friendly series of LED fixtures with the energy savings, quality of light, long life and hassle-free maintenance. X1 LED fixtures are UL Listed with the latest LED T8 Bypass lamps. Fixtures provide over 44% energy savings over comparable fluorescent fixtures utilizing less expensive fixtures than the fluorescent version (no ballast required) and have flexibility to change wattage and color temperature any time. Fixture performance will evolve over time with the evolution of the T8 LED lamp technology. Concerned about maintenance with an LED array and driver fixture, X1 LED solves that by utilizing a self contained LED lamp that fits into fixture just like a fluorescent lamp.

Lamp Specifcations:

Our T8 LED lamps are available in 2 or 4 ft sizes in different wattage, lumens and color temperature options. Savegreen Lighting is a premier supplier of LED T8 lamps and makes a variety of Bypass T8 lamps to meet the needs of your special application. Options include more energy efficient 12W, 15W and 17W lamps with Premium 10 Year warranty as well as high output options up to 3500 lumens. Double ended LED T8 lamps are also available. See lamp options and specs at www.savegreenlighting.com.

Optional Dimming Options:

The 4 FT lamps are available with two dimming options; Specially designed dimming lamps require an external driver that runs 1 or 2 lamps. So more than 2 lamps require multiple external drivers or Consult for Bypass Type B lamps that can be dimmed without any external driver and dim with standard 2 wire dimming. See dimming options and specs at www. saylite.com.

Emergency Options:

The standard X1 LED Lamps require an inverter or an All-inone emergency kit that includes LED array, battery and driver. Dimmable T8 LED with external driver works with standard LED EM. For a 5 watt inverter that is similar to adding a 500 Lumen emergency in a conventional fluorescent fixture, add "INV5W" to the end of the item number. This will allow 5 watts of one lamp to work in emergency mode. Or add "EMKT12" to the end of the item number to get a 12W stand alone emergency kit in the fixture that comes with a driver, battery and small LED array that works in Emergency mode. See emergency options and specs at www.saylite.com.



Catalog	Number:	

Notes:





Texas Fluorescents

Reinvented

Ordering Options

(Fixtures below include LED T8 Lamp LT8ABP48L18W2250LXXK. For Other Lamp Options See below and Replace LNXXX with short code below. Specify without Lamps by removing LNXXX)

ITEM NO.	DESCRIPTION	
555MW232X1LN18W40	4ft. Wall 4500 Lumen 2x18W LED T8 4000K Lamps Included	

For 5W Emergency, Add INV5 at the End of Item Number for KTEMRGLED5500AC. See other options at www.saylite.com

For fixtures wired for double ended lamps, change X1 to X2 and see the Savegreen Lamps below for the proper Double Ended Lamp. For fixtures without lamps included, remove the "LNXXX" at the end of the item number and have X1 or X2 for Single or Double Ended wiring.

LN18W40 - Lamp Specification		
50,000 Hour Life with 5 Year Warranty		
Beam Angle 140 Degree		
Aluminum Base and Aluminum Housing with Glass Cover		
Operating Temperature: - 20C to 50C		
Color Temperature: 3500K, 4000K, 5000K		
G13 Pins (Same as Fluorescent Linear T8 Bipin)		
AC100 – 277V without Ballast		
Single Ended or Double Ended Power (If not specified use X1 Single Ended Power)		

Savegreen T8 or T5 LED Lamp Options

To include one of these lamps in fixture, remove "LNXXX" and add Savegreen Inside code below.

(See www.savegreenlighting.com for specification sheets or more information on these lamp options.)

VERSION	SAVEGREEN INSIDE	SAVEGREEN ITEM NO.	
Popular	SGB15W35	LT8BG48L15W1740LXXK]
Standard	SGS29W35	LT8BGC24L9W1050LXXK	
Standard	SGS312W35	LT8BGC36L12W1200LXXK	
Standard	SGS15W35	LT8BGC48L15W1740LXXK	
Premium	SGP12W35	L10T8BGC48L12W1750LXXK	10-YEAR
Premium	SGP15W35	L10T8BGC48L15W2000LXXK	WARRANTY
Premium	SGP18W35	L10T8BGC48L18W2500LXXK]
High Output	SGH26W40	LT8BGC48L26W3500LXXK	
Double Ended	SGD18W35	LT8BDGC48L18W2100LXXK	
T5HO	SGT525W40*	LT5BG46L25W3300LXXK]
Magic	SGM18W35K	LT8ABP48L18W2250LXXK]
Magic	SGM18W35K	LT8ABP48L15W1875LXXK]
Magic	SGM215W35K	LT8ABP24L15W1875LXXK]

Change 35 to 40 or 50 for different Kelvin. *For T5, CCT 40K and 50K available.



Catalog	Number [.]
Catalog	numper.

Notes: