



JOB NAME:

CAT#:

TYPE:

FEATURES & BENEFITS

- Input Voltage: 120VAC, 56/60Hz
- Input Current: 150mA ± 10%
- L₇₀ >36000 hrs
- Ambient Temperature: -20°C to +50°C
- Min CRI 80
- CCT: 4000K (Consult for other color temperatures)
- Suitable for damp locations
- Fixture is linkable and can be hard wired or use power cord.
- Fixture comes with power cord, knock-connector and joiner cable.
- Fixture comes with rocker switch installed



DIMENSIONS

- 9”L x 5”W x 1”H
- 12”L x 5”W x 1”H
- 18”L x 5”W x 1”H
- 24”L x 5”W x 1”H
- 33”L x 5”W x 1”H
- 42”L x 5”W x 1”H

ORDERING

EXAMPLE: MLUC 9 L 5W E120 40

MLUC

1. SERIES	2. SIZE	3. ROW CONNECTION	4. WATTAGE/LUMENS	5. DRIVER	6. COLOR TEMP
MLUC	9 9”	L Linkable	9 in.	E120 Electronic 120V only	MCT 3000K, 3500K, 4000K Color selectable
LED Under Cabinet Fixture	12 12”		5W 5 Watts 250 Lumens		
	18 18”		12 in.		
	24 24”		6W 6 Watts 300 Lumens		
	33 33”		18 in.		
	42 42”		9W 9 Watts 450 Lumens		
			24 in.		
			11W 11 Watts 550 Lumens		
			33 in.		
			13W 13 Watts 650 Lumens		
			42 in.		
			16W 16 Watts 900 Lumens		

NOTE: Values shown are typical or recorded under standardized conditions at 25°C. Actual performance may vary based on environment or application. Specifications are subject to change without notice. We reserve the right to change design, materials, LED's and finish in any way that will not alter installed appearance or reduce function and performance.



JOB NAME:

CAT#:

TYPE:

ACCESSORIES



Knock-out Connector



39" Power Cord



6" Joiner Cable

DIMENSIONS

