



JOB NAME:


CAT#:

TYPE:

APPLICATIONS

The Square/Rectangle

Transform the lighting in your space using PGN44 (polygon 4"x4") series fixtures to provide bright, white and energy efficient illumination. Choose different bracket styles and fixture lengths to construct a completely customizable lighting system with uplight and downlight options, such as squares or rectangles. Instantly revamp the look and feel of your space with interesting luminaires.





FEATURES & BENEFITS

- 4 standard fixture sizes – 24", 48", 72", and 96"
- Customizable bracket colors available
- Pendant mount for most ceilings
- Many lumen package / wattage options via programmable drivers
- CRI >80 (90 CRI available)
- >50,000 hrs of L70 LED life
- Power factor >0.90

DIMENSIONS

| Part | L | W |
|----------------|------|------|
| PGN44-P34X34 | 34" | 34" |
| PGN44-P58X58 | 58" | 58" |
| PGN44-P82X82 | 82" | 82" |
| PGN44-P108X108 | 108" | 108" |

L = Length
W = Width



90° Bracket

Dimensions and specifications subject to change without notice.





JOB NAME:

CAT#:

TYPE:

ORDERING

EXAMPLE: PGN44 P 34X34 LED 96 DMV BK SF 30 RD EM14 -SQ

PGN44

P

LED

| 1. SERIES | 2. MOUNTING | 3. WIDTH X LENGTH ¹ | 4. GEAR | 5. DISTRIBUTION | 6. WATTAGE/LUMENS ² | 7. DRIVER |
|--------------|------------------|--|------------|--|--|---|
| PGN44 | P Pendant | 34X34 34"W x 34"L 58X58 58"W x 58"L 82X82 82"W x 82"L 108X108 108"W x 108"L | LED | Blank Downlight (std.) 1U2D Uplight and Downlight | Downlight 34X34 in. 96 96 Watts 9600 Lumens 58X58 in. 192 192 Watts 19200 Lumens 82X82 in. 288 288 Watts 28800 Lumens 108X108 in. 384 384 Watts 38400 Lumens 1 Up and 2 Down Only 34X34 in. 152 152 Watts 5600U-9600D 58X58 in. 304 304 Watts 11200U-19200D 82X82 in. 456 456 Watts 16800U-28800D 108X108 in. 608 608 Watts 22400U-38400D | DMV 120-277V Multivolt 0-10V Dimmable |

| 8. FINISH ³ | 9. LENS | 10. CRI | 11. COLOR TEMP | 12. FLAIR ⁴ | 13. EM (O) ⁶ | 15. CONFIGURATION |
|--|---|--------------------------------|--|---|---|---|
| BK Black SI Silver WH White | SF Snap-in Frosted Acrylic Lens (85% transmission) | Blank 80 9 90 | 30 3000K 35 3500K 40 4000K 50 5000K | RD Red BL Blue BK Matte Black | EM14 14W Emergency Battery Backup ⁵ | -SQ Square -RT Rectangle |

Notes:

- ¹Square/rectangle configurations are measured by an overall system width and length.
- ²Wattage and lumen values are total for the system. Minimum fixture wattage of 10W. Minimum 5W per fixture foot uplight and downlight. Maximum 9W per fixture foot uplight and 18W per fixture foot downlight. Power feed cable is 18AWG, power drop is required every 800W or 48 feet for 0-10V dimming, whichever comes first. EM not available in fixtures with sections 2' and shorter if there is uplight and downlight.
- ³Consult for custom finish options
- ⁴Consult for custom flair options
- ⁵Emergency battery backup is integrated in fixtures 4' and longer
- ⁶(O) is optional



Dimensions and specifications subject to change without notice.



JOB NAME:

CAT#:

TYPE:

FLAIR BRACKET COLORS AND FINISHES



Gloss Black
(GB)




Matte Black
(BK)




Matte Silver
(SL)




Statuary Bronze
(BZ)



Glimmer (Iron)
(IR)



Safety Yellow
(YL)



Safety Orange
(OR)



Red
(RD)



Fire Engine Red
(FR)



Blue
(BL)

NOTE: Factory offers any Tiger Drylac RAL finish, contact Saylite for more information. Consult factory for information on specialty "real wood" finishes.

Dimensions and specifications subject to change without notice.





JOB NAME:

CAT#:

TYPE:


APPLICATIONS

The Hexagon

Transform the lighting in your space using PGN44 (polygon 4"x4") series fixtures to provide bright, white and energy efficient illumination. Choose different bracket styles and fixture lengths to construct a completely customizable lighting system with uplight and downlight options, such as The Hexagon. Instantly revamp the look and feel of your space with interesting luminaires.




FEATURES & BENEFITS

- 4 standard fixture sizes – 24", 48", 72", and 96"
- Customizable bracket colors available
- Pendant mount for most ceilings
- Many lumen package / wattage options via programmable drivers
- CRI >80 (90 CRI available)
- >50,000 hrs of L70 LED life
- Power factor >0.90



DIMENSIONS

| Part | D | D = Diameter |
|------------|------|--------------|
| PGN44-P61 | 61" | |
| PGN44-P108 | 108" | |
| PGN44-P156 | 156" | |
| PGN44-P204 | 204" | |



Dimensions and specifications subject to change without notice.



JOB NAME:

CAT#:

TYPE:

ORDERING

EXAMPLE: PGN44 P 108 LED 1U2D 456 DMV BK SF 30 RD EM14 -HX

PGN44

P

LED

| 1. SERIES | 2. MOUNTING | 3. DIAMETER ¹ | 4. GEAR | 5. DISTRIBUTION | 6. WATTAGE/LUMENS ² | 7. DRIVER |
|--------------|------------------|--|------------|--|--|--|
| PGN44 | P Pendant | 61 61" Dia. 108 108" Dia. 156 156" Dia. 204 204" Dia. | LED | Blank Downlight (std.) 1U2D Uplight and Downlight | Downlight 61 in. 144 Watts 14400 Lumens 108 in. 288 Watts 28800 Lumens 156 in. 432 Watts 43200 Lumens 204 in. 576 Watts 57600 Lumens 1 Up and 2 Down Only 61 in. 228 Watts 8400U-14400D 108 in. 456 Watts 16800U-28800D 156 in. 684 Watts 25200U-43200D 204 in. 912 Watts 33600U-57600D | DMV 120-277V Multivolt 0-10V Dimmable |

| 8. FINISH ³ | 9. LENS | 10. CRI | 11. COLOR TEMP | 12. FLAIR ⁴ | 13. EM (O) ⁶ | 15. CONFIGURATION |
|--|---|--------------------------------|--|--|---|--------------------|
| BK Black SI Silver WH White | SF Snap-in Frosted Acrylic Lens (85% transmission) | Blank 80 9 90 | 30 3000K 35 3500K 40 4000K 50 5000K | RD Red BL Blue BK Matte Black | EM14 14W Emergency Battery Backup ⁵ | -HX Hexagon |

Notes:

- ¹Hexagon configurations are measured by overall system diameter.
- ²Wattage and lumen values are total for the system. Minimum fixture wattage of 10W. Minimum 5W per fixture foot uplight and downlight. Maximum 9W per fixture foot uplight and 18W per fixture foot downlight. Power feed cable is 18AWG, power drop is required every 800W or 48 feet for 0-10V dimming, whichever comes first. EM not available in fixtures with sections 2 and shorter if there is uplight and downlight.
- ³Consult for custom finish options
- ⁴Consult for custom flair options
- ⁵Emergency battery backup is integrated in fixtures 4' and longer
- ⁶(O) is optional



Dimensions and specifications subject to change without notice.



JOB NAME:

CAT#:

TYPE:


FLAIR BRACKET COLORS AND FINISHES



Gloss Black
(GB)




Matte Black
(BK)




Matte Silver
(SL)




Statuary Bronze
(BZ)



Glimmer (Iron)
(IR)



Safety Yellow
(YL)



Safety Orange
(OR)



Red
(RD)



Fire Engine Red
(FR)



Blue
(BL)

NOTE: Factory offers any Tiger Drylac RAL finish, contact Saylite for more information. Consult factory for information on specialty "real wood" finishes.

Dimensions and specifications subject to change without notice.





JOB NAME:


CAT#:

TYPE:

APPLICATIONS

The Octagon

The Transform Series creates a new method for customizing the lighting in your space. Choose from multiple different bracket styles and fixture lengths to construct a unique, personalized lighting system. The popular 44P fixtures provide bright, white and energy efficient illumination with up and down lighting options. Rejuvenate your space with an interesting custom fixture!





FEATURES & BENEFITS

- 4 standard fixture sizes – 24", 48", 72", and 96"
- Customizable bracket colors available
- Pendant mount for most ceilings
- Many lumen package / wattage options via programmable drivers
- CRI >80 (90 CRI available)
- >50,000 hrs of L70 LED life
- Power factor >0.90


DIMENSIONS

| Part | D |
|----------------|------|
| PGN44-P34X34 | 77" |
| PGN44-P58X58 | 140" |
| PGN44-P82X82 | 203" |
| PGN44-P108X108 | 265" |

D = Diameter



135° Bracket



Dimensions and specifications subject to change without notice.





JOB NAME:

CAT#:

TYPE:

ORDERING

EXAMPLE: PGN44-P 203 LED 576 DMV BK SF 30 RD EM14 -OT

PGN44 — P

LED

| 1. SERIES | 2. MOUNTING | 3. DIAMETER ¹ | 4. GEAR | 5. DISTRIBUTION | 6. WATTAGE/LUMENS ² | 7. DRIVER |
|-----------------------------|------------------|--|------------|--|---|--|
| PGN44 | P Pendant | 77 77" Dia. 140 140" Dia. 203 203" Dia. 265 265" Dia. | LED | Blank Downlight (std.) 1U2D Uplight and Downlight | Downlight 77 in. 192 192 Watts 19200 Lumens 140 in. 384 384 Watts 19200 Lumens 203 in. 576 576 Watts 57600 Lumens 265 in. 768 768 Watts 76800 Lumens | DMV 120-277V Multivolt 0-10V Dimmable |
| 1 Up and 2 Down Only | | | | | | |
| | | | | | 77 in. 304 304 Watts 11200U-19200D 140 in. 608 608 Watts 22400U-38400D 203 in. 912 912 Watts 33600U-57600D 265 in. 1216 1216 Watts 44800U-76800D | |

| 8. FINISH ³ | 9. LENS | 10. CRI | 11. COLOR TEMP | 12. FLAIR ⁴ | 13. EM (O) ⁶ | 15. CONFIGURATION |
|--|---|--------------------------------|--|--|---|--------------------|
| BK Black SI Silver WH White | SF Snap-in Frosted Acrylic Lens (85% transmission) | Blank 80 9 90 | 30 3000K 35 3500K 40 4000K 50 5000K | RD Red BL Blue BK Matte Black | EM14 14W Emergency Battery Backup ⁵ | -OT Octagon |

Notes:

- ¹Octagon configurations are measured by an overall system diameter.
- ²Wattage and lumen values are total for the system. Minimum fixture wattage of 10W. Minimum 5W per fixture foot uplight and downlight. Maximum 9W per fixture foot uplight and 18W per fixture foot downlight. Power feed cable is 18AWG, power drop is required every 800W or 48 feet for 0-10V dimming, whichever comes first. EM not available in fixtures with sections 2' and shorter if there is uplight and downlight.
- ³Consult for custom finish options
- ⁴Consult for custom flair options
- ⁵Emergency battery backup is integrated in fixtures 4' and longer
- ⁶(O) is optional



Dimensions and specifications subject to change without notice.



JOB NAME:

CAT#:

TYPE:


FLAIR BRACKET COLORS AND FINISHES



Gloss Black
(GB)




Matte Black
(BK)




Matte Silver
(SL)




Statuary Bronze
(BZ)



Glimmer (Iron)
(IR)



Safety Yellow
(YL)




Safety Orange
(OR)



Red
(RD)



Fire Engine Red
(FR)



Blue
(BL)

NOTE: Factory offers any Tiger Drylac RAL finish, contact Saylite for more information. Consult factory for information on specialty "real wood" finishes.

Dimensions and specifications subject to change without notice.






JOB NAME:

CAT#:

TYPE:

APPLICATIONS


Transform the lighting in your space using PGN44 (polygon 4"x4") series fixtures to provide bright, white and energy efficient illumination. Choose different bracket styles and fixture lengths to construct a completely customizable lighting system with uplight and downlight options. Instantly revamp the look and feel of your space with interesting luminaires!




FEATURES & BENEFITS

- 4 standard fixture sizes – 24", 48", 72", and 96"
- Customizable bracket colors available
- Pendant mount for most ceilings
- Many lumen package / wattage options via programmable drivers
- CRI >80 (90 CRI available)
- >50,000 hrs of L70 LED life
- Power factor >0.90

EXAMPLE CONFIGURATION PATTERNS*



C01 - Pattern 01



C02- Pattern 02

*NOTE: The patterns above are examples, please consult the factory to design your own custom pattern. All custom patterns require design and drawing approval.

Dimensions and specifications subject to change without notice.






JOB NAME:



CAT#:

TYPE:



BRACKET DIMENSIONS





90° Bracket





120° Bracket





135° Bracket





180° Bracket




120° Y Bracket



90° X Bracket



End Cap Bracket



Dimensions and specifications subject to change without notice.





JOB NAME:

CAT#:

TYPE:

FLAIR BRACKET COLORS AND FINISHES




Gloss Black
(GB)



Matte Black
(BK)




Matte Silver
(SL)




Statuary Bronze
(BZ)



Glimmer (Iron)
(IR)



Safety Yellow
(YL)



Safety Orange
(OR)



Red
(RD)



Fire Engine Red
(FR)



Blue
(BL)

NOTE: Factory offers any Tiger Drylac RAL finish, contact Saylite for more information. Consult factory for information on specialty "real wood" finishes.

Dimensions and specifications subject to change without notice.

