

Polygon 44P Series

The Hexagon

The Polygon 44P Series creates a new method for customizing the lighting in your space. Choose from multiple different bracket styles and fixture lengths to construct a unique, personalized lighting system. The popular 44P fixtures provide bright, white and energy efficient illumination with up and down lighting options. Rejuvenate your space with an interesting custom fixture!

CONSTRUCTION


Fixture housing is welded and die-formed 22 gauge powder coated cold-rolled steel; brackets are fabricated from 18 gauge cold-rolled steel.

OPTIONS

14W emergency battery backup integrated in fixtures 4 ft and up.

FLAIR

Customize the color of your brackets and/or end caps to add flair to your unique hanging luminaire system. Consult factory for more information.



DIMENSIONS

24" 44P: 60" Nominal Dia.
48" 44P: 108" Nominal Dia.
72" 44P: 156" Nominal Dia.
96" 44P: 204" Nominal Dia.

SPECIFICATIONS

- 4 standard fixture sizes – 24", 48", 72", and 96"
- Customizable bracket colors available
- Pendant mount for most ceilings
- Many lumen package / wattage options via programmable drivers
- Multiple Kelvin temperature options (3000K, 3500K, 4000K, 5000K)
- Emergency battery backup options available
- CRI >80 (90 CRI available)
- >50,000 hrs of L70 LED life
- Rated for dry and damp locations
- 0-10 Volt dimmable 120-277V (120V ELV/TRIAC avail)
- Power factor >0.90
- 5 year warranty

CATALOG# :

PROJECT :

TYPE :

Polygon 44P Series

Geometric 44P Pendant Bracket System

ORDERING GUIDE

Factory at your fingertips. Fill in the blanks to create your part number or create a custom configuration.

Sample Part Number: PLY44 -SF-108-LR-U168-D288-DMV-WH-30K-SL-EM14-HX

SERIES	DIFFUSER	DIAMETER ¹	GEAR	WATTAGE & LUMENS* ²
PLY44	SF Snap-in Frosted acrylic	60 60" Dia.	L	Up & Down UR84D144 Uplight 84W & 8400 Lumens, Downlight 144W & 14400 Lumens
				Down Only R144 Downlight 144W & 14400 Lumens
				Up & Down UR168D288 Uplight 168W & 16800 Lumens, Downlight 288W & 28800 Lumens
				Down Only R288 Downlight 288W & 28800 Lumens
		108 108" Dia.	L	Up & Down UR252D432 Uplight 252W & 25200 Lumens, Downlight 432W & 43200 Lumens
				Down Only R432 Downlight 432W & 43200 Lumens
				Up & Down UR336D576 Uplight 336W & 33600 Lumens, Downlight 576W & 57600 Lumens
				Down Only R576 Downlight 576W & 57600 Lumens
		156 156" Dia.	L	Up & Down UR252D432 Uplight 252W & 25200 Lumens, Downlight 432W & 43200 Lumens
				Down Only R432 Downlight 432W & 43200 Lumens
				Up & Down UR336D576 Uplight 336W & 33600 Lumens, Downlight 576W & 57600 Lumens
				Down Only R576 Downlight 576W & 57600 Lumens
		204 204" Dia.	L	Up & Down UR336D576 Uplight 336W & 33600 Lumens, Downlight 576W & 57600 Lumens
				Down Only R576 Downlight 576W & 57600 Lumens

DRIVER	FINISH	CCT	FLAIR ³	OPTIONS
DMV 0-10V Dimming	WH White	30K 3000K	SL Silver	EMERGENCY EM14 14W Emergency battery backup (integrated in fixtures 4ft and over)
DMV11 0-10V Dimming Separate drivers for uplight and downlight	BK Black	35K 3500K	BK Black	CONFIGURATION HX Hexagon
	SL Silver	40K 4000K	RD Red	
		50K 5000K		

Note:

- Width and length measured as overall system diameter, dimensions will change for each custom pattern created.
- Values shown are per fixture. Minimum fixture wattage of 10W. Minimum 5W per fixture foot uplight and downlight. Maximum 9W per fixture foot uplight and 18W per fixture foot downlight. Power feed cable is 18AWG, power drop is required every 800W or 48 feet for 1-10V dimming, whichever comes first. EM not available in fixtures with sections 2' and shorter if there is uplight and downlight.
- NEW! Personalize your lighting even further by choosing a standard flair color for your brackets, at no additional cost, from the guide on the following page.
- Create your own custom pattern to fit your space! All custom patterns require design and drawing approval, contact factory for more information.
- HC712 hanging kit comes standard with PLY44 fixtures. Consult factory for other options.

*Programmable LED drivers allow custom configured wattages and corresponding lumens.

We reserve the right to change design, materials, LED's and finish in any way that will not alter installed appearance or reduce function and performance.


STANDARD FLAIR BRACKET COLORS AND FINISHES



Gloss Black
(GB)




Matte Black
(BK)




Matte Silver
(SL)




Statuary Bronze
(BZ)



Glimmer (Iron)
(IR)




Safety Yellow
(YL)




Safety Orange
(OR)



Red
(RD)



Fire Engine Red
(FR)



Blue
(BL)

NOTE: Factory offers any Tiger Drylac RAL finish, contact Saylite for more information. Consult factory for information on specialty "real wood" finishes.

CATALOG# : _____


PROJECT : _____

TYPE : _____


Polygon 44P Series

Geometric 44P Pendant Bracket System


PRODUCT DIMENSIONS



Sample Part Number	Diameter
PLY44SF60LUR84D144DMVWH30KBK-HX	61 in.
PLY44SF108LUR168D288DMVWH30KBK-HX	108 in.
PLY44SF156LUR252D432DMVWH30KBK-HX	156 in.
PLY44SF204LUR336D576DMVWH30KBK-HX	204 in.



120° Bracket



Polygon 44P Series

The Octagon

The Polygon 44P Series creates a new method for customizing the lighting in your space. Choose from multiple different bracket styles and fixture lengths to construct a unique, personalized lighting system. The popular 44P fixtures provide bright, white and energy efficient illumination with up and down lighting options. Rejuvenate your space with an interesting custom fixture!

CONSTRUCTION


Fixture housing is welded and die-formed 22 gauge powder coated cold-rolled steel; brackets are fabricated from 18 gauge cold-rolled steel.

OPTIONS

14W emergency battery backup integrated in fixtures 4 ft and up.

FLAIR

Customize the color of your brackets and/or end caps to add flair to your unique hanging luminaire system. Consult factory for more information.



DIMENSIONS

24" 44P: 77" Nominal Dia.
48" 44P: 140" Nominal Dia.
72" 44P: 203" Nominal Dia.
96" 44P: 265" Nominal Dia.

SPECIFICATIONS

- 4 standard fixture sizes – 24", 48", 72", and 96"
- Customizable bracket colors available
- Pendant mount for most ceilings
- Many lumen package / wattage options via programmable drivers
- Multiple Kelvin temperature options (3000K, 3500K, 4000K, 5000K)
- Emergency battery backup options available
- CRI >80 (90 CRI available)
- >50,000 hrs of L70 LED life
- Rated for dry and damp locations
- 0-10 Volt dimmable 120-277V (120V ELV/TRIAC avail)
- Power factor >0.90
- 5 year warranty



CATALOG# :

PROJECT :

TYPE :

Polygon 44P Series

Geometric 44P Pendant Bracket System

ORDERING GUIDE

Factory at your fingertips. Fill in the blanks to create our part number or create a custom configuration.

Sample Part Number: *PLY44 -SF-77-LR-U112-D192-DMV-WH-30K-SL-EM14-OT*

SERIES	DIFFUSER	DIAMETER ¹	GEAR	WATTAGE & LUMENS ^{*2}
PLY44	SF Snap-in Frosted acrylic	77	L	Up & Down UR112D192 Uplight 112W & 11200 Lumens, Downlight 192W & 19200 Lumens
				Down Only R192 Downlight 192W & 19200 Lumens
		140	L	Up & Down UR224D384 Uplight 224W & 22400 Lumens, Downlight 384W & 38400 Lumens
				Down Only R384 Downlight 384W & 38400 Lumens
		203	L	Up & Down UR336D576 Uplight 336W & 33600 Lumens, Downlight 576W & 57600 Lumens
				Down Only R576 Downlight 576W & 57600 Lumens
		265	L	Up & Down UR448D768 Uplight 448W & 44800 Lumens, Downlight 768W & 76800 Lumens
				Down Only R768 Downlight 768W & 76800 Lumens

DRIVER	FINISH	CCT	FLAIR ³	OPTIONS
DMV 0-10V Dimming	WH White	30K 3000K	SL Silver	EMERGENCY EM14 14W Emergency battery backup (integrated in fixtures 4ft and over)
DMV11 0-10V Dimming Separate drivers for uplight and downlight	BK Black	35K 3500K	BK Black	CONFIGURATION OT Octagon
	SL Silver	40K 4000K	RD Red	
		50K 5000K		

Note:

- Width and length measured as overall system diameter, dimensions will change for each custom pattern created.
- Values shown are per fixture. Minimum fixture wattage of 10W. Minimum 5W per fixture foot uplight and downlight. Maximum 9W per fixture foot uplight and 18W per fixture foot downlight. Power feed cable is 18AWG, power drop is required every 800W or 48 feet for 0-10V dimming, whichever comes first. EM not available in fixtures with sections 2' and shorter if there is uplight and downlight. Two power drops required when 96" fixtures are chosen.
- NEW! Personalize your lighting even further by choosing a standard flair color for your brackets, at no additional cost, from the guide on the following page.
- Create your own custom pattern to fit your space! All custom patterns require design and drawing approval, contact factory for more information.
- HC712 hanging kit comes standard with PLY44 fixtures. Consult factory for other options.

*Programmable LED drivers allow custom configured wattages and corresponding lumens.

We reserve the right to change design, materials, LED's and finish in any way that will not alter installed appearance or reduce function and performance.

CATALOG# : _____

PROJECT : _____

TYPE : _____

Polygon 44P Series

Geometric 44P Pendant Bracket
System


STANDARD FLAIR BRACKET COLORS AND FINISHES



Gloss Black
(GB)




Matte Black
(BK)




Matte Silver
(SL)




Statuary Bronze
(BZ)



Glimmer (Iron)
(IR)




Safety Yellow
(YL)




Safety Orange
(OR)



Red
(RD)



Fire Engine Red
(FR)



Blue
(BL)

NOTE: Factory offers any Tiger Drylac RAL finish, contact Saylite for more information. Consult factory for information on specialty "real wood" finishes.

CATALOG# :


PROJECT :

TYPE :


Polygon 44P Series

Geometric 44P Pendant Bracket System


PRODUCT DIMENSIONS



Sample Part Number	Diameter
PLY44SF77LUR112D192DMVWH30KBK-OT	77 in.
PLY44SF140LUR224D384DMVWH30KBK-OT	140 in.
PLY44SF203LUR336D576DMVWH30KBK-OT	203 in.
PLY44SF265LUR448D768DMVWH30KBK-OT	265 in.



135° Bracket



Polygon 44P Series

The Rectangle

The Polygon 44P Series creates a new method for customizing the lighting in your space. Choose from multiple different bracket styles and fixture lengths to construct a unique, personalized lighting system. The popular 44P fixtures provide bright, white and energy efficient illumination with up and down lighting options. Rejuvenate your space with an interesting custom fixture!

CONSTRUCTION


Fixture housing is welded and die-formed 22 gauge powder coated cold-rolled steel; brackets are fabricated from 18 gauge cold-rolled steel.

OPTIONS

14W emergency battery backup integrated in fixtures 4 ft and up.

FLAIR

Customize the color of your brackets and/or end caps to add flair to your unique hanging luminaire system. Consult factory for more information.



DIMENSIONS

24" 44P: 34"L x 34"W x 4.05"H
48" 44P: 58"L x 58"W x 4.05"H
72" 44P: 82"L x 82"W x 4.05"H
96" 44P: 106"L x 106"W x 4.05"H

SPECIFICATIONS

- 4 standard fixture sizes – 24", 48", 72", and 96"
- Customizable bracket colors available
- Pendant mount for most ceilings
- Many lumen package / wattage options via programmable drivers
- Multiple Kelvin temperature options (3000K, 3500K, 4000K, 5000K)
- Emergency battery backup options available
- CRI >80 (90 CRI available)
- >50,000 hrs of L70 LED life
- Rated for dry and damp locations
- 0-10 Volt dimmable 120-277V (120V ELV/TRIAC avail)
- Power factor >0.90
- 5 year warranty



CATALOG# :

PROJECT :

TYPE :

Polygon 44P Series

Geometric 44P Pendant Bracket System

ORDERING GUIDE

Factory at your fingertips. Fill in the blanks to create your part number or create a custom configuration.

Sample Part Number: PLY44 -SF-34X58-LR-U84-D144-DMV-WH-30K-SL-EM14-SQ

SERIES	DIFFUSER	WIDTH X LENGTH ¹	GEAR	WATTAGE & LUMENS* ²
PLY44	SF Snap-in Frosted acrylic	34X58 34"W x 58"L	L	UR84D144 Uplight 84W & 8400 Lumens, Downlight 144W & 14400 Lumens
				R144 Downlight 144W & 14400 Lumens
		34X82 34"W x 82"L	L	UR112D192 Uplight 112W & 11200 Lumens, Downlight 192W & 19200 Lumens
				R192 Downlight 192W & 19200 Lumens
		34X106 34"W x 106"L	L	UR140D240 Uplight 140W & 14000 Lumens, Downlight 240W & 24000 Lumens
				R240 Downlight 240W & 24000 Lumens
		58X82 58"W x 82"L	L	UR140D240 Uplight 140W & 14000 Lumens, Downlight 240W & 24000 Lumens
				R240 Downlight 240W & 24000 Lumens

DRIVER	FINISH	CCT	FLAIR ³	OPTIONS
DMV 0-10V Dimming	WH White	30K 3000K	SL Silver	EMERGENCY EM14 14W Emergency battery backup (integrated in fixtures 4ft and over)
DMV11 0-10V Dimming Separate drivers for uplight and downlight	BK Black	35K 3500K	BK Black	CONFIGURATION SQ Square
	SL Silver	40K 4000K	RD Red	
		50K 5000K		

Note:

- Width and length measured as overall system dimensions, dimensions will change for each custom pattern created.
- Values shown are per fixture. Minimum fixture wattage of 10W. Minimum 5W per fixture foot uplight and downlight. Maximum 9W per fixture foot uplight and 18W per fixture foot downlight. Power feed cable is 18AWG, power drop is required every 800W or 48 feet for 1-10V dimming, whichever comes first. EM not available in fixtures with sections 2' and shorter if there is uplight and downlight.
- NEW! Personalize your lighting even further by choosing a standard flair color for your brackets, at no additional cost, from the guide on the following page.
- Create your own custom pattern to fit your space! All custom patterns require design and drawing approval, contact factory for more information.
- HC712 hanging kit comes standard with PLY44 fixtures. Consult factory for other options.

*Programmable LED drivers allow custom configured wattages and corresponding lumens.

We reserve the right to change design, materials, LED's and finish in any way that will not alter installed appearance or reduce function and performance.

CATALOG# :

PROJECT :

TYPE :

Polygon 44P Series

Geometric 44P Pendant Bracket System

ORDERING GUIDE

Factory at your fingertips. Fill in the blanks to create your part number or create a custom configuration.

Sample Part Number: PLY44-SF-58X106-LR-U168-D288-DMV-WH-30K-SL-EM14-SQ

SERIES	DIFFUSER	WIDTH X LENGTH ¹	GEAR	WATTAGE & LUMENS* ²
PLY44	SF Snap-in Frosted acrylic	58X106 58"W x 106"L	L	Up & Down UR168D288 Uplight 168W & 16800 Lumens, Downlight 288W & 28800 Lumens
				Down Only R288 Downlight 288W & 28800 Lumens
		82X106 82"W x 106"L	L	Up & Down UR196D336 Uplight 196W & 19600 Lumens, Downlight 336W & 33600 Lumens
				Down Only R336 Downlight 336W & 33600 Lumens

DRIVER	FINISH	CCT	FLAIR ³	OPTIONS
DMV 0-10V Dimming	WH White	30K 3000K	SL Silver	EMERGENCY EM14 14W Emergency battery backup (integrated in fixtures 4ft and over)
DMV11 0-10V Dimming Separate drivers for uplight and downlight	BK Black	35K 3500K	BK Black	CONFIGURATION SQ Square
	SL Silver	40K 4000K	RD Red	
		50K 5000K		

Note:

- Width and length measured as overall system dimensions, dimensions will change for each custom pattern created.
- Values shown are per fixture. Minimum fixture wattage of 10W. Minimum 5W per fixture foot uplight and downlight. Maximum 9W per fixture foot uplight and 18W per fixture foot downlight. Power feed cable is 18AWG, power drop is required every 800W or 48 feet for 1-10V dimming, whichever comes first. EM not available in fixtures with sections 2' and shorter if there is uplight and downlight.
- NEW! Personalize your lighting even further by choosing a standard flair color for your brackets, at no additional cost, from the guide on the following page.
- Create your own custom pattern to fit your space! All custom patterns require design and drawing approval, contact factory for more information.
- HC712 hanging kit comes standard with PLY44 fixtures. Consult factory for other options.

*Programmable LED drivers allow custom configured wattages and corresponding lumens.

We reserve the right to change design, materials, LED's and finish in any way that will not alter installed appearance or reduce function and performance.

CATALOG# : _____

PROJECT : _____

TYPE : _____

Polygon 44P Series

Geometric 44P Pendant Bracket
System


STANDARD FLAIR BRACKET COLORS AND FINISHES



Gloss Black
(GB)




Matte Black
(BK)




Matte Silver
(SL)




Statuary Bronze
(BZ)




Glimmer (Iron)
(IR)




Safety Yellow
(YL)




Safety Orange
(OR)



Red
(RD)



Fire Engine Red
(FR)



Blue
(BL)

NOTE: Factory offers any Tiger Drylac RAL finish, contact Saylite for more information. Consult factory for information on specialty "real wood" finishes.

CATALOG#:


PROJECT:

TYPE:


Polygon 44P Series

Geometric 44P Pendant Bracket System


PRODUCT DIMENSIONS



Sample Part Number	W	L
PLY44SF34X58LUR84D144DMVWH30KBK-RT	34 in.	58 in.
PLY44SF34X82LUR112D192DMVWH30KBK-RT	34 in.	82 in.
PLY44SF34X106LUR140D240DMVWH30KBK-RT	34 in.	106 in.
PLY44SF58X82LUR140D240DMVWH30KBK-RT	58 in.	82 in.
PLY44SF58X106LUR168D288DMVWH30KBK-RT	58 in.	106 in.
PLY44SF82X106LUR196D336DMVWH30KBK-RT	82 in.	106 in.



90° Bracket



Polygon 44P Series

The Square/Rectangle

The Polygon 44P Series creates a new method for customizing the lighting in your space. Choose from multiple different bracket styles and fixture lengths to construct a unique, personalized lighting system. The popular 44P fixtures provide bright, white and energy efficient illumination with up and down lighting options. Rejuvenate your space with an interesting custom fixture!

CONSTRUCTION


Fixture housing is welded and die-formed 22 gauge powder coated cold-rolled steel; brackets are fabricated from 18 gauge cold-rolled steel.

OPTIONS

14W emergency battery backup integrated in fixtures 4 ft and up.

FLAIR

Customize the color of your brackets and/or end caps to add flair to your unique hanging luminaire system. Consult factory for more information.



DIMENSIONS

24" 44P: 34"L x 34"W x 4.05"H
48" 44P: 58"L x 58"W x 4.05"H
72" 44P: 82"L x 82"W x 4.05"H
96" 44P: 106"L x 106"W x 4.05"H

SPECIFICATIONS

- 4 standard fixture sizes – 24", 48", 72", and 96"
- Customizable bracket colors available
- Pendant mount for most ceilings
- Many lumen package / wattage options via programmable drivers
- Multiple Kelvin temperature options (3000K, 3500K, 4000K, 5000K)
- Emergency battery backup options available
- CRI >80 (90 CRI available)
- >50,000 hrs of L70 LED life
- Rated for dry and damp locations
- 0-10 Volt dimmable 120-277V (120V ELV/TRIAC avail)
- Power factor >0.90
- 5 year warranty



CATALOG# :

PROJECT :

TYPE :

Polygon 44P Series

Geometric 44P Pendant Bracket System

ORDERING GUIDE

Factory at your fingertips. Fill in the blanks to create your part number or create a custom configuration. Sample Part Number: *PLY44 -SF-58X58-LR-U112-D192-DMV-WH-30K-SL-EM14-SQ*

SERIES	DIFFUSER	WIDTH X LENGTH ¹	GEAR	WATTAGE & LUMENS* ²
PLY44	SF Snap-in Frosted acrylic	34X34 34"W x 34"L	L	Up & Down UR56D96 Uplight 56W & 5600 Lumens, Downlight 96W & 9600 Lumens
				Down Only R96 Downlight 96W & 9600 Lumens
				Up & Down UR112D192 Uplight 112W & 11200 Lumens, Downlight 192W & 19200 Lumens
				Down Only R192 Downlight 192W & 19200 Lumens
		58X58 58"W x 58"L		Up & Down UR168D288 Uplight 168W & 16800 Lumens, Downlight 288W & 28800 Lumens
				Down Only R288 Downlight 288W & 28800 Lumens
				Up & Down UR224D384 Uplight 224W & 22400 Lumens, Downlight 384W & 38400 Lumens
				Down Only R384 Downlight 384W & 38400 Lumens
		82X82 82"W x 82"L		Up & Down UR168D288 Uplight 168W & 16800 Lumens, Downlight 288W & 28800 Lumens
				Down Only R288 Downlight 288W & 28800 Lumens
				Up & Down UR224D384 Uplight 224W & 22400 Lumens, Downlight 384W & 38400 Lumens
				Down Only R384 Downlight 384W & 38400 Lumens
		106X106 106"W x 106"L		Up & Down UR224D384 Uplight 224W & 22400 Lumens, Downlight 384W & 38400 Lumens
				Down Only R384 Downlight 384W & 38400 Lumens

DRIVER	FINISH	CCT	FLAIR ³	OPTIONS
DMV 0-10V Dimming	WH White	30K 3000K	SL Silver	EMERGENCY EM14 14W Emergency battery backup (integrated in fixtures 4ft and over)
DMV11 0-10V Dimming Separate drivers for uplight and downlight	BK Black	35K 3500K	BK Black	CONFIGURATION SQ Square
	SL Silver	40K 4000K	RD Red	
		50K 5000K		

Note:

- Width and length measured as overall system dimensions, dimensions will change for each custom pattern created.
- Values shown are per fixture. Minimum fixture wattage of 10W. Minimum 5W per fixture foot uplight and downlight. Maximum 9W per fixture foot uplight and 18W per fixture foot downlight. Power feed cable is 18AWG, power drop is required every 800W or 48 feet for 1-10V dimming, whichever comes first. EM not available in fixtures with sections 2' and shorter if there is uplight and downlight.
- NEW! Personalize your lighting even further by choosing a standard flair color for your brackets, at no additional cost, from the guide on the following page.
- Create your own custom pattern to fit your space! All custom patterns require design and drawing approval, contact factory for more information.
- HC712 hanging kit comes standard with PLY44 fixtures. Consult factory for other options.

*Programmable LED drivers allow custom configured wattages and corresponding lumens.

We reserve the right to change design, materials, LED's and finish in any way that will not alter installed appearance or reduce function and performance.

CATALOG# : _____

PROJECT : _____

TYPE : _____

Polygon 44P Series

Geometric 44P Pendant Bracket
System


STANDARD FLAIR BRACKET COLORS AND FINISHES



Gloss Black
(GB)




Matte Black
(BK)




Matte Silver
(SL)




Statuary Bronze
(BZ)




Glimmer (Iron)
(IR)




Safety Yellow
(YL)




Safety Orange
(OR)



Red
(RD)



Fire Engine Red
(FR)



Blue
(BL)

NOTE: Factory offers any Tiger Drylac RAL finish, contact Saylite for more information. Consult factory for information on specialty "real wood" finishes.

CATALOG#:


PROJECT:

TYPE:


Polygon 44P Series

Geometric 44P Pendant Bracket System

PRODUCT DIMENSIONS



Sample Part Number	W	L
PLY44SF34X34LUR56D96DMVWH30KBK-SQ	34 in.	34 in.
PLY44SF58X58LUR112D192DMVWH30KBK-SQ	58 in.	58 in.
PLY44SF82X82LUR168D288DMVWH30KBK-SQ	82 in.	82 in.
PLY44SF108X108LUR224D384DMVWH30KBK-SQ	108 in.	108 in.



90° Bracket

