


СА	Т	Α	L	0	G	#	

PROJECT:

TYPE:



LED High Bay Full Body



CONSTRUCTION


Housing is 22 gauge prepainted steel. Air vents surround the drivers in the back of the fixture to maximize LED and driver performance, reliability and life. High reflective enhanced white reflectors are computer designed to maximize photometric performance and put the light where you need it. Access plate in the back makes wiring fast and hassle-free. Back of fixture is designed with built-in mounting holes for tong hanger, cable kit.

MOUNTING

Designed for pendant or chain hanging. Mounting holes are provided for simple, fast installation. See Buyers Guide for list of all mounting options available and sold separately.

TYPICAL OPTIONS & ACCESSORIES

Emergency battery backup, Cord sets, whips, occupancy sensors, Hanging kits, Wire guards. Contact factory for additional options.



24L: 24.056"L x 20.385"W x 3.62"H 48L: 48.056"L x 11.369"W x 3.62"H (118W and below)

48L: 48.056"L x 16.385"W x 3.62"H (above 118W)

48L: 48.056"L x 20.385"W x 3.62"H (above 433W)

FEATURES & BENEFITS

- A sturdy/durable fixture body with superior appearance and appeal
- Ideal for commercial, retail and industrial applications
- Mounts easily with chain or cable kit
- Protected by an optional wire guard
- Suitable for dry or damp locations
- >50,000 hrs of L70 LED life
- · CRI >80
- 0-10 Volt dimmable 120-277V
- Power factor 0.99
- 5 year warranty







Texas Fluorescents Reinvented CATALOG#:
PROJECT:

TYPE:

Series HBC

LED High Bay Full Body

DRAWINGS & IMAGES













22L - 24.056"L x 20.385"W







48L - 48"L x 11.385"W







48L - 48"L x 16.385"W





48L - 48"L x 20.385"W







CATALOG#:		
PROJECT:		
PROJECT:		

Series HBC LED High Bay Full Body

ORDER INFORMATION

SERIES	LENS	MATERIAL		SIZES	WATTAGE &	LUMENS	RE	FLECTOR ²	DRIVER	CO	LOR
НВС	Blank	No lens	24L	24"Lx20.385"W	B65W10000L	65 Watts 10000 Lumens	W30	White Steel	DMV 0-10V Dimming DHV 347-480V	30K 35K	3000K 3500K
	L¹	Frosted Smooth Acrylic			B95W15000L	95 Watts 15000 Lumens		Reflector	DMVFID Factory install Dimming Wires	40K 50K	4000K 5000K
	DFFR	Door Frame			B130W20000L	130 Watts 20000 Lumens			(Option)		
		w/Frosted Lens			B165W25000L	165 Watts 25000 Lumens					
					B190W30000L	190 Watts 30000 Lumens					
			48L	48"L×11.385"W	Y65W10000L	65 Watts 10000 Lumens	A10	Aluminum Reflector			
					Y95W15000L	95 Watts 15000 Lumens					
					Y130W20000L	130 Watts 20000 Lumens					
			48L	48"Lx16.385"W	N127W18000L	127 Watts 18000 Lumens	A10	Aluminum Reflector			
					B162W26000L	162 Watts 26000 Lumens					
					B215W35000L	215 Watts 35000 Lumens					
					B260W40000L	260 Watts 40000 Lumens					
					B285W45000L	285 Watts 45000 Lumens					
					B320W50000L	320 Watts 50000 Lumens					
			48L	48"Lx20.385"W	X433W60000L	433 Watts 60000 Lumens	A10	Aluminum Reflector			
					*	*					

	OPTIONS
MDT4	Occupancy Sensor Wide Angle
MDF4	Occupancy Sensor and Daylight
MDT4480	Occupancy Sensor Wide Angle 480 Volt
cs	5-15P 120V 8ft Cord & Plug
CS12	L7-15P 277V 8ft Cord & Plug
CS08	8ft Cord No Plug
WP	6ft 3 Wire, Whip
WP10	6ft 4 Wire, Whip
EM	10W, 90 mins, 120-277VAC
WG	Wire Guard
LSXR610(xx)	Occupancy Sensor (Full On and Steps to XX% Level)

Nota:

*Programmable LED drivers allow custom configured wattages and corresponding lumens.

 $^{1}\textsc{Estimate}$ 10% lumen output loss with lens. Lens not available on 20.385" x 48" fixture size.

²W30 Reflector not compatible with 'L - Frosted Smooth Acrylic' lens option

We reserve the right to change design, materials, LED's and finish in any way that will not alter installed appearance or reduce function and performance.



CATALOG#:
PROJECT:
TYPE:

Series HBC LED High Bay Full Body

Item Number

HBC48LB162W26000LA10DHV50Koooo(not WG)
HBC48LB216W33000LA10DHV50Koooo(not WG)
HBC48LB247WA10DHV50Koooo(not WG)

