



JOB NAME:

CAT#:

TYPE:

APPLICATIONS

The CER is a round, commercial-grade wall or ceiling mounted fixture available in black or white, with frosted lens. Available with plain, grill, or eyelid lenses. Ideal for nautical applications. Wet location.

FEATURES & BENEFITS


- Available in black or white with frosted lenses
- Fade and rust resistant composite constructions
- High power factor
- cUL_{US} listed for wet locations
- 3 year warranty for MV and INC w/ lamp
- 5 year warranty for LED dimmable 120V Ambient temperature -40°C - +40°C
- Wall or ceiling mount



FC361




FC362




FC363

DIMENSIONS


FC361




HCMT: 5 1/8"




FC362




HCMT: 5 1/8"



FC363



HCMT: 5 1/8"





JOB NAME:

CAT#:

TYPE:

ORDERING

EXAMPLE: FC361 LE800 W W C P

LE800

| 1. STYLE | 2. LIGHT SOURCE | 3. COLOR TEMP | 4. BODY | 5. DIFFUSER | 6. OPTIONS ¹ |
|--|---|----------------------------------|----------------------------------|------------------|-------------------------|
| FC361 Plain Lens FC362 Eyelid Lens FC363 Grill Lens | LE800 13W Power Input, CRI 80 >88 Lumens Per Watt (TYP) | W 3000K C 4000K | W White B Black | F Frosted | P Photocell* |

ORDERING (INCANDESCENT)

EXAMPLE: FC361 I75 W C LWE

I75

| 1. STYLE | 2. LIGHT SOURCE | 3. BODY | 4. DIFFUSER | 5. LAMPING |
|--|------------------------|----------------------------------|---------------------------|--|
| FC361 Plain Lens FC362 Eyelid Lens FC363 Grill Lens | I75 1 X 75W Max | W White B Black | C Clear Flemish | LWE A19/E26, 3000K LCE A19/E26, 4000K |

Notes:

¹Photocell not available for FB255 style

