



JOB NAME:

CAT#:

TYPE:

APPLICATIONS

This unique LED Retrofit Kits is an energy efficient, easy to install solution to upgrade your fluorescent troffer to LED. Compatible with both standard and narrow T-grids, it offers a simple retrofit that will improve the look of your ceiling with its architectural styling without the need to actually break the ceiling plenum. This kit offers a true Indirect/Direct solution that not only provides more energy efficiency but also the true comfortable performance of an indirect/direct fixture designed especially for workspaces with CRTs. The main diffuser and slanted troffer help reduce glare and create a pleasant, uniform throw of light. With this kit, you will get the energy savings and performance of the latest technology without the fuss and mess of changing out fixtures completely.

The RKDISE retrofit kit is a great upgrade solution for converting fluorescent troffers to LED. The kit provides a stylish architectural look without breaking the ceiling plenum, and provides a more efficient solution with greater energy savings and the performance of the latest technology without the fuss and mess of changing out complete fixtures.



FEATURES & BENEFITS

- Input voltage 120-277VAC
- _cETL_{US} recognized as retrofit
- 0-10V Dimmable
- 5 year warranty
- THD <10%
- PF >0.95
- Min CRI 82

DIMENSIONS

1x4 - 48.0"L x 12.0"W x 3.65"H

2x2 - 23.97"L x 23.97"W x 3.65"H

2x4 - 48.0"L x 23.97"W x 3.65"H

NOTE: Values shown are typical or recorded under standardized conditions at 25°C. Actual performance may vary based on environment or application. Specifications are subject to change without notice. We reserve the right to change design, materials, LED's and finish in any way that will not alter installed appearance or reduce function and performance.





JOB NAME:

CAT#:

TYPE:

ORDERING

EXAMPLE: RKDISE 14 LED 17 DMV FR 30 SS

RKDISE		LED												
1. SERIES	2. SIZE	3. GEAR	4. WATTAGE/LUMENS		5. DRIVER		6. LENS		7. COLOR TEMP		8. EMERGENCY (O) ¹			
RKDISE	14 1X4	LED	1x4 Standard		DMV 120-277V Multivolt 0-10V Dimmable	FR Frosted	30 3000K 35 3500K 40 4000K 50 5000K	EM Emergency Battery Backup						
	22 2X2		17 17 Watts 2260 Lumens											
	24 2X4		22 22 Watts 2295 Lumens											
			24 24 Watts 3260 Lumens											
			30 30 Watts 4140 Lumens											
			32 32 Watts 4435 Lumens						SDMV Step dimming multivolt					
			35 35 Watts 4725 Lumens											
			40 40 Watts 5235 Lumens											
			45 45 Watts 5770 Lumens											
			50 50 Watts 6280 Lumens											
			2X2 Standard											
			17 17 Watts 2260 Lumens											
			18 18 Watts 2410 Lumens											
			20 20 Watts 2880 Lumens											
			24 24 Watts 3125 Lumens											
			28 28 Watts 3610 Lumens											
			30 30 Watts 3775 Lumens											
			35 35 Watts 4160 Lumens											
			40 40 Watts 5160 Lumens											
			45 45 Watts 5780 Lumens											
			2X4 Standard											
			15 15 Watts 2155 Lumens											
			21 21 Watts 3090 Lumens											
			28 28 Watts 4060 Lumens											
			30 30 Watts 4315 Lumens											
			32 32 Watts 4600 Lumens											
			35 35 Watts 5030 Lumens											
			40 40 Watts 5700 Lumens											
			48 48 Watts 6690 Lumens											
			57 57 Watts 7675 Lumens											

9. SENSOR (O) ¹	
SS	Integrated Sensor
SNS200	Occupancy Sensor w/ daylight harvesting

Notes: ¹(O) is optional

NOTE: Values shown are typical or recorded under standardized conditions at 25°C. Actual performance may vary based on environment or application. Specifications are subject to change without notice. We reserve the right to change design, materials, LED's and finish in any way that will not alter installed appearance or reduce function and performance.

