

JOB NAME:

CAT#:

TYPE:

APPLICATIONS

Introducing the Mobern PRF1-LED Premium grade enclosed and gasketed vaportight fixture. This Energy-Saving High Performance LED enclosure is ideal for both indoor and outdoor applications where dust and water resistance is required. Ideal for parking garages, cold storage, marinas, barns, canopies, car washes, poultry farms, agricultural applications and other areas susceptible to corrosive and wet conditions.

FEATURES & BENEFITS

- Single piece co-extruded lens and housing
- Lens and housing are all one piece
- Available in 2' & 4' lengths



ORDERING

EXAMPLE: PRF1 2 LED 24 DMV GY A 30

PRF1		LED		DMV		6. FINISH	
1. SERIES		2. SIZE	3. GEAR	4. WATTAGE/LUMENS	5. DRIVER		
PRF1		2 2 ft 4 4 ft	LED	<u>2ft</u> 16 16 Watts 1700 Lumens 24 24 Watts 2500 Lumens <u>4ft</u> 32 32 Watts 3300 Lumens 48 48 Watts 5000 Lumens	DMV 0-10V Dimming 120-277VAC Multivolt SDMV Step Dimming 120-277VAC 100%-40% D120 120V Dimmable D347V 347VAC 0-10V Dimmable D277 Triac Dimming 277VAC	GY Grey	
7. HOUSING MATERIAL	8. COLOR TEMP	9. SENSOR(O)¹		10. EMERGENCY(O)¹	11. CORD(O)¹		
A Acrylic	30 3000K 35 3500K 40 4000K 50 5000K	OS Occ Sensor -On/Off OSD Occ Sensor w/Dimming & Daylight Harvesting OSW Occ Sensor Wet Location OSC Occ Sensor Cold Location SS Occ Sensor Internal Microwave	EM Emergency Battery Backup	CS Cord 18/3 6"			

Notes:

¹O is Optional

NOTE: Values shown are typical or recorded under standardized conditions at 25°C. Actual performance may vary based on environment or application. Specifications are subject to change without notice. We reserve the right to change design, materials, LED's and finish in any way that will not alter installed appearance or reduce function and performance.





JOB NAME:

CAT#:

TYPE:

ACCESSORIES

- A-PRF-MB Mounting Bracket
- A-PRF-S1-SB Safety bail (order 2 per mounting bracket)
- A-PRF-AS-BLK-N ACME screw
- A-SLP-GRMT-0500 Optional wire grommet

DIMENSIONS

4'L x 3.86"W x 3.75"H

2'L x 3.86"W x 3.75"H

