

**JOB NAME:**
**CAT#:**
**TYPE:**

## APPLICATIONS

Introducing the Mobern PRF1-LED Premium grade enclosed and gasketed vaportight fixture. This Energy-Saving High Performance LED enclosure is ideal for both indoor and outdoor applications where dust and water resistance is required. Ideal for parking garages, cold storage, marinas, barns, canopies, car washes, poultry farms, agricultural applications and other areas susceptible to corrosive and wet conditions.



## FEATURES & BENEFITS

- Single piece co-extruded lens and housing
- Lens and housing are all one piece
- Available in 2', 4' & 8' lengths



## ORDERING

EXAMPLE: PRF1 2 LED 24 DMV WH A 30

PRF1		LED		DMV		6. FINISH		
1. SERIES	2. SIZE	3. GEAR	4. WATTAGE/LUMENS	5. DRIVER				
PRF1	2 2 ft	LED	<u>2ft</u>	DMV 0-10V Dimming 120-277VAC Multivolt	BK Black WH White			
	4 4 ft		16 16 Watts 1700 Lumens			SDMV Step Dimming 120-277VAC 100%-40%		
	8 8 ft		24 24 Watts 2500 Lumens				D120 120V Dimmable D347V 347VAC 0-10V Dimmable D277 Triac Dimming 277VAC	
		<u>4ft</u>						
		32 32 Watts 3300 Lumens						
		48 48 Watts 5000 Lumens	<u>8ft</u>					
		64 64 Watts 6600 Lumens	96 96 Watts 10000 Lumens					
7. HOUSING MATERIAL	8. COLOR TEMP	9. SENSOR(O) <sup>1</sup>		10. EMERGENCY(O) <sup>1</sup>	11. CORD(O) <sup>1</sup>			
A Acrylic	30 3000K	OS Occ Sensor -On/Off	OSD Occ Sensor w/Dimming & Daylight Harvesting	EM Emergency Battery Backup	CS Cord 18/3 6"			
	35 3500K	OSW Occ Sensor Wet Location	OSC Occ Sensor Cold Location					
	40 4000K	SS Occ Sensor Internal Microwave						
	50 5000K							

**Notes:**
<sup>1</sup>O is Optional

**NOTE:** Values shown are typical or recorded under standardized conditions at 25°C. Actual performance may vary based on environment or application. Specifications are subject to change without notice. We reserve the right to change design, materials, LED's and finish in any way that will not alter installed appearance or reduce function and performance.





JOB NAME:

CAT#:

TYPE:

**ACCESSORIES**

- A-PRF-MB            Mounting Bracket
- A-PRF-S1-SB        Safety bail (order 2 per mounting bracket)
- A-PRF-AS-BLK-N    ACME screw
- A-SLP-GRMT-0500   Optional wire grommet

**DIMENSIONS**

- 8'L x 3.86"W x 3.75"H
- 4'L x 3.86"W x 3.75"H
- 2'L x 3.86"W x 3.75"H

