

Texas Fluorescents Reinvented

44R SERIES

Recessed Version



A linear 4x4 recessed mounted fixture for distinctive architectural lighting plans. Ideal for corridors, lobbies and office areas, 4x4 Series fixtures can be installed individually or in group patterns. Available with flange or flangeless.

LAMP

1, or 2 lamp positions

HOUSING

Die-formed and welded 22-gauge cold rolled steel. Knockouts on ends allow continuous wireway mounting. A 1/2" regressed flange at the bottom insures uniformity and rigidity.

DIFFUSERS (not included)

Fixture accepts various lenses or louvers. 6' and 8' units have a steel mullion to join two individual diffusers.

MOUNTING

Fixtures can be recessed mounted in grid ceiling tiles or plaster with flange

SIZE W x L x H in inches 4ft. - 4" x 48" x 4" 8ft. - 4" x 96" x 4"



X1 LED

The most economical, practical and user friendly series of LED fixtures with the energy savings, quality of light, long life and hassle-free maintenance. X1 LED fixtures are UL Listed with the latest LED T8 Bypass lamps. Fixtures provide over 44% energy savings over comparable fluorescent fixtures utilizing less expensive fixtures than the fluorescent version (no ballast required) and have flexibility to change wattage and color temperature any time. Fixture performance will evolve over time with the evolution of the T8 LED lamp technology. Concerned about maintenance with an LED array and driver fixture, X1 LED solves that by utilizing a self contained LED lamp that fits into fixture just like a fluorescent lamp.

Lamp Specifcations:

Our T8 LED lamps are available in 2 or 4 ft sizes in different wattage, lumens and color temperature options. Savegreen Lighting is a premier supplier of LED T8 lamps and makes a variety of Bypass T8 lamps to meet the needs of your special application. Options include more energy efficient 12W, 15W and 17W lamps with Premium 10 Year warranty as well as high output options up to 3500 lumens. Double ended LED T8 lamps are also available. See lamp options and specs at www.savegreenlighting.com.

Optional Dimming Options:

The 4 FT lamps are available with two dimming options; Specially designed dimming lamps require an external driver that runs 1 or 2 lamps. So more than 2 lamps require multiple external drivers or Consult for Bypass Type B lamps that can be dimmed without any external driver and dim with standard 2 wire dimming. See dimming options and specs at www. saylite.com.

Emergency Options:

The standard X1 LED Lamps require an inverter or an All-in-one emergency kit that includes LED array, battery and driver. Dimmable T8 LED with external driver works with standard LED EM. For a 5 watt inverter that is similar to adding a 500 Lumen emergency in a conventional fluorescent fixture, add "INV5W" to the end of the item number. This will allow 5 watts of one lamp to work in emergency mode. Or add "EMKT12" to the end of the item number to get a 12W stand alone emergency kit in the fixture that comes with a driver, battery and small LED array that works in Emergency mode. See emergency options and specs at www.saylite.com.





Note: In order for UL safety certification to be valid, only approved lamps may be installed in the fixture and must be shipped with the fixture from the factory.





Texas Fluorescents

Reinvented

Ordering Options

(Fixtures below include LED T8 Lamp LT8ABP48L18W2250LXXK. For Other Lamp Options See below and Replace LNXXX with short code below. Specifiy without Lamps by removing LNXXX)

ITEM NO.	DESCRIPTION
44RSF117X1WHLN15W40K	4" x 24" 1700 Lumen Recessed 1x 15W LED T8 4000K Lamps Included
44RSF217X1WHLN15W40K	4" x 24" 3400 Lumen Recessed 2x 15W LED T8 4000K Lamps Included
44RSF132X1WHLN18W40K	4" x 48" 2100 Lumen Recessed 1x 18W LED T8 4000K Lamps Included
44RSF232X1WHLN18W40K	4" x 48" 4200 Lumen Recessed 2x 18W LED T8 4000K Lamps Included
44RSF1328X1WHLN18W40K	4" x 96" 4200 Lumen Recessed 2x 18W LED T8 4000K Lamps Included
44RSF2328X1WHLN18W40K	4" x 96" 8400 Lumen Recessed 4x 18W LED T8 4000K Lamps Included

Change 40 to 35 or 50 for different Kelvin. Change Lamp Wattage to 13W on 2FT or 15W on 4FT Change SF (Snap Fit Frosted Lens) to MW for Matte White Regressed Lens For Baffled Louver, change MW to BL

For 5W Emergency, Add INV5 at the End of Item Number for KTEMRGLED5500AC. See other options at www.saylite.com
For fixtures wired for double ended lamps, change X1 to X2 and see the Savegreen Lamps below for the proper Double Ended Lamp. For fixtures without lamps included, remove the "LNXXX" at the end of the item number and have X1 or X2 for Single or Double Ended wiring.

LN18W40 - Lamp Specification

50,000 Hour Life with 5 Year Warranty

Beam Angle 140 Degree

Aluminum Base and Aluminum Housing with Glass Cover

Operating Temperature: - 20C to 50C Color Temperature: 3500K, 4000K, 5000K G13 Pins (Same as Fluorescent Linear T8 Bipin)

AC100 - 277V without Ballast

Single Ended or Double Ended Power (If not specified use X1 Single Ended Power)

Savegreen T8 or T5 LED Lamp Options

To include one of these lamps in fixture, remove "LNXXX" and add Savegreen Inside code below. (See www.savegreenlighting.com for specification sheets or more information on these lamp options.)

VERSION	SAVEGREEN INSIDE	SAVEGREEN ITEM NO.	
Popular	SGB15W35	LT8BG48L15W1740LXXK	
Standard	SGS29W35	LT8BGC24L9W1050LXXK	
Standard	SGS312W35	LT8BGC36L12W1200LXXK	
Standard	SGS15W35	LT8BGC48L15W1740LXXK	
Premium	SGP12W35	L10T8BGC48L12W1750LXXK	
Premium	SGP15W35	L10T8BGC48L15W2000LXXK	
Premium	SGP18W35	L10T8BGC48L18W2500LXXK	
High Output	SGH26W40	LT8BGC48L26W3500LXXK	
Double Ended	SGD18W35	LT8BDGC48L18W2100LXXK	
Т5НО	SGT525W40*	LT5BG46L25W3300LXXK	
Magic	SGM18W35K	LT8ABP48L18W2250LXXK	
Magic	SGM18W35K	LT8ABP48L15W1875LXXK	
Magic	SGM215W35K	LT8ABP24L15W1875LXXK	

WARRANTY

I SG

Change 35 to 40 or 50 for different Kelvin. *For T5, CCT 40K and 50K available.

Note: In order for UL safety certification to be valid, only approved lamps may be installed in the fixture and must be shipped with the fixture from the factory.

Saylite	, Texas	Fluor	esce	nts Reinve	ented
2055 L	una Rd.	Suite	142	Carrollton,	TX 75006

Phone: 972-247-3171 Fax: 972-247-0200 www.saylite.com email: sales@saylite.com

Catalog Number:	
Notes:	