



# LVS6 SERIES

## Modern Louvered Industrial Strip



A direct/indirect lighting fixture that makes a bold statement, complementing design elements such as stone, metal, brick and glass. Industrial look provides a modern aesthetic. Available with slots in reflector for indirect light or solid reflector. Available standard in galvanized steel finish or powder coated black. Mounts with cable kit. Louver is matte silver anodized parabolic.

**SIZE** W x L x H in inches (mm)  
8.0W x 49.0L x 6.5H

**LAMP**  
2 lamp positions, Available in T8 and T5

**HOUSING**  
Die-formed cold rolled steel body with heavy duty construction. Mates with Parabolic louver.

**LOUVER**  
Matte silver anodized, parabolic. with optional slots on the side of louver. End cap complete the finished louvered look.

**MOUNTING**  
Fixtures can be surface mounted to the ceiling or pendant hung by stem or cable. Welded heavy gauge steel flanges can be ordered to accept 3/8" threaded stems. Alignment brackets are available for continuous row mounting

### X1 LED

The most economical, practical and user friendly series of LED fixtures with the energy savings, quality of light, long life and hassle-free maintenance. X1 LED fixtures are UL Listed with the latest LED T8 Bypass lamps. Fixtures provide over 44% energy savings over comparable fluorescent fixtures utilizing less expensive fixtures than the fluorescent version (no ballast required) and have flexibility to change wattage and color temperature any time. Fixture performance will evolve over time with the evolution of the T8 LED lamp technology. Concerned about maintenance with an LED array and driver fixture, X1 LED solves that by utilizing a self contained LED lamp that fits into fixture just like a fluorescent lamp.

### Lamp Specifications:

Our T8 LED lamps are available in 2 or 4 ft sizes in different wattage, lumens and color temperature options. See lamp options and specs at [www.texasfluorescents.com/X1LEDLamps](http://www.texasfluorescents.com/X1LEDLamps).

- 50,000 Hour Life with 5 Year Warranty
- Beam Angle 140 Degree
- Aluminum Base and Aluminum Housing with Glass Cover
- Operating Temperature: - 20C to 50C
- Color Temperature: 3500K, 4000K, 5000K
- G13 Pins (Same as Fluorescent Linear T8 Bipin)
- AC100 – 277V without Ballast
- Single Ended or Double Ended Power (If not specified use X1 Single Ended Power)

### Optional Dimming Options:

The 4 FT lamps are available with a dimming option. Specially designed dimming lamps require an external driver that runs 1 or 2 lamps. So more than 2 lamps require multiple external drivers. See dimming options and specs at [www.texasfluorescents.com/X1LEDdimming](http://www.texasfluorescents.com/X1LEDdimming).

### Emergency Options:

The standard X1 LED Lamps require an inverter or an All-in-one emergency kit that includes LED array, battery and driver. Dimmable T8 LED with external driver works with standard LED EM it. See emergency options and specs at [www.texasfluorescents.com/X1LEDemergency](http://www.texasfluorescents.com/X1LEDemergency).

ITEM NO.	DESCRIPTION
LVS6232X1WHLN18W40-HC301WH	48" LVS WHITE 4200 Lumen 2x18W LED T8 4000K Lamps included w/5 ft cable kit
LVS62328X1WHLN18W40-HC401WH	96" LVS WHITE 8400 Lumen 4x18W LED T8 4000K Lamps included w/5 ft cable kit

Change 40 to 35 or 50 for different Kelvin. Change Lamp Wattage to 15W on 2FT or 15W on 4FT  
Change WH TO BK (Black), IR (Iron), SL (Silver) or BR (Bronze)



**Note: In order for UL safety certification to be valid, only approved lamps may be installed in the fixture and must be shipped with the fixture from the factory.**

Saylite  
2055 Luna Rd. Suite 142 Carrollton, TX 75006  
Phone: 972-247-3171 Fax: 972-247-0200  
[www.saylite.com](http://www.saylite.com) email: [sales@saylite.com](mailto:sales@saylite.com)

Catalog Number:
Notes: