



**JOB NAME:**

**CAT#:**

**TYPE:**

## APPLICATIONS

Provides general illumination in residential, institutional, and commercial interiors. Ideal for use in kitchens, office, utility areas or closets. Crown molding frame available in oak or white finish. Specially formed plastic diffuser produces flawless light source with even illumination on all sides and no distracting dark spots. Invisible hanging clips permit removal of lens from either side.

- Bracket and single screw frame
- 2 or 4 lamp positions
- May be surface or pendant mounted

The most economical, practical, and user friendly series of LED fixtures with energy savings, quality of light, long life and hassle-free maintenance/ EZLED fixtures are UL listed with the latest LED T8 bypass lamps. These fixtures provide over 44% energy savings over comparable fluorescent fixtures utilizing less expensive fixtures than the fluorescent version (no ballast required). They also provide the flexibility to change the wattage and color temperature at any time. Are you concerned about maintenance with an LED array and driver fixture? EZLED resolves that issue by utilizing a self-contained LED lamp that fits into your fixture just like the classic fluorescent tube. The fixture performance will evolve over time with the evolution of the T8 LED lamp technology, and our five-year warranty guarantees a reliable, high quality product.



## FEATURES & BENEFITS

Our EZLED fixtures come standard with SaveGreen T8 LED lamps. They are available in 2 or 4 foot sizes in different wattage, lumens, and color temperature options (see lamp options and specifications at [www.savegreenlighting.com](http://www.savegreenlighting.com)).

- $L_{70} > 50,000$  hrs.
- Operating temperature: -20°C to 50°C
- Color Temperature: 3500K, 4000K, 5000K
- G13 pins (same as fluorescent linear T8 bipin)
- AC100-277V
- Integral driver (non-isolated) eliminates the need for external driver or ballast
- Environmentally friendly, no mercury used
- UL Classified
- Min CRI 80
- 5 year warranty

## DIMENSIONS

25.0W x 25.0L x 4.125Dp  
11.5W x 48.875L x 4.125Dp  
16.75W x 48.875L x 4.125Dp

### Emergency Options

The standard EZ LED Lamps require an inverter or an All-in-one emergency kit that includes LED array, battery and driver. Dimmable T8 LED with external driver works with standard LED EM it. See emergency options and specs at [www.mobern.com/EZLEDemergency](http://www.mobern.com/EZLEDemergency).

### Optional Dimming

The 4 foot lamps are available with a dimming option. Specially designed dimming lamps require an external driver that runs 1 or 2 lamps (more than 2 lamps require multiple external drivers).

**Note: In order for UL safety certification to be valid, only approved lamps may be installed in the fixture and must be shipped with the fixture from the factory.**





JOB NAME:

CAT#:

TYPE:

**ORDERING**

EXAMPLE: CWN 14 2 17 LEDL15W WH MW 830 WP INV5

**CWN**

1. SERIES	2. SIZE	3. # OF LAMPS	4. LAMPT TYPE	5. WATTAGE/LUMENS	6. FINISH	7. LENS
CWN	14 1x4	2 2 Lamps	17 24 inch T8	<b>T8 Options</b> <u>2 ft.</u> <b>LEDL15W</b> 9 Watts 1050 Lumens <u>Keystone</u> <u>4 ft.</u> <b>LEDL15W</b> 15 Watts 1740 Lumens <u>Keystone</u> <b>LEDL18W*</b> 18 Watts 2500 Lumens <b>T5 Options</b> <b>LEDL25W</b> 25 Watts 3300 Lumens	<b>WH</b> White <b>GO</b> Golden Oak <b>UF</b> Unfinished <b>BW</b> Bleached White	<b>MW</b> Matte White Acrylic
	22 2x2	3 3 Lamps	32 32 inch T8			
	24 2x4	4 4 Lamps	54 46 inch T5HO			
	3 and 4 lamp options not available in 1x4					

8. COLOR TEMP	9. CORD(O) <sup>2</sup>	10. INVERTER(O) <sup>2</sup>
830 3000K	<b>WP</b> 6' Whip, 3 Wire	<b>INV5</b> 5W Integrated Inverter
835 3500K		
840 4000K		
850 5000K		

**NOTES:**

<sup>1</sup>Special Tube

<sup>2</sup>O is optional

Dimensions and specifications subject to change without notice.



**Note: In order for UL safety certification to be valid, only approved lamps may be installed in the fixture and must be shipped with the fixture from the factory.**