



JOB NAME:

CAT#:

TYPE:



The most economical, practical, and user friendly series of LED fixtures with energy savings, quality of light, long life and hassle-free maintenance/ EZLED fixtures are UL listed with the latest LED T8 bypass lamps. These fixtures provide over 44% energy savings over comparable fluorescent fixtures utilizing less expensive fixtures than the fluorescent version (no ballast required). The also provide the flexibility to change the wattage and color temperature at any time. Are you concerned about maintenance with an LED array and driver fixture? EZLED resolves that issue by utilizing a self-contained LED lamp that fits into your fixture just like the classic fluorescent tube. The fixture performance will evolve over time with the evolution of the T8 LED lamp technology, and our five-year warranty guarantees a reliable, high quality product.

Lamp Specifications

Our EZLED fixtures come standard with SaveGreen T8 LED lamps. They are available in 2 or 4 foot sizes in different wattage, lumens, and color temperature options (see lamp options and specifications at www.savegreenlighting.com).

- $L_{70} > 50,000$ hrs.
- Operating temperature: -20°C to 50°C
- Color Temperature: 3500K, 4000K, 5000K
- G13 pins (same as fluorescent linear T8 bipin)
- AC100-277V
- Integral driver (non-isolated) eliminates the need for external driver or ballast
- Environmentally friendly, no mercury used
- UL Classified
- Min CRI 80
- 5 year warranty

Optional Dimming

The 4 foot lamps are available with a dimming option. Specially designed dimming lamps require an external driver that runs 1 or 2 lamps (more than 2 lamps require multiple external drivers).

Emergency Options

The standard EZLED lamps require an inverter or an all-in-one emergency kit that includes LED array, battery, and driver. Dimmable T8 LED with external driver works with standard LED EM in it.

A direct/indirect lighting fixture that makes a bold statement by complementing design elements such as stone, metal, brick and glass. Industrial look provides a modern aesthetic. Available standard in white finish with matte silver anodized parabolic louver. Mounts with cable kit.

- Available standard in white, black, or silver finish
- Surface or pendant mounted
- Matte silver anodized parabolic louver
- 5 year warranty

CONSTRUCTION

The Housing is Die-formed cold rolled steel body with heavy duty construction. Mates with Parabolic louver which is a silver anodized, parabolic with optional slots on the side of louver. End cap completes the finished louvered look.

SIZE L x W x H in inches

48.0"L x 6.0"W x 5.25"H

96.0"L x 6.0"W x 5.25"H



Note: In order for UL safety certification to be valid, only approved lamps may be installed in the fixture and must be shipped with the fixture from the factory.



JOB NAME:

CAT#:

TYPE:

ORDERING

EXAMPLE: DLV6 2 32TAN LEDL7W BK 40 KEY H12W5

DLV6

1. SERIES	2. # OF LAMPS	3. LAMP TYPE	4. LAMP WATTAGE	5. FINISH	6. COLOR TEMP	
DLV6	1	1 Lamp				
	2	2 Lamps				
			32 48" T8	T8 Options	WH White	30 3000K
			54 48" T5HO*	2ft.	BK Black	35 3500K
			32TAN 48" Tandem T8	LEDL7W 7 Watts 950 Lumens	SI Silver	40 4000K
				LEDL9W 9 Watts 1050 Lumens		50 5000K
				4ft.		
			54TAN 46" Tandem T5HO ¹	LEDL12W 12.5 Watts 1750 Lumens		
				LEDL15W 15 Watts 1740 Lumens		
				LEDL18W 18 Watts 2500 Lumens		
			T5 Options			
			LEDL25W 25 Watts 3300 Lumens			

7. LAMP BRAND

Blank House Brand (Savegreen)
KEY Keystone
JAM James Brand (Special Order)

8. HANGING KIT(O)²

H4W5 Cable kit with 4' Cable & 5 wire Power Feed/Cable Incl. and White Canopy
H12W5 Cable Kit with 12' Cable and 5 wire Power Feed/Cable Incl. and White Canopy
2SCS24WH Two Stem Kits with 24" Stem, Canopy and Mounting hardware for a 4' fixture

9. INVERTER(O)²

INV5 5W Integrated Inverter

NOTES:

¹Only Available in 840 & 850

²O is optional

Dimensions and specifications subject to change without notice.



Note: In order for UL safety certification to be valid, only approved lamps may be installed in the fixture and must be shipped with the fixture from the factory.