



JOB NAME:

CAT#:

TYPE:

## APPLICATIONS

A linear 6x6 surface mounted fixture for distinctive architectural lighting plans. Ideal for corridors, lobbies and office areas, 6x6 fixtures can be installed individually or in group patterns. UL listed for damp locations.

### CONSTRUCTION

Die-formed and welded cold rolled steel. Knockouts on ends allow continuous wireway mounting. A 1/2" regressed flange at the bottom insures uniformity and rigidity. Uplight fixtures have two rows of 1/2" x 4" apertures along the top of the housing to provide approximately 12% uplight for ceiling illumination. Fixtures can be surface mounted to the ceiling, pendant hung by stem, cable, or wall mounted. Welded heavy gauge steel flanges can be ordered to accept 3/8" threaded stems. Alignment brackets are available for continuous row mounting. Fixtures can be mounted flush against the wall or hung with wall brackets measuring 4 1/2" square by 1" deep. Two brackets are used on 2, 3 and 4 foot fixtures and 2 or 3 brackets for 6 and 8 foot fixtures as required.



The most economical, practical, and user friendly series of LED fixtures with energy savings, quality of light, long life and hassle-free maintenance/ EZLED fixtures are UL listed with the latest LED T8 bypass lamps. These fixtures provide over 44% energy savings over comparable fluorescent fixtures utilizing less expensive fixtures than the fluorescent version (no ballast required). They also provide the flexibility to change the wattage and color temperature at any time. Are you concerned about maintenance with an LED array and driver fixture? EZLED resolves that issue by utilizing a self-contained LED lamp that fits into your fixture just like the classic fluorescent tube. The fixture performance will evolve over time with the evolution of the T8 LED lamp technology, and our five-year warranty guarantees a reliable, high quality product.

## FEATURES & BENEFITS

Our EZLED fixtures come standard with SaveGreen T8 LED lamps. They are available in 2 or 4 foot sizes in different wattage, lumens, and color temperature options (see lamp options and specifications at [www.savegreenlighting.com](http://www.savegreenlighting.com)).

- $L_{70} > 50,000$  hrs.
- Operating temperature: -20°C to 50°C
- Color Temperature: 3500K, 4000K, 5000K
- G13 pins (same as fluorescent linear T8 bipin)
- AC100-277V
- Integral driver (non-isolated) eliminates the need for external driver or ballast
- Environmentally friendly, no mercury used
- UL Classified
- Min CRI 80
- 5 year warranty

### Emergency Options

The standard EZ LED Lamps require an inverter or an All-in-one emergency kit that includes LED array, battery and driver. Dimmable T8 LED with external driver works with standard LED EM it. See emergency options and specs at [www.mobern.com/EZLEDemergency](http://www.mobern.com/EZLEDemergency).

### Optional Dimming

The 4 foot lamps are available with a dimming option. Specially designed dimming lamps require an external driver that runs 1 or 2 lamps (more than 2 lamps require multiple external drivers).

## DIMENSIONS

- 2ft - 6"W x 24"L x 6"H
- 4ft - 6"W x 48"L x 6"H
- 8ft - 6"W x 96"L x 6"H



**Note: In order for UL safety certification to be valid, only approved lamps may be installed in the fixture and must be shipped with the fixture from the factory.**



JOB NAME:

CAT#:

TYPE:

**ORDERING**

EXAMPLE: L66 R 117 LEDL7W S5 830 HC301WH P11

**L66**

1. SERIES	2. MOUNTING	3. # OF LAMPS	4. LAMP TYPE	5. LAMP WATTAGE	6. FINISH
<b>L66</b>	<b>R</b> Regular recess lay-in	<b>1</b> 1 Lamp	<b>17</b> 24 inch T8	<b>T8 OPTIONS</b> <b>2 ft.</b> <b>LEDL7W</b> 7 Watts 950 Lumens <u>Keystone</u>	<b>Blank</b> For recessed <b>WH</b> White <b>BK</b> Black <b>SL</b> Silver <b>IN</b> Iron <b>BZ</b> Bronze
	<b>RF</b> Recessed with flange*	<b>2</b> 2 Lamps	<b>25</b> 36 inch T8		
	<b>RR</b> Recessed for dry wall 1/2"		<b>25TAN</b> 72 inch T8 - 36"		
	<b>S</b> Surface/pendant (direct only)		<b>32</b> 48 inch T8		
	<b>SI</b> Surface/pendant (indirect only)		<b>32TAN</b> 96 inch T8 - 2-48		
	<b>SDI</b> Surface/pendant direct w/ indirect slots)		<b>54<sup>1</sup></b> 46 inch T5HO		
	<b>WI</b> Wall mount indirect only			<b>3 ft.</b> <b>LEDL9W</b> 9 Watts 1050 Lumens <u>Keystone</u> <b>4 ft.</b> <b>LEDL12W</b> 12 Watts 1250 Lumens <u>Keystone</u> <b>LEDL12W</b> 12.5 Watts 1750 Lumens <u>Keystone</u> <b>LEDL15W</b> 15 Watts 1740 Lumens <b>LEDL18W</b> 18 Watts 2500 Lumens <b>T5 OPTIONS</b> <b>LEDL25W</b> 25 Watts 3300 Lumens	
	<b>WDI</b> Wall mount direct w/indirect slots				
	<b>W</b> Wall mount direct only				

7. LENS OPTIONS	8. COLOR TEMP	9. LAMP BRAND	10. REFLECTOR(O) <sup>3</sup>	11. CABLE(O) <sup>3</sup>	12. PLUG IN OPTIONS(O) <sup>3</sup>
<b>S5</b> Specular parabolic louver 1/2"x 1/2"x3/8"	<b>830</b> 3000K <b>835</b> 3500K <b>840</b> 4000K <b>850</b> 5000K	<b>Blank</b> House Brand <b>KEY</b> Keystone Brand <b>JAM</b> James Brand <sup>2</sup>	<b>Blank</b> Standard <b>WW</b> Wall Wash	<b>HC301WH</b> 4' cable kit with white canopy <b>HC302WH</b> 12' cable kit with white canopy	<b>P11</b> 3 wire harness, including white, black and green <b>P12</b> 4 wire harness, including white, black, green and blue for emergency backup <b>P13D</b> 5 wire harness, including white, black, green, violet and gray <b>INV5</b> 5W Integrated Inverter
<b>A</b> Prismatic acrylic #12 pattern					
<b>MW</b> Smooth white .100 thick lens standard					
<b>SF</b> Snap-in frosted lens					
<b>LV</b> Baffled Louver					

**NOTES:**

<sup>1</sup>Only Available in 840 & 850  
<sup>2</sup>Special Order  
<sup>3</sup>O is optional

Lumens are subject to a tolerance of ±10% and not relevant to RGB  
Input wattage can vary depending on options  
Dimensions and specifications subject to change without notice.



**Note: In order for UL safety certification to be valid, only approved lamps may be installed in the fixture and must be shipped with the fixture from the factory.**